

CITY OF BLOOMINGTON



May 23, 2024 @ 5:30 p.m.
City Hall, 401 N. Morton Street
Common Council Chambers, Room #115

<https://bloomington.zoom.us/j/82448983657?pwd=enJxcnArK1pLVDI nWGROTU43dEpXdz09>

Meeting ID: 824 4898 3657
Passcode: 319455

**CITY OF BLOOMINGTON
BOARD OF ZONING APPEALS (Hybrid Meeting)**

City Hall, 401 N. Morton Street
Common Council Chambers, Room #115 and via Zoom

May 23, 2024 at 5:30 p.m.

❖ **Virtual Meeting:**

<https://bloomington.zoom.us/j/82448983657?pwd=enJxcnArK1pLVdInWGROTU43dEpXdz09>

Meeting ID: 824 4898 3657

Passcode: 319455

Petition Map: <https://arcg.is/1aHCbe>

ROLL CALL

APPROVAL OF MINUTES: April 18, 2024

PETITIONS CONTINUED TO: June 20, 2024

- AA-17-22 **Joe Kemp Construction, LLC & Blackwell Construction, Inc.**
Summit Woods (Sudbury Farm Parcel O) W. Ezekiel Dr.
Parcel(s): 53-08-07-400-008.002-009, 53-08-07-400-008.004-009...
Request: Administrative Appeal of the Notice of Violation (NOV) issued
March 25, 2022. Case Manager: Jackie Scanlan
- V-27-22 **Cutters Kirkwood 123, LLC**
113 E. Kirkwood Ave.
Parcel: 53-05-33-310-062.000-005
Request: Variances from Downtown Character Overlay standards to allow less
non-residential area and less large display windows; and a variance from the
requirement to align with the front setback of an adjacent historic structure in the
Mixed-Use Downtown zoning district with the Courthouse Square Character
Overlay (MD-CS). Case Manager: Jackie Scanlan
- V-05-24 **Candi Sipes**
2303 S Rockport Road
Parcel: 53-01-51-137-500.000-009
Request: Variances from accessory structure size standards, accessory structure
setbacks, driveway width standards, and a determinate sidewalk variance to
allow construction of a new single-family dwelling structure in the Residential
Medium Lot (R2) zoning district. Case Manager: Gabriel Holbrow

****Next Meeting: June 20, 2024**

The City is committed to providing equal access to information. However, despite our efforts, at times, portions of our board and commission packets are not accessible for some individuals. If you encounter difficulties accessing material in this packet, please contact Melissa Hirtzel at hirtzelm@bloomington.in.gov and provide your name, contact information, and a link to or description of the document or web page you are having problems with.

V-08-24 **Andrew Huck**
 2226 East Maxwell Lane
 Parcel: 53-08-03-100-002.000-009
 Request: Variance from riparian buffer standards to allow construction of deck stairs and terrace for an existing single-family dwelling in the Residential Medium Lot (R2) zoning district. Case Manager: Gabriel Holbrow

PETITIONS:

V-10-24 **Ruby Creek Homes**
 914 N. Oolitic Drive
 Parcel(s): 53-05-32-201-076.057-005
 Request: Variance from the Karst Geology standards to allow the construction of single-family homes in the Residential Medium Lot (R2) zoning district.
Case Manager: Katie Gandhi

V-13-24 **Ruby Creek Homes**
 918 N. Oolitic Drive
 Parcel(s): 53-05-32-201-106.058-005
 Request: Variance from the Karst Geology standards to allow the construction of single-family homes in the Residential Medium Lot (R2) zoning district.
Case Manager: Katie Gandhi

V-14-24 **Ruby Creek Homes**
 922 N. Oolitic Drive
 Parcel(s): 53-05-32-201-077.059-005
 Request: Variance from the Karst Geology standards to allow the construction of single-family homes in the Residential Medium Lot (R2) zoning district.
Case Manager: Katie Gandhi

V-15-24 **Sarah Nelson**
 803 E. Winslow Road
 Parcel: 53-08-09-400-002.000-009
 Request: Variance from fence height standards in the Residential Small Lot (R3) zoning district. Case Manager: Katie Gandhi

V-16-24 **BPO Elks #446**
 400 N. Walnut St
 Parcel: 53-05-33-306-003.000-005
 Request: Variance from front yard setback requirements for a flag pole in the Mixed-Use Downtown (MD) within the Downtown Core Overlay (DCO) zoning district. Case Manager: Eric Greulich

CU-17-24 **Bloomington Builders, LLC & Latitude 39 North Properties, LLC**
 506 E. Wylie Street
 Parcel: 53-08-04-113-095.000-009
 Request: Conditional Use approval to allow a duplex in the Residential Lot (R3) zoning district. Case Manager: Eric Greulich

****Next Meeting: June 20, 2024**

The City is committed to providing equal access to information. However, despite our efforts, at times, portions of our board and commission packets are not accessible for some individuals. If you encounter difficulties accessing material in this packet, please contact Melissa Hirtzel at hirtzelm@bloomington.in.gov and provide your name, contact information, and a link to or description of the document or web page you are having problems with.

Auxiliary aids for people with disabilities are available upon request with adequate notice. Please call [812-349-3429](tel:812-349-3429) or E-mail human.rights@bloomington.in.gov.

****Next Meeting: June 20, 2024**

The City is committed to providing equal access to information. However, despite our efforts, at times, portions of our board and commission packets are not accessible for some individuals. If you encounter difficulties accessing material in this packet, please contact Melissa Hirtzel at hirtzelm@bloomington.in.gov and provide your name, contact information, and a link to or description of the document or web page you are having problems with.

**BLOOMINGTON BOARD OF ZONING APPEALS
STAFF REPORT****CASE #: V-10-24/VAR-2024-03-0028
DATE: May 23, 2024****Location: 914 N Oolitic Dr (parcel #53-05-32-201-076.057-005) (Lot 57 of Forest Homes)**

PETITIONER: Ruby Creek Homes
11990 E 1400 N, Oden, IN 47562**CONSULTANTS:** Melvin Graber
11990 E 1400 N, Oden, IN 47562

REQUEST: Variance from Karst Preservation standards to allow disturbance within 25' of the last closed contour of a karst feature for a property in the Residential Medium Lot (R2) zoning district.

REPORT: This 0.2-acre property is located at 914 N Oolitic Dr. The property is zoned Residential Medium Lot (R2). Surrounding zones are all Residential Medium Lot (R2) and surrounding land uses are all Dwelling, Single Family (detached).

Previous to the current owner, this lot of record, along with the Forest Homes Lots 58 and 59 (918 and 922 N Oolitic), were owned by the same owner and two mobile homes sat on all three lots for many years.

There is a karst feature, a sinkhole, located on this property. Existing elevations on this site range from 874 feet to 878 feet. There is currently no stormwater infrastructure at or near this site.

Chapter 4 of the Unified Development Ordinance (UDO), Title 20 of the Bloomington Municipal Code) states that no land-disturbing activity, mowing, or temporary or permanent structure shall be allowed within the sinkhole nor within 25 feet of the last closed contour of the sinkhole. Title 20 of the UDO defines the sinkhole as the last closed contour line of the feature on the City's geographic information system. Historic contour mapping shows that this entire property located at 914 N Oolitic falls within the last closed contours of the karst feature, which is at an elevation of 882 feet, which means that according to the UDO, the entire lot cannot be disturbed. Since this entire site lies within the area shown to be within the last closed contour of the karst feature, a variance must be granted to allow any disturbance on this property.

The petitioner is requesting a variance from the karst preservation standards to allow disturbance within 25' of the last closed contour of the karst feature.

As part of this variance request, a report of geotechnical engineering exploration was submitted. The report confirmed that a sinkhole is present on the site and it provided information about soil composition in two locations on this property through analysis of soil borings. The report also provided sinkhole remediation methods of treatment and construction recommendations for placing a single family structure on the site.

CRITERIA AND FINDINGS FOR DEVELOPMENT STANDARDS VARIANCE
20.06.080(b)(3)(E) Standards for Granting Variances from Development Standards:

A variance from the development standards of the Unified Development Ordinance may be approved only upon determination in writing that each of the following criteria is met:

- 1) *The approval will not be injurious to the public health, safety, morals, and general welfare of the community.*

PROPOSED FINDING: The granting of the variance will not be injurious to the public health, safety, morals, or general welfare of the community. A number of structures have existed in and around this karst feature for many years with no collapse. Proper testing of and restoration of the site will be required before building construction is allowed in order to maximize water infiltration on the site and ensure that water is not diverted off site, and to make sure that the site is safe for construction.

- 2) *The use and value of the area adjacent to the property included in the Development Standards Variance will not be affected in a substantially adverse manner.*


PROPOSED FINDING: No adverse impacts to the use and value of surrounding properties as a result of the requested variance are found. The majority of this property is located four feet in elevation higher than the apparent lowest point of the property. Current site elevation conditions show that the portions of the karst feature that are most sensitive are found on the adjacent property to the north of this property. With the remediation of the sinkhole, drainage analysis and the installation of drainage solutions, impact to surrounding properties should be mitigated.

- 3) *The strict application of the terms of the Unified Development Ordinance will result in practical difficulties in the use of the property; that the practical difficulties are peculiar to the property in question; that the Development Standards Variance will relieve the practical difficulties.*

PROPOSED FINDING: The strict application of the terms of the Unified Development Ordinance will result in practical difficulties in the use of the property because it renders the entire site unbuildable. There has been development within the last closed contour of this feature for a number of years without any indications of negative impact. The practical difficulties are peculiar to the property in question because it is uncommon for an entire property to be located within a UDO-defined sinkhole, but because the properties in this area are smaller, the extent of the last closed contour of the sinkhole renders the entire site unbuildable.


RECOMMENDATION: The Department recommends that the Board of Zoning Appeals adopt the proposed findings and approve **V-10-24/ VAR-2024-03-0028, with the following conditions:**


1. Development of the lot is limited to the east half of the lot, beyond the 876 contour line, in order to maximize the area of land present between development and movement of water toward the sinkhole on the adjacent lot to the north.
2. Implementation of sinkhole remediation as outlined in the attached geotechnical report, is required – at all three properties (914, 918 and 922 N Oolitic) - before any Certificate of Zoning Compliances will be issued.
3. Submission of a drainage and water flow analysis post-sinkhole remediation is required before a Certificate of Zoning Compliance will be issued. The report must be approved by City of Bloomington Planning & Transportation and Utility Departments.
4. Implementation of design and construction recommendations provided in the attached geotechnical report is required before a Certificate of Zoning Compliance will be issued.
5. Soil and water contamination testing and provision of any necessary remediation identified related to those tests is required before a Certificate of Zoning Compliance will be issued.
6. A Zoning Commitment shall be recorded indicating the presence of the karst feature and describing the Karst Conservancy Easement before a Certificate of Zoning Compliance will be issued.
- 7.








Map Legend


- Addresses
- Parcels
- Sinkholes
- Contours 2021
- Bloomington Municipal Boundary
- Planned Unit Development
- Residential Medium Lot
- Mixed-Use Employment






Map Legend

-  Addresses
-  Parcels
-  Sinkholes
-  Contours 2021
-  Bloomington Municipal Boundary





10

1503

913

907

last closed contour of sinkhole

25 feet

926

922

918

914

N Oolitic Dr

N Oolitic Dr

N Oolitic

892



911

907

905

903


last closed contour of sinkhole



TOWNSHIP: Bloomington, Section 32
 DESCRIPTION: Lot 57, Forest Homes

USE: Single Family Residential
 PARKING PLAN: 2 parking spaces/unit required

OWNER ADDRESS:
 11990 E. 1400 N.
 ODON, IN 47562



Prepared by:

C.D. Graham

Charles D. Graham
 Registration No. LS29500014

I affirm under penalties of perjury that I have taken reasonable care to redact each social security number in this document, unless required by law.



BYNUM FANYO & ASSOCIATES, INC.
 528 North Walnut Street
 Bloomington, Indiana 47404
 Phone (812)332-8030 Fax (812)339-2990

(LOT 71)


(LOT 72)

(LOT 73)

(LOT 58)

(LOT 56)

staff note: these plans will likely need to change according to any variance conditions that are approved -KAG



NOTE:
 BUILDER TO GRADE LOT TO
 PROVIDE ADEQUATE DRAINAGE
 AWAY FROM BUILDING

NOTE:
 See Architectural Plans for house dimensions.

NOTES:
 This plot plan complies with Chapter 802-4
 This plot plan complies with the
 requirements under Chapter 815, including
 positive drainage away from the structure
 are shown as compliant.

PLOT PLAT FOR PARCEL #53-05-32-201-076.057-005
 914 North Oolitic Drive, Bloomington, IN 47408
 Lot 57, Forest Homes Addition
 RUBY CREEK HOMES, LLC.

Date:10/23/2023

Project No: 5023089

To Whom it may concern,

Ruby Creek Homes LLC (RCH) is requesting a variance from code UDO 20.04.030 (g) Pursuant to Indiana Code 36-7-4-918.5.

Project Location

914, 918, 922 N Oolitic Dr.

(See Attached Survey)

Scope of Project

In 2023, 2 deteriorated homes were removed from said properties (Demo Permit #s R-23-610, R-23-612) for the:

Purpose of

New Home Construction

See Attached Site Plan

Difficulties

The strict application of UDO 20.04.030 (g) renders the entire properties undevelopable, for which use it was previously intended.


See Attached - Forrest Homes Development Recording 1927

Granting the requested variance would:

Improve neighboring Property values

And would be an asset rather than a liability to public health safety and general welfare of the community by providing much needed and deficient "Affordable Housing".

staff note: these plans will likely need to change according to any variance conditions that are approved -KAG




Camera 1

08/14/2023 10:00 AM
COURTESY OF THE CITY OF CEDAR RAPIDS
DESIGNED BY: KEN WAGLER
DRAWING NO: 2023-001
DATE: 10/2/2023
SCALE: 1/8" = 1'-0"
SHEET: P-1

DRAWINGS PROVIDED BY:
Ken Wagler
8227 N 725 E
Oden IA 52522
812-486-4328
khwagler88@sic.e-mail

Project Overview

New Plans For.....
Cedar 4 Bedrooms



LIVING AREA
1524.56 SQ. FT.

1st Floor

FRAMING NOTES


- ALL EXTERIOR WALLS ARE SHOWN AS 4" WALLS UNLESS NOTED OTHERWISE
- ALL INTERIOR WALLS ARE SHOWN AS 5 1/2" WALLS UNLESS NOTED OTHERWISE
- 4" 1/2" WALLS UNLESS NOTED OTHERWISE
- ALL EXTERIOR WINDOW HEIGHTS TO TOP OF WINDOW SILL UNLESS NOTED OTHERWISE
- ALL WINDOW E.O. INCLUDED FOR SILVERLINE WINDOWS
- ALL HEADER HEIGHTS AT 8" UNLESS NOTED OTHERWISE

ONE PLAN & APPROXIMATE ONE FLOOR
CONSTRUCTION OF THE PROJECT IS
CONSIDERED TO BE A RESIDENTIAL
CONSTRUCTION PROJECT. THE CONTRACTOR
SHOULD VERIFY ALL LOCAL AND STATE
REGULATIONS AND PERMITS ARE
OBTAINED PRIOR TO CONSTRUCTION.
THESE DRAWINGS ARE NOT TO BE USED
FOR ANY OTHER PROJECT WITHOUT THE
WRITTEN CONSENT OF THE ARCHITECT.
DATE: 10/2/2023


SCALE:

DATE:


DRAWINGS PROVIDED BY:
Ken Waibel
8227 N 725 E
Orem, UT 84052
812-466-6328
khwaibel88@slc.email




Elevation 1



Elevation 2



Elevation 3



Elevation 4

DATE: 10/2/2023
 SCALE:
 SHEET:

New Plans For.....
 Cedar 4 Bedrooms

DRAWINGS PROVIDED BY:
 Ken Waizer
 8227 N 725 E
 Orem UT 84052
 812-466-6328
 khwaizer88@sic.e-mail

DRAWINGS PROVIDED BY:
Ken Weiler
8227 N 725 E
Orem UT 84052
812-466-6328
khagler88@slc.email


DATE:

10/2/2023


SCALE:

SHEET:

ONE OF OUR ARCHITECTS HAS BEEN
COMMISSIONED BY THE UNIVERSITY
OF UTAH TO CONDUCT A STUDY ON
THE IMPACT OF CLIMATE CHANGE ON
ARCHITECTURE. THE STUDY IS CURRENTLY
UNDERWAY AND WILL BE COMPLETED
BY THE END OF THE YEAR. THE STUDY
WILL EXAMINE THE IMPACT OF CLIMATE
CHANGE ON ARCHITECTURE AND
STRUCTURES. THE STUDY WILL ALSO
EXAMINE THE IMPACT OF CLIMATE
CHANGE ON THE ENVIRONMENT AND
ON THE HEALTH OF HUMANS.



Foundation



Attic









55-ROLL



REPORT OF GEOTECHNICAL ENGINEERING EXPLORATION

**OOLITIC DRIVE RESIDENCES
BLOOMINGTON, INDIANA**

PREPARED FOR:

**RCH, LLC
1190 EAST 1400 NORTH
ODON, INDIANA 47562**

**Patriot Engineering and Environmental, Inc.
2006 South Yost Avenue
Bloomington, Indiana 47403**

May 6, 2024



May 6, 2024

Mr. Melvin Graber
RCH, LLC
11990 East 1400 North
Odon, Indiana 47562

Re: **Report of Geotechnical Engineering Exploration
Oolitic Drive Residences
922 North Oolitic Drive
Bloomington, Indiana
Patriot Project No.: 24-0455-11G**

Dear Melvin:

Attached is the report of our geotechnical engineering exploration for the above referenced project. This exploration was completed in general accordance with our Proposal No. P24-0688-11G dated March 25, 2024.


This report includes detailed and graphic logs of six (6) soil borings drilled at the proposed project site. Also included in the report are the results of laboratory tests performed on samples obtained from the site, and geotechnical recommendations pertinent to the site development, foundation design, and construction.

We appreciate the opportunity to perform this geotechnical engineering exploration and are looking forward to working with you during the construction phase of the project. If you have any questions regarding this report or if we may be of any additional assistance regarding any geotechnical aspect of the project, please do not hesitate to contact our office.

Respectfully submitted,
Patriot Engineering and Environmental, Inc.



Mark Jonard, E.I.
Geotechnical Engineer



William D. Dubois, P.E.
Senior Principal Engineer

TABLE OF CONTENTS

1.0 INTRODUCTION	1
1.1 General	1
1.2 Purpose and Scope	1
2.0 PROJECT INFORMATION	1
3.0 SITE AND SUBSURFACE CONDITIONS	2
3.1 Site Conditions	2
3.2 General Subsurface Conditions	2
3.3 Groundwater Conditions	3
4.0 DESIGN RECOMMENDATIONS	4
4.1 Basis	4
4.2 Overall Site Evaluation.....	4
4.3 Foundations	5
4.4 Floor Slabs	7
4.5 Seismic Considerations	7
5.0 CONSTRUCTION CONSIDERATIONS	8
5.1 Site Preparation.....	8
5.2 Sinkhole Remediation.....	9
5.3 Foundation Excavations	10
5.4 Structural Fill and Fill Placement Control.....	11
5.5 Groundwater Considerations	12
6.0 EXPLORATIONAL PROCEDURES	13
6.1 Field Work	13
6.2 Laboratory Testing.....	13
7.0 ILLUSTRATIONS	14

APPENDICES

Appendix A:	Site Vicinity Map (Figure No. 1)
	Boring Location Map (Figure No. 2)
	Boring Logs
	Boring Log Key
	Unified Soil Classification System (USCS)
Appendix B:	Seismic Site Class Evaluation
Appendix C:	General Qualifications
	Standard Clause for Unanticipated Subsurface Conditions

REPORT OF GEOTECHNICAL ENGINEERING EXPLORATION

**Oolitic Drive Residences
922 Oolitic Drive
Bloomington, Indiana
Patriot Project No.: 24-0455-11G**

1.0 INTRODUCTION

1.1 General

RCH, LLC is planning the construction of a three (3) small single-family homes to be located at the three (3) lots at 922 North Oolitic Drive in Bloomington, Indiana. The results of our geotechnical engineering exploration for the project are presented in this report.

1.2 Purpose and Scope

The purpose of this exploration is to determine the general near surface and subsurface conditions within the project area and to develop the geotechnical engineering recommendations necessary for the design and construction of the proposed structures. This was achieved by drilling soil borings, and by conducting laboratory tests on samples taken from the borings. This report contains the results of our findings, an engineering interpretation of these results with respect to the available project information, and recommendations to aid in the design and construction of the proposed facility.

2.0 PROJECT INFORMATION

The proposed project is located along Oolitic Drive in Bloomington, Indiana. The project consists of three (3) single-family homes being built. These homes will be one (1)-story structures of slab-on-grade construction, approximately 32 feet by 48 feet of in plan dimension.

No structural loading information is available to us at the time of this report, but based on similar projects in the area, we can estimate that the proposed structures will have wall loads not exceeding 1,500 pounds per lineal foot (plf), isolated column loads not exceeding 60 kips, and that floor loads will not exceed 150 pounds per square foot (psf). Additionally, based on visual observations of the existing site, it is assumed that any grade raise fill to complete the construction of building pads, finished pavement subgrades, etc., will not exceed 2 feet above the existing ground surface.

3.0 SITE AND SUBSURFACE CONDITIONS

3.1 Site Conditions

The project site is presently an approximately 0.6 acres used for residential purposes. There were previously two (2) modular homes that were removed prior to our mobilization. The surrounding area is generally an area of residential development. The topography in the area proposed for construction is sloped down towards the center of the site, where a recorded sinkhole, per the Indiana Sinkhole Inventory provided by the Indiana Geological Survey, is present. Although the proposed buildings are not planned to be placed above the sinkhole, remediation is required for the project.

3.2 General Subsurface Conditions

Our interpretation of the subsurface conditions is based upon six (6) soil borings drilled at the approximate locations shown on the Boring Location Map (Figure No. 2) in Appendix "A". All depths discussed below refer to depths below the existing ground surface. Based on the results of the soil borings completed at the site, the following subsurface profile is presented. A description of each general soil unit has been identified and is described below:

Topsoil – Topsoil, a surficial layer of material that is a blend of silts, sands, and clays, with varying amounts of organic matter, was encountered at the ground surface at all of the six (6) boring locations. The topsoil layer was about 3 to 8 inches thick in the borings.

Silty Clay (CL) - The surficial layer is generally underlain by brown, slightly moist to very moist, soft to very stiff, silty clay. The silty clay layers extended to depths of 6 to 13.5 feet below the existing ground surface. The natural moisture content of this material ranges from 16 to 29 percent (%). The silty clay layers have unconfined compressive strengths, as determined by a hand penetrometer, of 1.9 to 4.5 tons per square foot (tsf). Standard Penetration Test N-values in this material varied from 4 to 23 blows per foot (bpf). Additionally, fill material, such as asphalt, gravel, brick and organics, was observed in multiple borings to varying depths (see the Table 1 below).

Clay (CH) - The silty clay layer is underlain by red, moist to very moist, medium stiff to hard, *High plasticity* clay. The clay layers extended to depths of 10 to 20 feet below the existing ground surface. The natural moisture content of this material ranges from 26 to 40 %. The silty clay layers have unconfined compressive strengths of 3.0 to 3.9 tsf. Standard Penetration Test N-values in this material varied from 13 to greater than 50 bpf.

Limestone – Below the clay layers at auger refusal, highly weather limestone was present.

The soil conditions described above are general, and some variations in the descriptions should be expected; for more specific information, please refer to the boring logs presented in Appendix “A”. It should be noted that the dashed stratification lines shown on the soil boring logs indicate approximate transitions between soil types. In-situ stratification changes could occur gradually or at different depths.

As previously mentioned, soft clays and unsuitable fill material were encountered in four (4) of the six (6) borings, at depths up to 13.5 feet below the existing ground surface. The following table presents the extent of the unsuitable soils encountered in the borings:

Table No. 1: Summary of Unsuitable Soils Encountered in Borings

Boring Number	Soil Classification	Approximate Depth of Unsuitable Soils (feet) ⁽¹⁾
B-3	Silty Clay (CL) with some asphalt and gravel (FILL)	3.5 to 6
B-4	Silty Clay (CL) with some asphalt (FILL)	0 to 3.5
	Asphalt and Gravel (FILL)	3.5 to 6
B-5	Soft Silty Clay (CL) with a trace of gravel and organics (FILL)	0 to 6
B-6	Silty Clay (CL) with a trace of asphalt (FILL)	0 to 6
	Silty Clay (CL) with some gravel and brick (FILL)	6 to 13.5

⁽¹⁾ Represents depth below existing ground surface.

3.3 Groundwater Conditions

The term groundwater pertains to any water that percolates through the soil found on site. This includes any overland flow that permeates through a given depth of soil, perched water, and water that occurs below the “water table”, a zone that remains saturated and water-bearing year round.

Groundwater was observed during drilling in one (1) of the soil borings (B-5) performed at the site at depths of 13 feet below the existing ground surface. Groundwater was not observed in the remaining borings during drilling. Immediately after the borings were completed and the augers were removed from the boreholes, groundwater was not observed.

It should be recognized that fluctuations in the groundwater level should be expected over time due to variations in rainfall and other environmental or physical factors. ***The true static groundwater level can only be determined through observations made in cased holes over a long period of time, the installation of which was beyond the scope of this exploration.***

4.0 DESIGN RECOMMENDATIONS

4.1 Basis

Our recommendations are based on data presented in this report, which include soil borings, laboratory testing, and our experience with similar projects. Subsurface variations that may not be indicated by a dispersive exploratory boring program can exist on any site. If such variations or unexpected conditions are encountered during construction, or if the project information is incorrect or changed, we should be informed immediately since the validity of our recommendations may be affected.

4.2 Overall Site Evaluation

The borings indicate that the site is mostly underlain by clayey (CL) soils with fill materials observed in multiple borings. In general, the areas near soil borings performed may be suitable for the anticipated development following removal of the fill material. The soils will then be suitable for shallow foundations, and for support of floor slabs and pavements with these undercuts and soil replacement with compacted structural fill of the near surface soils. Additional Concerns for construction are listed below.

Expansive (Highly Plastic) Clays

Four (4) of the six (6) borings encountered highly plastic (expansive) clays (CH) at depths typically between about 6 and 20 feet below the existing ground surface. Expansive soils undergo volume changes upon wetting and drying. Expansive soils tend to shrink on drying and expand when the degree of saturation increases. However, the primary factors

that govern the amount of expansion of the soils are the availability of moisture and the amount and type of clay particles in the soil.

In Indiana, typically expansive soils within the upper 5 to 10 feet of the surface grade are influenced most by climatic environmental factors, which affect the water content of the soils and hence cause the soils to shrink and swell. This range of influence is generally referred to as the active zone. Foundations, floor slabs, pavements and subsurface utilities placed on or in this active zone of highly plastic (expansive) clays can be subjected to detrimental effects of shrink and swell; which can cause unsuitable total and/or differential settlements, along with cracking. Therefore, we recommend that foundations, floor slabs, pavements, other infrastructure not bear or be placed directly on highly plastic clays (CH). Positive drainage of surface water both during construction and after construction is complete will be especially important to reduce the amount of surface water that is allowed to permeate into the subgrade soils and subsequently reduce the potential for unsuitable shrinking or swelling of the underlying highly plastic clays. Water and drainage lines should be located such that if any leakage occurs, water will not be readily accessible to foundations, floor slabs and/or pavement sections. Additionally, the installation and use of an irrigation system at the parcel is highly discouraged.

Karst

The project site is located within a region known for karstic features. Karstic areas are typically associated with the development of solution features within the soluble carbonate bedrock leading to formation of sinkholes. A sinkhole is described as “Closed depression in soil or bedrock formed by the erosion and transport of earth material from below the land surface.” Sinkholes may develop within karstic areas as a result of soil fines migrating from the overburden soil by infiltrating water flowing downward into the bedrock through solution features/channels, such as voids and clay seams within the rock. Sinkholes may consist of a relatively localized weathered feature or larger features resulting from a collapse within a void formed in the overburden soils as a result of loss of the fine soils into the bedrock features. A sinkhole was observed on-site, as well as confirmed by the Indiana Sinkhole Inventory provided by the Indiana Geological Survey. Recommendations for remediation can be found in Section 5.2. If further evaluation of karst is desired, *Patriot* can provide geophysical testing services.

4.3 Foundations

As previously mentioned, unsuitable fill material was encountered in four (4) of the six (6) to depths up to 13.5 feet below existing grade and it is highly likely that potential existing fill

materials could be present within the project area due to previous construction activities. ***If soft clays, existing fill materials, or other unsuitable materials are encountered at the footing level or below, they must be undercut 3 feet below the bottom of the foundation and replaced with well-compacted structural fill prior to construction of foundations or the footings can be extended to suitable natural soils.*** Following the excavation of the footing areas, the foundations subgrade should be visually inspected by a *Patriot* representative and probed at multiple locations at isolated footings and at every 10 feet (maximum) along wall footings using a Dynamic Cone Penetrometer (DCP) to a minimum depth of 5 feet below the footing subgrade to verify that the underlying soil has a SPT blow count of 7 or more or unconfined compressive strength of 1.0 tsf or more. Any unsuitable soils encountered at the footing subgrade or below should be removed and replaced with well-compacted structural fill.

Provided the above recommendations are followed, the proposed structure can be supported on spread footings bearing on the medium stiff to very stiff silty clay encountered at shallow depths or on new well-compacted structural fill overlying the same. These footings should be proportioned using a net allowable soil bearing pressure not exceeding 2,000 pounds per square foot (psf) for column footings or 1,500 psf for wall (strip) footings. For proper performance at the recommended design bearing pressure, foundations must be constructed in compliance with the recommendations for footing excavation inspection that are discussed in Section 5.0 “*Construction Considerations*”.

In using the above net allowable soil bearing pressures, the weight of the foundation and backfill over the foundation need not be considered. Hence, only loads applied at or above the minimum finished grade adjacent to the footing need to be used for dimensioning the foundations. Each new foundation should be positioned so it does not induce significant pressure on adjacent foundations; otherwise the stress overlap must be considered in the design.

All exterior foundations and foundations in unheated areas should be located at a depth of at least 24 inches below final exterior grade for frost protection. We recommend that wall (strip) footings be at least 18 inches wide and column footings be at least 24 inches wide for bearing capacity considerations.

We estimate that the total foundation settlement should not exceed approximately 1 inch and that differential settlement should not exceed about $\frac{3}{4}$ inch. Careful field control during construction is necessary to minimize the actual settlement that will occur.

Positive drainage of surface water, including downspout discharge, should be maintained away from structure foundations to avoid wetting and weakening of the foundation soils both during construction and after construction is complete.

4.4 Floor Slabs

The near surface or shallow subgrade soils encountered within the proposed building footprint generally consist of medium stiff to stiff silty clay and fill material. While the silty clay material is suitable for floor slab support, the fill material is not. ***If soft clays, existing fill materials, or other unsuitable materials are encountered at the floor slab subgrade, they must be undercut and replaced with well-compacted structural fill prior to construction of floor slabs.***

We recommend that all floor slabs be designed as "floating", that is, fully ground supported and not structurally connected to walls or foundations. This is to minimize the possibility of cracking and displacement of the floor slabs because of differential movements between the slab and the foundation. Although the movements are estimated to be within the tolerable limits for the structural safety, such movements could be detrimental to the slabs if they were rigidly connected to the foundations. Additionally, we recommend that all slabs should be liberally jointed and designed with the appropriate reinforcement for the anticipated loading conditions.

The building floor slabs should be supported on a minimum 6 inch thick well-compacted granular base course (i.e. Indiana Department of Transportation (INDOT) No. 53 crushed stone) bearing on a suitably prepared subgrade (Refer to Section 5.0 "*Construction Considerations*"). The granular base course is expected to help distribute loads and equalize moisture conditions beneath the slab.

Provided that the recommendations above for floor slab design and construction are followed, a modulus of subgrade reaction, "K₃₀" value of 75 pounds per cubic inch (pci), is recommended for the design of ground supported floor slabs. It should be noted that the "K₃₀" modulus is based on a 30 inch diameter plate load empirical relationship.

4.5 Seismic Considerations

For structural design purposes, we recommend using a ***Site Classification of "C"*** as defined by the Indiana Building Code (modified 2012 International Building Code (IBC)). Furthermore, along with using a Site Classification of "C", we recommend the use of the

maximum considered spectral response acceleration and design spectral response acceleration coefficients provided in Table No. 2 below. Refer to Appendix “B” for “*Seismic Site Class Evaluation*” report summary.

Table No. 2: Seismic Design Spectral Response Acceleration Coefficients

Period (seconds)	Maximum Considered Spectral Response Acceleration Coefficient	Soil Factor	Design Spectral Response Acceleration Coefficient
0.2	$S_S = 0.225 \text{ g}$	1.20	$S_{DS} = 0.180 \text{ g}$
1.0	$S_1 = 0.107 \text{ g}$	1.69	$S_{D1} = 0.121 \text{ g}$

These values were obtained from the “*Earthquake Ground Motion Parameters*” program for seismic design, developed by the United States Geological Survey (USGS) Earthquake Hazard Program, utilizing latitude 39.175149° north and longitude 86.5534332° west as the designation for identifying the location of the parcel. Other earthquake resistant design parameters should be applied consistent with the minimum requirements of the Indiana Building Code.

5.0 CONSTRUCTION CONSIDERATIONS

5.1 Site Preparation

All areas that will support foundations, floors, pavements or newly placed structural fill must be properly prepared. All loose surficial soil or “topsoil” and other unsuitable materials must be removed. Unsuitable materials include: frozen soil, relatively soft material, relatively wet soils, deleterious material, or soils that exhibit a high organic content.

Approximately 3 to 8 inches of loose surficial topsoil was encountered in the borings. The topsoil was measured at discrete locations as shown on the Boring Location Map (Figure No. 2) in Appendix “A”. The topsoil thickness measured at the boring locations may or may not be representative of the overall average topsoil thickness at the site. Therefore, it is possible that the actual stripping depth could significantly vary from this data. The data presented should be viewed only as a guide to the minimum stripping depth that will be

required to remove organic material at the surface. Additional field exploration by *Patriot* would be required to provide an accurate estimate of the stripping depth. This limited data indicates that a minimum stripping depth will be required to remove the organic material at the surface, followed by the potential for additional stripping and/or scarification and recompaction as may be required to achieve suitable subgrade support. **Additionally, if saturated conditions exist with the surface soils, light tracked equipment could be required to avoid pushing organics deeper into the suitable subgrade soils.** A *Patriot* representative should verify the stripping depth at the time grading operations occur.

Prior to construction of floor slabs, pavements or the placement of new structural fill, the exposed subgrade must be evaluated by a *Patriot* representative; which will include proofrolling of the subgrade. Proofrolling should consist of repeated passes of a loaded, pneumatic-tired vehicle such as a tandem-axle dump-truck or scraper. The proofrolling operations should be observed by a *Patriot* representative, and the proofrolling vehicle should be loaded as directed by *Patriot*. Any area found to rut, pump, or deflect excessively should be compacted in-place or, if necessary, undercut and replaced with structural fill, compacted as specified in Section 5.3 “*Structural Fill and Fill Placement Control*”.

Care must be exercised during grading and fill placement operations. **The combination of heavy construction equipment traffic and excess surface moisture can cause pumping and deterioration of the near surface soils. The severity of this potential problem depends to a great extent on the weather conditions prevailing during construction.** The contractor must exercise discretion when selecting equipment sizes and also make a concerted effort to control construction traffic and surface water while the subgrade soils are exposed. We recommend that heavy construction equipment (i.e. dump trucks, scrapers, etc.) be rerouted away from the building and pavement areas. If such problems do arise, the operations in the affected area should be halted and the *Patriot* representative contacted to evaluate the condition.

5.2 Sinkhole Remediation

The actual method used for the treatment of sinkholes is typically dependent on the depth to bedrock and the intended purpose of the area subjected to remediation. Several acceptable methods of treatment are discussed below.

If the depth to the top of bedrock is greater than 15 feet the following should be performed:

- Remove all debris from the hole

- Line hole with geotextile fabric (Mirafi 160N or equivalent), the geotextile fabric should be placed so that there is enough excess fabric to completely wrap the stone
- Backfill with No. 2 Crushed Limestone
- Wrap stone in geotextile fabric
- Place min 2 feet thick compacted clay soil cap, clay soil should be compacted to 100% of Standard Proctor maximum dry density

Please refer to Illustration A at the end of this report.

If the depth to the top of bedrock is less than 15 feet the following should be performed:

- Remove all debris from the hole
- Excavate to the top of the bedrock
- Line hole with geotextile fabric (Mirafi 160N or equivalent), the geotextile fabric should be placed so that there is enough excess fabric to completely wrap the stone
- Backfill with No. 2 Crushed Limestone
- Wrap stone in geotextile fabric
- Place 1 foot of compacted crushed limestone (DGA), compacted to 100% of standard proctor maximum dry density
- Place min 2 feet thick compacted clay soil cap, clay soil should be compacted to 100% of Standard Proctor maximum dry density
- Or instead of crushed limestone and soil cap, place 1-foot reinforced concrete cap

Please refer to Illustrations B and C at the end of this report.

5.3 Foundation Excavations

Upon completion of the foundation excavations and prior to the placement of reinforcing steel, a *Patriot* representative should check the exposed subgrade to confirm that a bearing surface of adequate strength has been reached. Any localized soft soil zones encountered at the bearing elevations should be further excavated until adequate support soils are encountered. The cavity should be backfilled with structural fill as defined below, or the footing can be poured at the excavated depth. Structural fill used as backfill beneath footings should be limited to lean concrete, well-graded sand and gravel, or crushed stone placed and compacted in accordance with Section 5.3 “*Structural Fill and Fill Placement Control*”.

If it is necessary to support spread footings on structural fill, the fill pad must extend laterally a minimum distance beyond the edge of the footing. The minimum structural pad

width would correspond with a point at which an imaginary line extending downward from the outside edge of the footing at a 1H:2V (horizontal: vertical) slope intersects the surface of the natural soils. For example, if the depth to the bottom of excavation is 4 feet below the bottom of the foundation, the excavation would need to extend laterally beyond the edge of the footing at least 2 feet, as shown in Illustration "A" found at the conclusion of this report.

Excavation slopes should be maintained within all requirements set-forth by the Occupational Safety and Health Standards (OSHA), but specifically Section 1926 Subpart "P" – "Excavations". We recommend that any surcharge fill or heavy equipment be kept at least 5 feet away from the edge of the excavation.

Construction traffic on the exposed surface of the bearing soil will potentially cause some disturbance of the subgrade and consequently loss of bearing capacity. However, the degree of disturbance can be minimized by proper protection of the exposed surface.

5.4 Structural Fill and Fill Placement Control

Structural fill, defined as any fill which will support structural loads, should be clean and free of organic material, debris, deleterious materials and frozen soils. Samples of the proposed fill materials should be tested prior to initiating the earthwork and backfilling operations to determine the classification, the natural and optimum moisture contents and maximum dry density and overall suitability as a structural fill. **Structural fill should have a liquid limit less than 40 and a plasticity index less than 20.**

All structural fill beneath floor slabs, adjacent to foundations and over foundations, should be compacted to at least 95 percent (%) of its maximum Standard Proctor dry density (ASTM D-698). This minimum compaction requirement should be increased to 100 percent (%) of the maximum Standard Proctor dry density for fill supporting footings, provided these are designed as outlined Section 4.0 "Design Recommendations".

Structural fill supporting, around and over utilities should be compacted to at least 95 percent (%) of its maximum Standard Proctor dry density (ASTM D-698) for utilities underlying structural areas (i.e. buildings, pavements, sidewalks, etc.). However, the minimum compaction requirement can be reduced for backfill around and over the utilities to 90 percent (%) of the maximum Standard Proctor dry density where utilities underlie greenbelt areas (i.e. grassy lawns, landscaping, etc.). It is recommended that a

clean well-graded granular material be utilized as the bedding material, as well as the backfill material around and over the utility lines.

In cut areas, where pavement sections are planned, the upper 10 inches of subgrade should be scarified and compacted to a dry density of at least 100 percent (%) of the Standard Proctor maximum dry density (ASTM D-698). Any grade-raise fill placed within 1 foot of the base of the pavement section should also be compacted to at least 100 percent (%) of the Standard Proctor maximum dry density. This can be reduced to 95 percent (%) for structural fill placed more than 1 foot below the base of the pavement section.

To achieve the recommended compaction of the structural fill, we suggest that the fill be placed and compacted in layers not exceeding 8 inches in loose thickness (the loose lift thickness should be reduced to 6 inches when utilizing small hand compactors) and within the range of 2 percentage (%) points below or above the optimum moisture content value. All fill placement should be monitored by a *Patriot* representative. ***Each lift should be tested for proper compaction at a frequency of at least one (1) test every 2,500 square feet (ft²) per lift for the building areas, at least one (1) test every 10,000 square feet (ft²) per lift for the parking and roadway areas, and at a frequency of at least one (1) test for every 50 lineal feet of utility installation.***

5.5 Groundwater Considerations

Groundwater was observed during our field activities at depths between 13 feet below the existing ground surface (Refer to Section 3.3 “Groundwater Conditions”); which is expected to be below the anticipated foundation excavation depths. Depending on seasonal conditions, localized and sporadic groundwater infiltration may occur into the building foundation excavations on this site.

Groundwater inflow into shallow excavations **above** the groundwater table is expected to be adequately controlled by conventional methods such as gravity drainage and/or pumping from sumps. More significant inflow can be expected in deeper excavations **below** the groundwater table requiring more aggressive dewatering techniques, such as well or wellpoint systems. For groundwater to have minimal effects on the construction, foundation excavations should be constructed and poured in the same day, if possible.

6.0 EXPLORATIONAL PROCEDURES

6.1 Field Work

A total of six (6) soil borings were drilled, sampled, and tested at the project site on April 17, 2024 at the approximate locations shown on the Boring Location Map (Figure No. 2) in Appendix "A". The soil borings were drilled to depths of 20 feet in the proposed building area. All depths are given as feet below the existing ground surface.

The borings were advanced using 3¼ inch inside diameter hollow-stem augers. Samples were recovered in the undisturbed material below the bottom of the augers using the standard drive sample technique in accordance with ASTM D 1586-74. A 2 inch outside diameter by 1³/₈ inch inside diameter split-spoon sampler was driven a total of 18 inches with the number of blows of a 140 pound hammer falling 30 inches recorded for each 6 inches of penetration. The sum of blows for the final 12 inches of penetration is the Standard Penetration Test result commonly referred to as the N-value (or blow-count). Split-spoon samples were recovered at 2.5 feet intervals, beginning at a depth of 1 foot below the existing surface grade, extending to a depth of 10 feet, and at 5 feet intervals thereafter to the termination of the boring.

Water levels were monitored at each borehole location during drilling and upon completion of the boring. The boreholes were backfilled with auger cuttings prior to demobilization for safety considerations.

Upon completion of the boring program, all of the samples retrieved during drilling were returned to *Patriot's* soil testing laboratory where they were visually examined and classified. A laboratory-generated log of each boring was prepared based upon the driller's field log, laboratory test results, and our visual examination. Test boring logs and a description of the classification system are included in Appendix "A" in this report. Indicated on each log are: the primary strata encountered, the depth of each stratum change, the depth of each sample, the Standard Penetration Test results, groundwater conditions, and selected laboratory test data. The laboratory logs were prepared for each boring giving the appropriate sample data and the textural description and classification.

6.2 Laboratory Testing


Representative samples recovered in the borings were selected for testing in the laboratory to evaluate their physical properties and engineering characteristics. Laboratory analysis included: natural moisture content determinations (ASTM D 2216) and an

estimate of the unconfined compressive strength (q_u) of the cohesive soil samples utilizing a calibrated hand penetrometer (q_p) were obtained. The results of laboratory tests are summarized in Section 3.2 “*General Subsurface Conditions*”. Soil descriptions on the boring logs are in accordance with the Unified Soil Classification System (USCS).

7.0 ILLUSTRATIONS

See Illustrations “D” and “E” on the following pages. These illustrations are presented for reference for the remediation and backfill of sinkholes presented in Section 5.2.

See Illustrations “D” and “E” on the following pages. These illustrations are presented to further visually clarify several of the construction considerations presented in Section 5.3 “*Foundation Excavations*”.




Patriot Engineering & Environmental, Inc.

Project: Oolitic Drive Residences
922 North Oolitic Drive
Bloomington, Indiana

Project Number: 24-0455-11G	Drawn By: J. DuMond
Date: May 2, 2024	Approved: B. Lauletta
	DWG: 24-0455-11_detail

Illustration A
Treatment Method for
Deep Sink Holes




Patriot Engineering & Environmental, Inc.

Project: Oolitic Drive Residences
922 North Oolitic Drive
Bloomington, Indiana

Project Number: 24-0455-11G	Drawn By: J. DuMond
Date: May 2, 2024	Approved: B. Lauletta
	DWG: 24-0455-11_detail

Illustration B
Treatment Method for Sink Holes




SOIL OVERBURDEN <15'



Project: Oolitic Drive Residences 922 North Oolitic Drive Bloomington, Indiana	
Project Number: 24-0455-11G	Drawn By: J. DuMond
Date: May 2, 2024	Approved: B. Lauletta
	DWG: 24-0455-11_detail

Illustration C
Treatment Method for
Sink Holes



*d IS DEPTH TO SUITABLE SOILS

* IN COMPLIANCE WITH OSHA STANDARDS




**PATRIOT ENGINEERING
and Environmental, Inc.**
Engineering Value for Project Success
Consulting Environmental, Geotechnical
and Materials Engineers

Excavation for Footings In an Area of Fill ILLUSTRATION D

job. no.:

figure:



**PATRIOT ENGINEERING
and Environmental, Inc.**
Engineering Value for Project Success
Consulting Environmental, Geotechnical
and Materials Engineers

Excavation Near Existing
In Use Foundations
ILLUSTRATION E

job. no.:

figure:

APPENDIX A

SITE VICINITY MAP (FIGURE NO. 1)

BORING LOCATION MAP (FIGURE NO. 2)

BORING LOGS

BORING LOG KEY

**UNIFIED SOIL CLASSIFICATION SYSTEM
(USCS)**



Image Source:
USGS Bloomington Topo 2022

Figure 1

Site Vicinity Map



Patriot Engineering &
Environmental, Inc.

Project: Oolitic Drive Residences
922 North Oolitic Drive
Bloomington, Indiana

Project Number: 24-0455-11
Date: April 23, 2024

Drawn By: J. DuMond
Approved: M. Jonard
DWG: 24-0455-11_geo



LEGEND

- PATRIOT Soil Boring
- B-1 Soil Boring ID

NOTES:

1. Boring locations were staked by PATRIOT. All locations are shown as approximate.
2. All locations were determined in the field with references to existing landmarks.
3. Image Source: Google Earth
4. Scale as shown.

Figure 2
Soil Boring Location Map

Project: Oolitic Drive Residences 922 North Oolitic Drive Bloomington, Indiana		Drawn By: J. DuMond
Project Number: 24-0455-11	Approved: M. Jonard	
Date: April 23, 2024	DWG: 24-0455-11_geo	



Patriot Engineering & Environmental, Inc.



LOG OF BORING B-1

(Page 1 of 1)

Oolitic Drive Residences
922 North Oolitic Drive
Bloomington, Indiana

Client Name : RCH LLC
Project Number : 24-0455-11G
Logged By : J. Rogers
Start Date : 04/17/2024
Drilling Method : HSA

Driller : E. Thomas
Sampling : Splitspoon
Approx. Elevation : +/- 881 feet
Latitude : 39°10'32.20"N
Longitude : 86°33'11.58"W

Depth (Feet)	Elevation (Feet)	Water Level	USCS	GRAPHIC	Water Levels					REMARKS
					▼ During Drilling - Dry	▽ After Completion - Dry	◆ After 24 Hours - N/A	Samples	Rec %	
DESCRIPTION										
0	881				TOPSOIL (4") Red, moist to very moist, stiff to hard, SILTY CLAY					
					1	100	4/4/7	2.3	24	
					2	67	4/6/7	1.9	23	
5	875		CL		3	33	6/10/13	2.7	24	
					4	94	6/7/8	4.5	22	Boring caved to 8.5 feet upon auger removal.
10	870				5	17	50-3"			Auger refusal encountered at 13.5 feet.
					Gray, highly weathered, LIMESTONE					
15	865				Splitspoon refusal encountered at 13.8 feet.					Groundwater was not encountered during drilling, nor upon completion.
20	860									
25										

05-02-2024 C:\Users\mjonard\Patriot_Engineering\GEO - Documents\Mtech\2024 Mtech\0455-11G\b1.bor



LOG OF BORING B-2

(Page 1 of 1)

Oolitic Drive Residences
922 North Oolitic Drive
Bloomington, Indiana

Client Name : RCH LLC
Project Number : 24-0455-11G
Logged By : J. Rogers
Start Date : 04/17/2024
Drilling Method : HSA

Driller : E. Thomas
Sampling : Splitspoon
Approx. Elevation : +/- 883 feet
Latitude : 39°10'32.44"N
Longitude : 86°33'11.73"W

Depth (Feet)	Elevation (Feet) 883	Water Level	USCS	GRAPHIC	Water Levels			Samples	Rec %	SPT Results	qp tsf	w %	REMARKS
					▼ During Drilling - Dry	▽ After Completion - Dry	◆ After 24 Hours - N/A						
DESCRIPTION													
0					TOPSOIL (8")								
			CL		Brown, very moist, stiff, SILTY CLAY with trace gravel	1	100	4/5/7			26		
880			CL		Red, very moist, stiff to very stiff, SILTY CLAY	2	89	4/7/8	2.5		26	Boring caved to 5 feet upon auger removal.	
5			CH		Red, very moist, stiff to very stiff, CLAY	3	100	4/6/8	3.0		37		
875					Gray, highly weathered LIMESTONE	4	50	4/18/50-4"			28		
10													
870					Auger refusal encountered at 12 feet							Groundwater was not encountered during drilling, nor upon completion.	
15													
865													
20													
860													
25													

05-02-2024 C:\Users\mjonard\Patriot_Engineering\GEO - Documents\Mtech\2024 Mtech\0455-11G\b2.bor



LOG OF BORING B-3

(Page 1 of 1)

Oolitic Drive Residences
922 North Oolitic Drive
Bloomington, Indiana

Client Name : RCH LLC
Project Number : 24-0455-11G
Logged By : J. Rogers
Start Date : 04/17/2024
Drilling Method : HSA

Driller : E. Thomas
Sampling : Splitspoon
Approx. Elevation : +/- 878 feet
Latitude : 39°10'31.98"N
Longitude : 86°33'11.69"W

Depth (Feet)	Elevation (Feet)	Water Level	USCS	GRAPHIC	Water Levels					REMARKS	
					▼ During Drilling - Dry	▽ After Completion - Dry	◆ After 24 Hours - N/A	Samples	Rec %		SPT Results
DESCRIPTION											
0	878				TOPSOIL (4")						
			CL		Red, moist, medium stiff, SILTY CLAY	1	17	9/5/3		21	Boring caved to 2 feet upon auger removal.
3.75			CL		Red, moist, medium stiff, SILTY CLAY with some gravel and asphalt (FILL)	2	44	1/3/3		21	
5			CH		Red, very moist, hard, CLAY with trace limestone	3	33	4/50-4"		40	
8.70					Gray, highly weathered, LIMESTONE	4	44	50-4"			
10											
12					Auger refusal encountered at 12 feet.						Groundwater was not encountered during drilling, nor upon completion.
15											
20											
25											



LOG OF BORING B-4

(Page 1 of 1)

Oolitic Drive Residences
922 North Oolitic Drive
Bloomington, Indiana

Client Name : RCH LLC
Project Number : 24-0455-11G
Logged By : J. Rogers
Start Date : 04/17/2024
Drilling Method : HSA

Driller : E. Thomas
Sampling : Splitspoon
Approx. Elevation : +/- 877 feet
Latitude : 39°10'31.60"N
Longitude : 86°33'11.65"W

Depth (Feet)	Elevation (Feet)	Water Level	USCS	GRAPHIC	Water Levels			Samples	Rec %	SPT Results	qp tsf	w %	REMARKS
					▼ During Drilling - Dry	▽ After Completion - Dry	◆ After 24 Hours - N/A						
DESCRIPTION													
0					TOPSOIL (3")								
875			CL		Brown, slightly moist, stiff, SILTY CLAY with some asphalt (FILL)	1	44	4/4/6		16			Boring caved to 6 feet upon auger removal.
5					ASPHALT and GRAVEL (FILL)	2	72	11/13/6		6			
870					Red, very moist, stiff to very stiff, CLAY	3	50	4/6/7	3.9	28			
10						4	72	8/11/9	3.6	31			
865			CH			5	100	7/13/10		27			
20						6	72	7/10/12		26			
855					Boring terminated at 20 feet.								Groundwater was not encountered during drilling, nor upon completion.
25													



LOG OF BORING B-5

(Page 1 of 1)

Oolitic Drive Residences
922 North Oolitic Drive
Bloomington, Indiana

Client Name : RCH LLC
Project Number : 24-0455-11G
Logged By : J. Rogers
Start Date : 04/17/2024
Drilling Method : HSA

Driller : E. Thomas
Sampling : Splitspoon
Approx. Elevation : +/- 878 feet
Latitude : 39°10'31.17"N
Longitude : 86°33'12.62"W

Depth (Feet)	Elevation (Feet)	Water Level	USCS	GRAPHIC	Water Levels					REMARKS					
					▼ During Drilling - 13.0 feet	▽ After Completion - Dry	◆ After 24 Hours - N/A	Samples	Rec %		SPT Results	qp tsf	w %		
DESCRIPTION															
0	878				TOPSOIL (5") Brown, moist to very moist, soft to medium stiff, SILTY CLAY with trace gravel and organics (FILL)										
3.75			CL			1	33	1/1/24		21					
5					Brown to Gray, moist to very moist, medium stiff to stiff, SILTY CLAY										
5						2	56	2/2/2		19					
8.7						3	33	4/4/4		24					
8.7						4	39	3/3/4		21					
10															
13.65		▼	CL			5	100	1/3/3		29					
15															
18.6						6	100	4/6/6		21					
20					Boring terminated at 20 feet.										
25															

Boring caved to 5 feet upon auger removal.



LOG OF BORING B-6

(Page 1 of 1)

Oolitic Drive Residences
922 North Oolitic Drive
Bloomington, Indiana

Client Name : RCH LLC
Project Number : 24-0455-11G
Logged By : J. Rogers
Start Date : 04/17/2024
Drilling Method : HSA

Driller : E. Thomas
Sampling : Splitspoon
Approx. Elevation : +/- 878 feet
Latitude : 39°10'31.23"N
Longitude : 86°33'11.77"W

Depth (Feet)	Elevation (Feet)	Water Level	USCS	GRAPHIC	Water Levels					REMARKS		
					▼ During Drilling - Dry	▽ After Completion - Dry	◆ After 24 Hours - N/A	Samples	Rec %		SPT Results	qp tsf
DESCRIPTION												
0	878				TOPSOIL (5")							
			CL		Brown, moist, stiff, SILTY CLAY with trace asphalt (FILL)	1	94	4/5/5		21	Boring caved to 8 feet upon auger removal.	
3.75			CL		Brown, moist, medium stiff, SILTY CLAY with trace asphalt (FILL)	2	56	4/5/5				
5			CL		Brown, moist, medium stiff, SILTY CLAY with trace asphalt (FILL)	3	33	4/4/3		19		
8.75			CL		Brown, moist, medium stiff, SILTY CLAY with some gravel and brick (FILL)	4	17	1/3/2				
10			CL		Brown, moist, medium stiff, SILTY CLAY with some gravel and brick (FILL)	5	67	9/11/12	3.3	32		
15	865		CH		Red, very moist, stiff to hard, CLAY	6	100	4/9/12	3.0	37		
20	860		Boring terminated at 20 feet.					Groundwater was not encountered during drilling, nor upon completion.				
25	855											

BORING LOG KEY

UNIFIED SOIL CLASSIFICATION SYSTEM (USCS) FIELD CLASSIFICATION SYSTEM FOR SOIL EXPLORATION

NON-COHESIVE SOILS (Silt, Sand, Gravel, and Combinations)

Density	Field Identification (SPT Blows/ft)	Grain Size Terminology		
		<u>Soil Fraction</u>	<u>Particle Size</u>	<u>US Standard Sieve Size</u>
Very Loose	0 - 4	Boulders	> 12 inches	> 12 inches
Loose	5 - 10	Cobbles	3 - 12 inches	3 - 12 inches
Medium Dense	11 - 30	Gravel: Coarse	¾ - 3 inches	¾ - 3 inches
Dense	31 - 50	Small	4.76 mm - ¾ inch	No. 4 - ¾ inches
Very Dense	> 51	Sand: Coarse	2.00 - 4.76 mm	No. 10 - No. 4
		Medium	0.42 - 2.00 mm	No. 40 - No. 10
		Fine	0.074 - 0.42 mm	No. 200 - No. 40
		Silt	0.005 - 0.074 mm	< No. 200
		Clay	< 0.005 mm	< No. 200

RELATIVE PROPORTIONS FOR SOILS

<u>Descriptive Term</u>	<u>Percent</u>
Trace	1 - 10
Little	11 - 20
Some	21 - 35
And	36 - 50

COHESIVE SOILS

(Clay, Silt and Combinations)

<u>Consistency</u>	<u>Unconfined Compressive Strength (tons/ft²)</u>	<u>Field Identification (SPT Blows/ft)</u>
Very Soft	Less than 0.25	0 - 2
Soft	0.25 - < 0.5	3 - 4
Medium Stiff	0.5 - < 1.0	5 - 8
Stiff	1.0 - < 2.0	9 - 15
Very Stiff	2.0 - < 4.0	16 - 30
Hard	Over 4.0	> 30

Classification: Provided on Boring Logs are made by visual inspection.


Standard Penetration Test: Driving a 2 inch outer-diameter (O.D.) by 1½ inch inner-diameter (I.D.) split-spoon sampler a total of 18 inches into undisturbed soil with the number of blows of a 140 pound hammer free-falling a distance of 30 inches recorded for each 6 inches of penetration. The sum of blows for the final 12 inches of penetration is the Standard Penetration Test result commonly referred to as the "N"-value (or blow-count).

Strata Changes: In the column "Descriptions" on the Boring Logs the horizontal lines represent strata changes. A solid line (——) represents an observed change, a dashed line (- - - -) represents an estimated change.

Groundwater: Observations were made at the times indicated on the Boring Logs. Fluctuations in the groundwater level should be expected over time due to variations in rainfall and other environmental or physical factors. *Groundwater symbols:* (▼)-observed groundwater level and/or elevation during drilling; (▽)-observed groundwater level and/or elevation upon completion of boring.

Unified Soil Classification System (USCS)


Major Divisions		Group Symbol	Typical Names	Classification Criteria for Coarse-Grained Soils				
Coarse-grained soils (more than half of material is larger than No. 200)	Gravels (more than half of coarse fraction is larger than No. 4 sieve size)	Clean gravels (little or no fines)	GW	Well-graded gravels, gravel-sand mixtures, little or no fines	$C_u \geq 4$ $1 \leq C_c \leq 3$	$C_u = \frac{D_{60}}{D_{10}}$	$C_c = \frac{D_{30}^2}{D_{10} D_{60}}$	
		Poorly graded gravels, gravel-sand mixtures, little or no fines	GP	Not meeting all gradation requirements for GW ($C_u < 4$ or $1 > C_c > 3$)				
		Gravels with fines (appreciable amount of fines)	GM	$\frac{U}{s}$	Silty gravels, gravel-sand-silt mixtures	Atterberg limits below A line or $P_I < 4$		Above A line with $4 < P_I < 7$ are borderline cases requiring use of dual symbols
			GC		Clayey gravels, gravel-sand-clay mixtures	Atterberg limits above A line or $P_I > 7$		
	Sands (more than half of coarse fraction is smaller than No. 4 sieve size)	Clean sands (little or no fines)	SW	Well-graded sands, gravelly sands, little or no fines	$C_u \geq 6$ $1 \leq C_c \leq 3$	$C_u = \frac{D_{60}}{D_{10}}$	$C_c = \frac{(D_{30})^2}{D_{10} D_{60}}$	
			SP	Not meeting all gradation requirements for SW ($C_u < 6$ or $1 > C_c > 3$)				
		Sands with fines (appreciable amount of fines)	SM	$\frac{U}{s}$	Silty sands, sand-silt mixtures	Atterberg limits below A line or $P_I < 4$		Limits plotting in hatched zone with $4 \leq P_I \leq 7$ are borderline cases requiring use of dual symbols
			SC		Clayey sands, sand-clay mixtures	Atterberg limits above A line with $P_I > 7$		
	Fine-grained soils (more than half of material is smaller than No. 200)	Silt and clays (liquid limit <50)	ML	Inorganic silts and very fine sands, rock flour, silty or clayey fine sands, or clayey silts with slight plasticity	<ol style="list-style-type: none"> Determine percentages of sand and gravel from grain size curve. Depending on percentages of fines (fraction smaller than 200 sieve size), coarse-grained soils are classified as follows: Less than 5% - GW, GP, SW, SP More than 12% - GM, GC, SM, SC 5-12% - Borderline cases requiring dual symbols 			
			CL	Inorganic clays of low to medium plasticity, gravelly clays, sandy clays, silty clays, lean clays				
OL			Organic silts and organic silty clays of low plasticity					
Silt and clays (liquid limit >50)		MH	Inorganic silts, micaceous or diatomaceous fine sandy or silty soils, elastic silts					
		CH	Inorganic clays or high plasticity, fat clays					
		OH	Organic clays of medium to high plasticity, organic silts					
Highly organic soils		PT	Peat and other highly organic soils					



APPENDIX B

SEISMIC SITE CLASS EVALUATION

 This is a beta release of the new ATC Hazards by Location website. Please [contact us](#) with feedback.

 The ATC Hazards by Location website will not be updated to support ASCE 7-22. [Find out why.](#)


ATC Hazards by Location

Search Information


Address: 922 N Oolitic Dr, Bloomington, IN 47404, USA
Coordinates: 39.175149, -86.5534332
Elevation: 879 ft
Timestamp: 2024-05-03T13:50:55.486Z
Hazard Type: Seismic
Reference Document: IBC-2012
Risk Category: II
Site Class: C



MCER Horizontal Response Spectrum



Design Horizontal Response Spectrum



Basic Parameters

Name	Value	Description
S_S	0.225	MCE _R ground motion (period=0.2s)
S_1	0.107	MCE _R ground motion (period=1.0s)
S_{MS}	0.269	Site-modified spectral acceleration value
S_{M1}	0.181	Site-modified spectral acceleration value
S_{DS}	0.18	Numeric seismic design value at 0.2s SA
S_{D1}	0.121	Numeric seismic design value at 1.0s SA

Additional Information

Name	Value	Description
SDC	B	Seismic design category
F_a	1.2	Site amplification factor at 0.2s
F_v	1.693	Site amplification factor at 1.0s
CR_S	0.9	Coefficient of risk (0.2s)
CR_1	0.854	Coefficient of risk (1.0s)
PGA	0.107	MCE _G peak ground acceleration
F_{PGA}	1.2	Site amplification factor at PGA
PGA_M	0.128	Site modified peak ground acceleration
T_L	12	Long-period transition period (s)
$SsRT$	0.225	Probabilistic risk-targeted ground motion (0.2s)
$SsUH$	0.25	Factored uniform-hazard spectral acceleration (2% probability of exceedance in 50 years)
SsD	1.5	Factored deterministic acceleration value (0.2s)
$S1RT$	0.107	Probabilistic risk-targeted ground motion (1.0s)
$S1UH$	0.125	Factored uniform-hazard spectral acceleration (2% probability of exceedance in 50 years)
$S1D$	0.6	Factored deterministic acceleration value (1.0s)

PGAd	0.6	Factored deterministic acceleration value (PGA)
------	-----	---

The results indicated here DO NOT reflect any state or local amendments to the values or any delineation lines made during the building code adoption process. Users should confirm any output obtained from this tool with the local Authority Having Jurisdiction before proceeding with design.

Please note that the ATC Hazards by Location website will not be updated to support ASCE 7-22. [Find out why.](#)

Disclaimer

Hazard loads are provided by the U.S. Geological Survey [Seismic Design Web Services](#).

While the information presented on this website is believed to be correct, ATC and its sponsors and contributors assume no responsibility or liability for its accuracy. The material presented in the report should not be used or relied upon for any specific application without competent examination and verification of its accuracy, suitability and applicability by engineers or other licensed professionals. ATC does not intend that the use of this information replace the sound judgment of such competent professionals, having experience and knowledge in the field of practice, nor to substitute for the standard of care required of such professionals in interpreting and applying the results of the report provided by this website. Users of the information from this website assume all liability arising from such use. Use of the output of this website does not imply approval by the governing building code bodies responsible for building code approval and interpretation for the building site described by latitude/longitude location in the report.

APPENDIX C

GENERAL QUALIFICATIONS

**STANDARD CLAUSE FOR UNANTICIPATED
SUBSURFACE CONDITIONS**

GENERAL QUALIFICATIONS
of Patriot Engineering's Geotechnical Engineering Investigation

This report has been prepared at the request of our client for his use on this project. Our professional services have been performed, findings obtained, and recommendations prepared in accordance with generally accepted geotechnical engineering principles and practices. This warranty is in lieu of all other warranties either expressed or implied.

The scope of our services did not include any environmental assessment or investigation for the presence or absence of wetlands, hazardous or toxic materials in the soil, groundwater, or surface water within or beyond the site studied. Any statements in this report or on the test borings logs regarding vegetation types, odors or staining of soils, or other unusual conditions observed are strictly for the information of our client and the owner.

This report may not contain sufficient information for purposes of other parties or other uses. This company is not responsible for the independent conclusions, opinions or recommendations made by others based on the field and laboratory data presented in this report. Should there be any significant differences in structural arrangement, loading or location of the structure, our analysis should be reviewed.

The recommendations provided herein were developed from the information obtained in the test borings, which depict subsurface conditions only at specific locations. The analysis, conclusions, and recommendations contained in our report are based on site conditions as they existed at the time of our exploration. Subsurface conditions at other locations may differ from those occurring at the specific drill sites. The nature and extent of variations between borings may not become evident until the time of construction. If, after performing on-site observations during construction and noting the characteristics of any variation, substantially different subsurface conditions from those encountered during our explorations are observed or appear to be present beneath excavations, we must be advised promptly so that we can review these conditions and reconsider our recommendations where necessary.

If there is a substantial lapse of time between the submission of our report and the start of work at the site, or if conditions have changed due to natural causes or construction operations at or adjacent to the site, we urge that our report be reviewed to determine the applicability of the conclusions and recommendations considering the changed conditions and time lapse.

We urge that Patriot be retained to review those portions of the plans and specifications that pertain to earthwork and foundations to determine whether they are consistent with our recommendations. In addition, we are available to observe construction, particularly the compaction of structural backfill and preparation of the foundations, and such other field observations as may be necessary.

In order to fairly consider changed or unexpected conditions that might arise during construction, we recommend the following verbiage (Standard Clause for Unanticipated Subsurface Conditions) be included in the project contract.

STANDARD CLAUSE FOR UNANTICIPATED SUBSURFACE CONDITIONS

"The owner has had a subsurface exploration performed by a soils consultant, the results of which are contained in the consultant's report. The consultant's report presents his conclusions on the subsurface conditions based on his interpretation of the data obtained in the exploration. The contractor acknowledges that he has reviewed the consultant's report and any addenda thereto, and that his bid for earthwork operations is based on the subsurface conditions as described in that report. It is recognized that a subsurface exploration may not disclose all conditions as they actually exist and further, conditions may change, particularly groundwater conditions, between the time of a subsurface exploration and the time of earthwork operations. In recognition of these facts, this clause is entered in the contract to provide a means of equitable additional compensation for the contractor if adverse unanticipated conditions are encountered and to provide a means of rebate to the owner if the conditions are more favorable than anticipated.

At any time during construction operations that the contractor encounters conditions that are different than those anticipated by the soils consultant's report, he shall immediately (within 24 hours) bring this fact to the owner's attention. If the owner's representative on the construction site observes subsurface conditions which are different than those anticipated by the consultant's report, he shall immediately (within 24 hours) bring this fact to the contractor's attention. Once a fact of unanticipated conditions has been brought to the attention of either the owner or the contractor, and the consultant has concurred, immediate negotiations will be undertaken between the owner and the contractor to arrive at a change in contract price for additional work or reduction in work because of the unanticipated conditions. The contract agrees that the following unit prices would apply for additional or reduced work under the contract. For changed conditions for which unit prices are not provided, the additional work shall be paid for on a time and materials basis."

Another example of a changed conditions clause can be found in paper No. 4035 by Robert F. Borg, published in ASCE Construction Division Journal, No. CO2, September 1964, page 37.

**BLOOMINGTON BOARD OF ZONING APPEALS
STAFF REPORT****CASE #: V-13-24/VAR-2024-04-0030
DATE: May 23, 2024****Location: 918 N Oolitic Dr (parcel # 53-05-32-201-106.058-005) (Lot 58 of Forest Homes)**

PETITIONER: Ruby Creek Homes
11990 E 1400 N, Oden, IN 47562**CONSULTANTS:** Melvin Graber
11990 E 1400 N, Oden, IN 47562

REQUEST: Variance from Karst Preservation standards to allow disturbance within 25' of the last closed contour of a karst feature for a property in the Residential Medium Lot (R2) zoning district.

REPORT: This 0.193-acre property is located at 918 N Oolitic Dr. The property is zoned Residential Medium Lot (R2). Surrounding zones are all Residential Medium Lot (R2) and surrounding land uses are all Dwelling, Single Family (detached).

Previous to the current owner, this lot of record, along with the Forest Homes Lots 57 and 59 (914 and 922 N Oolitic), were owned by the same owner and two mobile homes sat on all three lots for many years.

There is a karst feature, a sinkhole, located on this property. Existing elevations on this site range from 872 feet to 876 feet and the lowest portion of the sinkhole is on the south and southwest portions of this property. Evidence of makeshift flood control techniques and pumps were found on the site, demonstrating that the property owners experienced flooding on site. There is currently no stormwater infrastructure at or near this site.

Chapter 4 of the Unified Development Ordinance (UDO), Title 20 of the Bloomington Municipal Code) states that no land-disturbing activity, mowing, or temporary or permanent structure shall be allowed within the sinkhole nor within 25 feet of the last closed contour of the sinkhole. Title 20 of the UDO defines the sinkhole as the last closed contour line of the feature on the City's geographic information system. Historic contour mapping shows that this entire property located at 918 N Oolitic falls within the last closed contours of the karst feature, which is at an elevation of 882 feet, which means that according to the UDO, the entire lot cannot be disturbed. This lot contains the lowest point a sinkhole that covers multiple properties. Since this entire site lies within the area shown to be within the last closed contour of the karst feature, a variance must be granted to allow any disturbance on this property.

The petitioner is requesting a variance from the karst preservation standards to allow disturbance within 25' of the last closed contour of the karst feature.

As part of this variance request, a report of geotechnical engineering exploration was submitted. The report confirmed that a sinkhole is present on the site and it provided information about soil

composition in two locations on this property through analysis of soil borings. The report also provided sinkhole remediation methods of treatment and construction recommendations for placing a single family structure on the site.

CRITERIA AND FINDINGS FOR DEVELOPMENT STANDARDS VARIANCE

20.06.080(b)(3)(E) Standards for Granting Variances from Development Standards:

A variance from the development standards of the Unified Development Ordinance may be approved only upon determination in writing that each of the following criteria is met:

- 1) *The approval will not be injurious to the public health, safety, morals, and general welfare of the community.*

PROPOSED FINDING: The granting of the variance may be injurious to the public health, safety, morals, or general welfare of the community. A number of structures have existed in and around this karst feature for many years with no collapse. Building at the lowest point of the sinkhole increases the likelihood of local flooding. However, proper testing of and restoration of the site will be required before building construction is allowed in order to maximize water infiltration on the site and ensure that water is not diverted off site, and to make sure that the site is safe for construction.

- 2) *The use and value of the area adjacent to the property included in the Development Standards Variance will not be affected in a substantially adverse manner.*

PROPOSED FINDING: Adverse impacts to the use and value of surrounding properties as a result of the requested variance are possible if proper mitigation is not completed. The majority of this property is located in the lowest portion of the area, is most susceptible to flooding and is a collecting point for runoff from several properties. Current site elevation conditions show that the portions of the karst feature that are most sensitive are found on this property. Sinkhole remediation at this site will be required with approvals to building at 914 and 922 N Oolitic - the properties north and south adjacent to this site. If the conditions of approval included are successfully completed, the granting of the variance should not have adverse impacts on the use and value of surrounding properties.


- 3) *The strict application of the terms of the Unified Development Ordinance will result in practical difficulties in the use of the property; that the practical difficulties are peculiar to the property in question; that the Development Standards Variance will relieve the practical difficulties.*

PROPOSED FINDING: The strict application of the terms of the Unified Development Ordinance will result in practical difficulties in the use of the property because it renders the entire site unbuildable. There has been development within the last closed contour of this feature for a number of years without any indications of negative impact. The practical difficulties are peculiar to the property in question because it is uncommon for an entire property to be located within a UDO-defined sinkhole, but because the properties in this area

are smaller, the extent of the last closed contour of the sinkhole renders the entire site unusable.


RECOMMENDATION: The Department recommends that the Board of Zoning Appeals adopt the proposed findings and approve V-13-24/ VAR-2024-04-0030.


1. Development of this lot is limited to the east half of the lot in order to maximize the area of land present between development and movement of water toward the sinkhole.
2. Implementation of sinkhole remediation as outlined in the attached geotechnical report, is required – at all three properties (914, 918 and 922 N Oolitic) - before any Certificate of Zoning Compliances will be issued.
3. Submission of a drainage and water flow analysis post-sinkhole remediation is required before a Certificate of Zoning Compliance will be issued. The report must be approved by City of Bloomington Planning & Transportation and Utility Departments.
4. Implementation of design and construction recommendations provided in the attached geotechnical report is required before a Certificate of Zoning Compliance will be issued.
5. Testing of soil and water contamination testing and provision of any necessary remediation identified related to those tests is required before a Certificate of Zoning Compliance will be issued.
6. A Zoning Commitment shall be recorded indicating the presence of the karst feature and describing the Karst Conservancy Easement before a Certificate of Zoning Compliance will be issued.



Map Legend


- Addresses
- Parcels
- Sinkholes
- Contours 2021
- Bloomington Municipal Boundary






Map Legend

- Addresses
- Parcels
- Sinkholes
- Contours 2021
- Bloomington Municipal Boundary
- Planned Unit Development
- Residential Medium Lot
- Mixed-Use Employment





To Whom it may concern,

Ruby Creek Homes LLC (RCH) is requesting a variance from code UDO 20.04.030 (g) Pursuant to Indiana Code 36-7-4-918.5.

Project Location

914, 918, 922 N Oolitic Dr.

(See Attached Survey)

Scope of Project

In 2023, 2 deteriorated homes were removed from said properties (Demo Permit #s R-23-610, R-23-612) for the:

Purpose of

New Home Construction

See Attached Site Plan

Difficulties

The strict application of UDO 20.04.030 (g) renders the entire properties undevelopable, for which use it was previously intended.

See Attached - Forrest Homes Development Recording 1927

Granting the requested variance would:


Improve neighboring Property values

And would be an asset rather than a liability to public health safety and general welfare of the community by providing much needed and deficient "Affordable Housing".

Site Plans for New Home Const.

922, 918 Oolitic Drive, Lots 58, 59

staff note: these plans will likely need to change according to any variance conditions that are approved -KAG



staff note: these plans will likely need to change according to any variance conditions that are approved -KAG



Camera 3

©2021 Ken Wagler. All rights reserved. No part of this document may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, without the prior written permission of Ken Wagler. This document is the property of Ken Wagler and is to be used only for the project and location specified. Any other use is strictly prohibited. Ken Wagler, 8227 N 725 E, Cotton, IN 47522. Phone: 812-466-4328. Email: khwagler88@slc.email

DRAWINGS PROVIDED BY:
Ken Wagler
8227 N 725 E
Cotton, IN 47522
812-466-4328
khwagler88@slc.email

DATE:
1/20/2023

SCALE:

SHEET:


P-1

Project Overview

Maple - C

New Plans For.....


OWNER: [REDACTED]
CONTRACT NO.: [REDACTED]
DATE: [REDACTED]
PROJECT: [REDACTED]
SHEET NO.: [REDACTED]
SHEET TOTAL: [REDACTED]
DRAWING: [REDACTED]
SCALE: [REDACTED]
DATE: [REDACTED]




1st Floor

FRAMING NOTES


- ALL EXTERIOR WALLS ARE SHOWN AS 4" WALLS UNLESS NOTED OTHERWISE
- ALL INTERIOR WALLS ARE SHOWN AS 3 1/2" WALLS UNLESS NOTED OTHERWISE
- 4" 1/2" WALLS UNLESS NOTED OTHERWISE
- ALL EXTERIOR WINDOWS TO BE [REDACTED]
- ALL EXTERIOR DOORS TO BE [REDACTED]
- WINDOWS E.O. INCLUDED FOR SILVERLINE WINDOWS
- ALL HEADER HEIGHTS AT 8" UNLESS NOTED OTHERWISE




Elevation 4



Elevation 1




Elevation 3




Elevation 2

ALL INFORMATION CONTAINED HEREIN IS UNCLASSIFIED EXCEPT WHERE SHOWN OTHERWISE. DATE OF DECLASSIFICATION IS INDEFINITE. AUTHORITY: 50 CFR 17.102 (a).

OWNER: [REDACTED]
CONTRACTOR: [REDACTED]
ARCHITECT: [REDACTED]
DATE: [REDACTED]
PROJECT: [REDACTED]
SHEET: [REDACTED] OF [REDACTED]
DRAWING: [REDACTED]
SCALE: [REDACTED]
SHEET: [REDACTED] OF [REDACTED]



Foundation



Attic











REPORT OF GEOTECHNICAL ENGINEERING EXPLORATION

**OOLITIC DRIVE RESIDENCES
BLOOMINGTON, INDIANA**

PREPARED FOR:

**RCH, LLC
1190 EAST 1400 NORTH
ODON, INDIANA 47562**

**Patriot Engineering and Environmental, Inc.
2006 South Yost Avenue
Bloomington, Indiana 47403**

May 6, 2024



May 6, 2024

Mr. Melvin Graber
RCH, LLC
11990 East 1400 North
Odon, Indiana 47562

Re: **Report of Geotechnical Engineering Exploration
Oolitic Drive Residences
922 North Oolitic Drive
Bloomington, Indiana
Patriot Project No.: 24-0455-11G**


Dear Melvin:

Attached is the report of our geotechnical engineering exploration for the above referenced project. This exploration was completed in general accordance with our Proposal No. P24-0688-11G dated March 25, 2024.


This report includes detailed and graphic logs of six (6) soil borings drilled at the proposed project site. Also included in the report are the results of laboratory tests performed on samples obtained from the site, and geotechnical recommendations pertinent to the site development, foundation design, and construction.

We appreciate the opportunity to perform this geotechnical engineering exploration and are looking forward to working with you during the construction phase of the project. If you have any questions regarding this report or if we may be of any additional assistance regarding any geotechnical aspect of the project, please do not hesitate to contact our office.

Respectfully submitted,
Patriot Engineering and Environmental, Inc.



Mark Jonard, E.I.
Geotechnical Engineer



William D. Dubois, P.E.
Senior Principal Engineer

TABLE OF CONTENTS

1.0 INTRODUCTION	1
1.1 General	1
1.2 Purpose and Scope	1
2.0 PROJECT INFORMATION	1
3.0 SITE AND SUBSURFACE CONDITIONS	2
3.1 Site Conditions	2
3.2 General Subsurface Conditions	2
3.3 Groundwater Conditions	3
4.0 DESIGN RECOMMENDATIONS	4
4.1 Basis	4
4.2 Overall Site Evaluation.....	4
4.3 Foundations	5
4.4 Floor Slabs	7
4.5 Seismic Considerations	7
5.0 CONSTRUCTION CONSIDERATIONS	8
5.1 Site Preparation.....	8
5.2 Sinkhole Remediation.....	9
5.3 Foundation Excavations	10
5.4 Structural Fill and Fill Placement Control.....	11
5.5 Groundwater Considerations	12
6.0 EXPLORATIONAL PROCEDURES	13
6.1 Field Work	13
6.2 Laboratory Testing.....	13
7.0 ILLUSTRATIONS	14

APPENDICES

Appendix A:	Site Vicinity Map (Figure No. 1)
	Boring Location Map (Figure No. 2)
	Boring Logs
	Boring Log Key
	Unified Soil Classification System (USCS)
Appendix B:	Seismic Site Class Evaluation
Appendix C:	General Qualifications
	Standard Clause for Unanticipated Subsurface Conditions

REPORT OF GEOTECHNICAL ENGINEERING EXPLORATION

**Oolitic Drive Residences
922 Oolitic Drive
Bloomington, Indiana
Patriot Project No.: 24-0455-11G**

1.0 INTRODUCTION

1.1 General

RCH, LLC is planning the construction of a three (3) small single-family homes to be located at the three (3) lots at 922 North Oolitic Drive in Bloomington, Indiana. The results of our geotechnical engineering exploration for the project are presented in this report.

1.2 Purpose and Scope

The purpose of this exploration is to determine the general near surface and subsurface conditions within the project area and to develop the geotechnical engineering recommendations necessary for the design and construction of the proposed structures. This was achieved by drilling soil borings, and by conducting laboratory tests on samples taken from the borings. This report contains the results of our findings, an engineering interpretation of these results with respect to the available project information, and recommendations to aid in the design and construction of the proposed facility.

2.0 PROJECT INFORMATION

The proposed project is located along Oolitic Drive in Bloomington, Indiana. The project consists of three (3) single-family homes being built. These homes will be one (1)-story structures of slab-on-grade construction, approximately 32 feet by 48 feet of in plan dimension.

No structural loading information is available to us at the time of this report, but based on similar projects in the area, we can estimate that the proposed structures will have wall loads not exceeding 1,500 pounds per lineal foot (plf), isolated column loads not exceeding 60 kips, and that floor loads will not exceed 150 pounds per square foot (psf). Additionally, based on visual observations of the existing site, it is assumed that any grade raise fill to complete the construction of building pads, finished pavement subgrades, etc., will not exceed 2 feet above the existing ground surface.

3.0 SITE AND SUBSURFACE CONDITIONS

3.1 Site Conditions

The project site is presently an approximately 0.6 acres used for residential purposes. There were previously two (2) modular homes that were removed prior to our mobilization. The surrounding area is generally an area of residential development. The topography in the area proposed for construction is sloped down towards the center of the site, where a recorded sinkhole, per the Indiana Sinkhole Inventory provided by the Indiana Geological Survey, is present. Although the proposed buildings are not planned to be placed above the sinkhole, remediation is required for the project.

3.2 General Subsurface Conditions

Our interpretation of the subsurface conditions is based upon six (6) soil borings drilled at the approximate locations shown on the Boring Location Map (Figure No. 2) in Appendix "A". All depths discussed below refer to depths below the existing ground surface. Based on the results of the soil borings completed at the site, the following subsurface profile is presented. A description of each general soil unit has been identified and is described below:

Topsoil – Topsoil, a surficial layer of material that is a blend of silts, sands, and clays, with varying amounts of organic matter, was encountered at the ground surface at all of the six (6) boring locations. The topsoil layer was about 3 to 8 inches thick in the borings.

Silty Clay (CL) - The surficial layer is generally underlain by brown, slightly moist to very moist, soft to very stiff, silty clay. The silty clay layers extended to depths of 6 to 13.5 feet below the existing ground surface. The natural moisture content of this material ranges from 16 to 29 percent (%). The silty clay layers have unconfined compressive strengths, as determined by a hand penetrometer, of 1.9 to 4.5 tons per square foot (tsf). Standard Penetration Test N-values in this material varied from 4 to 23 blows per foot (bpf). Additionally, fill material, such as asphalt, gravel, brick and organics, was observed in multiple borings to varying depths (see the Table 1 below).

Clay (CH) - The silty clay layer is underlain by red, moist to very moist, medium stiff to hard, *High plasticity* clay. The clay layers extended to depths of 10 to 20 feet below the existing ground surface. The natural moisture content of this material ranges from 26 to 40 %. The silty clay layers have unconfined compressive strengths of 3.0 to 3.9 tsf. Standard Penetration Test N-values in this material varied from 13 to greater than 50 bpf.

Limestone – Below the clay layers at auger refusal, highly weather limestone was present.

The soil conditions described above are general, and some variations in the descriptions should be expected; for more specific information, please refer to the boring logs presented in Appendix “A”. It should be noted that the dashed stratification lines shown on the soil boring logs indicate approximate transitions between soil types. In-situ stratification changes could occur gradually or at different depths.

As previously mentioned, soft clays and unsuitable fill material were encountered in four (4) of the six (6) borings, at depths up to 13.5 feet below the existing ground surface. The following table presents the extent of the unsuitable soils encountered in the borings:

Table No. 1: Summary of Unsuitable Soils Encountered in Borings

Boring Number	Soil Classification	Approximate Depth of Unsuitable Soils (feet) ⁽¹⁾
B-3	Silty Clay (CL) with some asphalt and gravel (FILL)	3.5 to 6
B-4	Silty Clay (CL) with some asphalt (FILL)	0 to 3.5
	Asphalt and Gravel (FILL)	3.5 to 6
B-5	Soft Silty Clay (CL) with a trace of gravel and organics (FILL)	0 to 6
B-6	Silty Clay (CL) with a trace of asphalt (FILL)	0 to 6
	Silty Clay (CL) with some gravel and brick (FILL)	6 to 13.5

⁽¹⁾ Represents depth below existing ground surface.

3.3 Groundwater Conditions

The term groundwater pertains to any water that percolates through the soil found on site. This includes any overland flow that permeates through a given depth of soil, perched water, and water that occurs below the “water table”, a zone that remains saturated and water-bearing year round.

Groundwater was observed during drilling in one (1) of the soil borings (B-5) performed at the site at depths of 13 feet below the existing ground surface. Groundwater was not observed in the remaining borings during drilling. Immediately after the borings were completed and the augers were removed from the boreholes, groundwater was not observed.

It should be recognized that fluctuations in the groundwater level should be expected over time due to variations in rainfall and other environmental or physical factors. ***The true static groundwater level can only be determined through observations made in cased holes over a long period of time, the installation of which was beyond the scope of this exploration.***

4.0 DESIGN RECOMMENDATIONS

4.1 Basis

Our recommendations are based on data presented in this report, which include soil borings, laboratory testing, and our experience with similar projects. Subsurface variations that may not be indicated by a dispersive exploratory boring program can exist on any site. If such variations or unexpected conditions are encountered during construction, or if the project information is incorrect or changed, we should be informed immediately since the validity of our recommendations may be affected.

4.2 Overall Site Evaluation

The borings indicate that the site is mostly underlain by clayey (CL) soils with fill materials observed in multiple borings. In general, the areas near soil borings performed may be suitable for the anticipated development following removal of the fill material. The soils will then be suitable for shallow foundations, and for support of floor slabs and pavements with these undercuts and soil replacement with compacted structural fill of the near surface soils. Additional Concerns for construction are listed below.

Expansive (Highly Plastic) Clays

Four (4) of the six (6) borings encountered highly plastic (expansive) clays (CH) at depths typically between about 6 and 20 feet below the existing ground surface. Expansive soils undergo volume changes upon wetting and drying. Expansive soils tend to shrink on drying and expand when the degree of saturation increases. However, the primary factors

that govern the amount of expansion of the soils are the availability of moisture and the amount and type of clay particles in the soil.

In Indiana, typically expansive soils within the upper 5 to 10 feet of the surface grade are influenced most by climatic environmental factors, which affect the water content of the soils and hence cause the soils to shrink and swell. This range of influence is generally referred to as the active zone. Foundations, floor slabs, pavements and subsurface utilities placed on or in this active zone of highly plastic (expansive) clays can be subjected to detrimental effects of shrink and swell; which can cause unsuitable total and/or differential settlements, along with cracking. Therefore, we recommend that foundations, floor slabs, pavements, other infrastructure not bear or be placed directly on highly plastic clays (CH). Positive drainage of surface water both during construction and after construction is complete will be especially important to reduce the amount of surface water that is allowed to permeate into the subgrade soils and subsequently reduce the potential for unsuitable shrinking or swelling of the underlying highly plastic clays. Water and drainage lines should be located such that if any leakage occurs, water will not be readily accessible to foundations, floor slabs and/or pavement sections. Additionally, the installation and use of an irrigation system at the parcel is highly discouraged.

Karst

The project site is located within a region known for karstic features. Karstic areas are typically associated with the development of solution features within the soluble carbonate bedrock leading to formation of sinkholes. A sinkhole is described as “Closed depression in soil or bedrock formed by the erosion and transport of earth material from below the land surface.” Sinkholes may develop within karstic areas as a result of soil fines migrating from the overburden soil by infiltrating water flowing downward into the bedrock through solution features/channels, such as voids and clay seams within the rock. Sinkholes may consist of a relatively localized weathered feature or larger features resulting from a collapse within a void formed in the overburden soils as a result of loss of the fine soils into the bedrock features. A sinkhole was observed on-site, as well as confirmed by the Indiana Sinkhole Inventory provided by the Indiana Geological Survey. Recommendations for remediation can be found in Section 5.2. If further evaluation of karst is desired, *Patriot* can provide geophysical testing services.

4.3 Foundations

As previously mentioned, unsuitable fill material was encountered in four (4) of the six (6) to depths up to 13.5 feet below existing grade and it is highly likely that potential existing fill

materials could be present within the project area due to previous construction activities. ***If soft clays, existing fill materials, or other unsuitable materials are encountered at the footing level or below, they must be undercut 3 feet below the bottom of the foundation and replaced with well-compacted structural fill prior to construction of foundations or the footings can be extended to suitable natural soils.*** Following the excavation of the footing areas, the foundations subgrade should be visually inspected by a *Patriot* representative and probed at multiple locations at isolated footings and at every 10 feet (maximum) along wall footings using a Dynamic Cone Penetrometer (DCP) to a minimum depth of 5 feet below the footing subgrade to verify that the underlying soil has a SPT blow count of 7 or more or unconfined compressive strength of 1.0 tsf or more. Any unsuitable soils encountered at the footing subgrade or below should be removed and replaced with well-compacted structural fill.

Provided the above recommendations are followed, the proposed structure can be supported on spread footings bearing on the medium stiff to very stiff silty clay encountered at shallow depths or on new well-compacted structural fill overlying the same. These footings should be proportioned using a net allowable soil bearing pressure not exceeding 2,000 pounds per square foot (psf) for column footings or 1,500 psf for wall (strip) footings. For proper performance at the recommended design bearing pressure, foundations must be constructed in compliance with the recommendations for footing excavation inspection that are discussed in Section 5.0 “*Construction Considerations*”.

In using the above net allowable soil bearing pressures, the weight of the foundation and backfill over the foundation need not be considered. Hence, only loads applied at or above the minimum finished grade adjacent to the footing need to be used for dimensioning the foundations. Each new foundation should be positioned so it does not induce significant pressure on adjacent foundations; otherwise the stress overlap must be considered in the design.

All exterior foundations and foundations in unheated areas should be located at a depth of at least 24 inches below final exterior grade for frost protection. We recommend that wall (strip) footings be at least 18 inches wide and column footings be at least 24 inches wide for bearing capacity considerations.

We estimate that the total foundation settlement should not exceed approximately 1 inch and that differential settlement should not exceed about $\frac{3}{4}$ inch. Careful field control during construction is necessary to minimize the actual settlement that will occur.

Positive drainage of surface water, including downspout discharge, should be maintained away from structure foundations to avoid wetting and weakening of the foundation soils both during construction and after construction is complete.

4.4 Floor Slabs

The near surface or shallow subgrade soils encountered within the proposed building footprint generally consist of medium stiff to stiff silty clay and fill material. While the silty clay material is suitable for floor slab support, the fill material is not. ***If soft clays, existing fill materials, or other unsuitable materials are encountered at the floor slab subgrade, they must be undercut and replaced with well-compacted structural fill prior to construction of floor slabs.***

We recommend that all floor slabs be designed as "floating", that is, fully ground supported and not structurally connected to walls or foundations. This is to minimize the possibility of cracking and displacement of the floor slabs because of differential movements between the slab and the foundation. Although the movements are estimated to be within the tolerable limits for the structural safety, such movements could be detrimental to the slabs if they were rigidly connected to the foundations. Additionally, we recommend that all slabs should be liberally jointed and designed with the appropriate reinforcement for the anticipated loading conditions.

The building floor slabs should be supported on a minimum 6 inch thick well-compacted granular base course (i.e. Indiana Department of Transportation (INDOT) No. 53 crushed stone) bearing on a suitably prepared subgrade (Refer to Section 5.0 "*Construction Considerations*"). The granular base course is expected to help distribute loads and equalize moisture conditions beneath the slab.

Provided that the recommendations above for floor slab design and construction are followed, a modulus of subgrade reaction, "K₃₀" value of 75 pounds per cubic inch (pci), is recommended for the design of ground supported floor slabs. It should be noted that the "K₃₀" modulus is based on a 30 inch diameter plate load empirical relationship.

4.5 Seismic Considerations

For structural design purposes, we recommend using a ***Site Classification of "C"*** as defined by the Indiana Building Code (modified 2012 International Building Code (IBC)). Furthermore, along with using a Site Classification of "C", we recommend the use of the

maximum considered spectral response acceleration and design spectral response acceleration coefficients provided in Table No. 2 below. Refer to Appendix “B” for “*Seismic Site Class Evaluation*” report summary.

Table No. 2: Seismic Design Spectral Response Acceleration Coefficients

Period (seconds)	Maximum Considered Spectral Response Acceleration Coefficient	Soil Factor	Design Spectral Response Acceleration Coefficient
0.2	$S_S = 0.225 \text{ g}$	1.20	$S_{DS} = 0.180 \text{ g}$
1.0	$S_1 = 0.107 \text{ g}$	1.69	$S_{D1} = 0.121 \text{ g}$

These values were obtained from the “*Earthquake Ground Motion Parameters*” program for seismic design, developed by the United States Geological Survey (USGS) Earthquake Hazard Program, utilizing latitude 39.175149° north and longitude 86.5534332° west as the designation for identifying the location of the parcel. Other earthquake resistant design parameters should be applied consistent with the minimum requirements of the Indiana Building Code.

5.0 CONSTRUCTION CONSIDERATIONS

5.1 Site Preparation

All areas that will support foundations, floors, pavements or newly placed structural fill must be properly prepared. All loose surficial soil or “topsoil” and other unsuitable materials must be removed. Unsuitable materials include: frozen soil, relatively soft material, relatively wet soils, deleterious material, or soils that exhibit a high organic content.

Approximately 3 to 8 inches of loose surficial topsoil was encountered in the borings. The topsoil was measured at discrete locations as shown on the Boring Location Map (Figure No. 2) in Appendix “A”. The topsoil thickness measured at the boring locations may or may not be representative of the overall average topsoil thickness at the site. Therefore, it is possible that the actual stripping depth could significantly vary from this data. The data presented should be viewed only as a guide to the minimum stripping depth that will be

required to remove organic material at the surface. Additional field exploration by *Patriot* would be required to provide an accurate estimate of the stripping depth. This limited data indicates that a minimum stripping depth will be required to remove the organic material at the surface, followed by the potential for additional stripping and/or scarification and recompaction as may be required to achieve suitable subgrade support. ***Additionally, if saturated conditions exist with the surface soils, light tracked equipment could be required to avoid pushing organics deeper into the suitable subgrade soils.*** A *Patriot* representative should verify the stripping depth at the time grading operations occur.

Prior to construction of floor slabs, pavements or the placement of new structural fill, the exposed subgrade must be evaluated by a Patriot representative; which will include proofrolling of the subgrade. Proofrolling should consist of repeated passes of a loaded, pneumatic-tired vehicle such as a tandem-axle dump-truck or scraper. The proofrolling operations should be observed by a *Patriot* representative, and the proofrolling vehicle should be loaded as directed by *Patriot*. Any area found to rut, pump, or deflect excessively should be compacted in-place or, if necessary, undercut and replaced with structural fill, compacted as specified in Section 5.3 “*Structural Fill and Fill Placement Control*”.

Care must be exercised during grading and fill placement operations. ***The combination of heavy construction equipment traffic and excess surface moisture can cause pumping and deterioration of the near surface soils. The severity of this potential problem depends to a great extent on the weather conditions prevailing during construction.*** The contractor must exercise discretion when selecting equipment sizes and also make a concerted effort to control construction traffic and surface water while the subgrade soils are exposed. We recommend that heavy construction equipment (i.e. dump trucks, scrapers, etc.) be rerouted away from the building and pavement areas. If such problems do arise, the operations in the affected area should be halted and the *Patriot* representative contacted to evaluate the condition.

5.2 Sinkhole Remediation

The actual method used for the treatment of sinkholes is typically dependent on the depth to bedrock and the intended purpose of the area subjected to remediation. Several acceptable methods of treatment are discussed below.

If the depth to the top of bedrock is greater than 15 feet the following should be performed:

- Remove all debris from the hole

- Line hole with geotextile fabric (Mirafi 160N or equivalent), the geotextile fabric should be placed so that there is enough excess fabric to completely wrap the stone
- Backfill with No. 2 Crushed Limestone
- Wrap stone in geotextile fabric
- Place min 2 feet thick compacted clay soil cap, clay soil should be compacted to 100% of Standard Proctor maximum dry density

Please refer to Illustration A at the end of this report.

If the depth to the top of bedrock is less than 15 feet the following should be performed:

- Remove all debris from the hole
- Excavate to the top of the bedrock
- Line hole with geotextile fabric (Mirafi 160N or equivalent), the geotextile fabric should be placed so that there is enough excess fabric to completely wrap the stone
- Backfill with No. 2 Crushed Limestone
- Wrap stone in geotextile fabric
- Place 1 foot of compacted crushed limestone (DGA), compacted to 100% of standard proctor maximum dry density
- Place min 2 feet thick compacted clay soil cap, clay soil should be compacted to 100% of Standard Proctor maximum dry density
- Or instead of crushed limestone and soil cap, place 1-foot reinforced concrete cap

Please refer to Illustrations B and C at the end of this report.

5.3 Foundation Excavations

Upon completion of the foundation excavations and prior to the placement of reinforcing steel, a *Patriot* representative should check the exposed subgrade to confirm that a bearing surface of adequate strength has been reached. Any localized soft soil zones encountered at the bearing elevations should be further excavated until adequate support soils are encountered. The cavity should be backfilled with structural fill as defined below, or the footing can be poured at the excavated depth. Structural fill used as backfill beneath footings should be limited to lean concrete, well-graded sand and gravel, or crushed stone placed and compacted in accordance with Section 5.3 “*Structural Fill and Fill Placement Control*”.

If it is necessary to support spread footings on structural fill, the fill pad must extend laterally a minimum distance beyond the edge of the footing. The minimum structural pad

width would correspond with a point at which an imaginary line extending downward from the outside edge of the footing at a 1H:2V (horizontal: vertical) slope intersects the surface of the natural soils. For example, if the depth to the bottom of excavation is 4 feet below the bottom of the foundation, the excavation would need to extend laterally beyond the edge of the footing at least 2 feet, as shown in Illustration "A" found at the conclusion of this report.

Excavation slopes should be maintained within all requirements set-forth by the Occupational Safety and Health Standards (OSHA), but specifically Section 1926 Subpart "P" – "Excavations". We recommend that any surcharge fill or heavy equipment be kept at least 5 feet away from the edge of the excavation.

Construction traffic on the exposed surface of the bearing soil will potentially cause some disturbance of the subgrade and consequently loss of bearing capacity. However, the degree of disturbance can be minimized by proper protection of the exposed surface.

5.4 Structural Fill and Fill Placement Control

Structural fill, defined as any fill which will support structural loads, should be clean and free of organic material, debris, deleterious materials and frozen soils. Samples of the proposed fill materials should be tested prior to initiating the earthwork and backfilling operations to determine the classification, the natural and optimum moisture contents and maximum dry density and overall suitability as a structural fill. ***Structural fill should have a liquid limit less than 40 and a plasticity index less than 20.***

All structural fill beneath floor slabs, adjacent to foundations and over foundations, should be compacted to at least 95 percent (%) of its maximum Standard Proctor dry density (ASTM D-698). This minimum compaction requirement should be increased to 100 percent (%) of the maximum Standard Proctor dry density for fill supporting footings, provided these are designed as outlined Section 4.0 "Design Recommendations".

Structural fill supporting, around and over utilities should be compacted to at least 95 percent (%) of its maximum Standard Proctor dry density (ASTM D-698) for utilities underlying structural areas (i.e. buildings, pavements, sidewalks, etc.). However, the minimum compaction requirement can be reduced for backfill around and over the utilities to 90 percent (%) of the maximum Standard Proctor dry density where utilities underlie greenbelt areas (i.e. grassy lawns, landscaping, etc.). It is recommended that a

clean well-graded granular material be utilized as the bedding material, as well as the backfill material around and over the utility lines.

In cut areas, where pavement sections are planned, the upper 10 inches of subgrade should be scarified and compacted to a dry density of at least 100 percent (%) of the Standard Proctor maximum dry density (ASTM D-698). Any grade-raise fill placed within 1 foot of the base of the pavement section should also be compacted to at least 100 percent (%) of the Standard Proctor maximum dry density. This can be reduced to 95 percent (%) for structural fill placed more than 1 foot below the base of the pavement section.

To achieve the recommended compaction of the structural fill, we suggest that the fill be placed and compacted in layers not exceeding 8 inches in loose thickness (the loose lift thickness should be reduced to 6 inches when utilizing small hand compactors) and within the range of 2 percentage (%) points below or above the optimum moisture content value. All fill placement should be monitored by a *Patriot* representative. ***Each lift should be tested for proper compaction at a frequency of at least one (1) test every 2,500 square feet (ft²) per lift for the building areas, at least one (1) test every 10,000 square feet (ft²) per lift for the parking and roadway areas, and at a frequency of at least one (1) test for every 50 lineal feet of utility installation.***

5.5 Groundwater Considerations

Groundwater was observed during our field activities at depths between 13 feet below the existing ground surface (Refer to Section 3.3 “*Groundwater Conditions*”); which is expected to be below the anticipated foundation excavation depths. Depending on seasonal conditions, localized and sporadic groundwater infiltration may occur into the building foundation excavations on this site.

Groundwater inflow into shallow excavations **above** the groundwater table is expected to be adequately controlled by conventional methods such as gravity drainage and/or pumping from sumps. More significant inflow can be expected in deeper excavations **below** the groundwater table requiring more aggressive dewatering techniques, such as well or wellpoint systems. For groundwater to have minimal effects on the construction, foundation excavations should be constructed and poured in the same day, if possible.

6.0 EXPLORATIONAL PROCEDURES

6.1 Field Work

A total of six (6) soil borings were drilled, sampled, and tested at the project site on April 17, 2024 at the approximate locations shown on the Boring Location Map (Figure No. 2) in Appendix "A". The soil borings were drilled to depths of 20 feet in the proposed building area. All depths are given as feet below the existing ground surface.

The borings were advanced using 3¼ inch inside diameter hollow-stem augers. Samples were recovered in the undisturbed material below the bottom of the augers using the standard drive sample technique in accordance with ASTM D 1586-74. A 2 inch outside diameter by 1³/₈ inch inside diameter split-spoon sampler was driven a total of 18 inches with the number of blows of a 140 pound hammer falling 30 inches recorded for each 6 inches of penetration. The sum of blows for the final 12 inches of penetration is the Standard Penetration Test result commonly referred to as the N-value (or blow-count). Split-spoon samples were recovered at 2.5 feet intervals, beginning at a depth of 1 foot below the existing surface grade, extending to a depth of 10 feet, and at 5 feet intervals thereafter to the termination of the boring.

Water levels were monitored at each borehole location during drilling and upon completion of the boring. The boreholes were backfilled with auger cuttings prior to demobilization for safety considerations.

Upon completion of the boring program, all of the samples retrieved during drilling were returned to *Patriot's* soil testing laboratory where they were visually examined and classified. A laboratory-generated log of each boring was prepared based upon the driller's field log, laboratory test results, and our visual examination. Test boring logs and a description of the classification system are included in Appendix "A" in this report. Indicated on each log are: the primary strata encountered, the depth of each stratum change, the depth of each sample, the Standard Penetration Test results, groundwater conditions, and selected laboratory test data. The laboratory logs were prepared for each boring giving the appropriate sample data and the textural description and classification.

6.2 Laboratory Testing


Representative samples recovered in the borings were selected for testing in the laboratory to evaluate their physical properties and engineering characteristics. Laboratory analysis included: natural moisture content determinations (ASTM D 2216) and an

estimate of the unconfined compressive strength (q_u) of the cohesive soil samples utilizing a calibrated hand penetrometer (q_p) were obtained. The results of laboratory tests are summarized in Section 3.2 “*General Subsurface Conditions*”. Soil descriptions on the boring logs are in accordance with the Unified Soil Classification System (USCS).

7.0 ILLUSTRATIONS

See Illustrations “D” and “E” on the following pages. These illustrations are presented for reference for the remediation and backfill of sinkholes presented in Section 5.2.

See Illustrations “D” and “E” on the following pages. These illustrations are presented to further visually clarify several of the construction considerations presented in Section 5.3 “*Foundation Excavations*”.




Patriot Engineering & Environmental, Inc.

Project: Oolitic Drive Residences
922 North Oolitic Drive
Bloomington, Indiana

Drawn By: J. DuMond
Approved: B. Lauletta
DWG: 24-0455-11_detail

Project Number: 24-0455-11G
Date: May 2, 2024

Illustration A
Treatment Method for
Deep Sink Holes



Patriot Engineering & Environmental, Inc.

Project: Oolitic Drive Residences
922 North Oolitic Drive
Bloomington, Indiana

Project Number: 24-0455-11G


Date: May 2, 2024

Drawn By: J. DuMond

Approved: B. Lauletta

DWG: 24-0455-11_detail

Illustration B
Treatment Method for Sink Holes




SOIL OVERBURDEN <15'



Project: Oolitic Drive Residences 922 North Oolitic Drive Bloomington, Indiana	
Project Number: 24-0455-11G	Drawn By: J. DuMond
Date: May 2, 2024	Approved: B. Lauletta
	DWG: 24-0455-11_detail

Illustration C
Treatment Method for
Sink Holes



*d IS DEPTH TO SUITABLE SOILS


* IN COMPLIANCE WITH OSHA STANDARDS

**PATRIOT ENGINEERING
and Environmental, Inc.**
Engineering Value for Project Success
Consulting Environmental, Geotechnical
and Materials Engineers

Excavation for Footings
In an Area of Fill
ILLUSTRATION D

job. no.:

figure:



**PATRIOT ENGINEERING
and Environmental, Inc.**
Engineering Value for Project Success
Consulting Environmental, Geotechnical
and Materials Engineers

Excavation Near Existing
In Use Foundations
ILLUSTRATION E

job. no.:

figure:

APPENDIX A

SITE VICINITY MAP (FIGURE NO. 1)

BORING LOCATION MAP (FIGURE NO. 2)

BORING LOGS

BORING LOG KEY

**UNIFIED SOIL CLASSIFICATION SYSTEM
(USCS)**



Image Source:
USGS Bloomington Topo 2022

Figure 1

Site Vicinity Map



Patriot Engineering &
Environmental, Inc.

Project: Oolitic Drive Residences
922 North Oolitic Drive
Bloomington, Indiana

Project Number: 24-0455-11	Drawn By: J. DuMond
Date: April 23, 2024	Approved: M. Jonard
	DWG: 24-0455-11_geo



LEGEND

- PATRIOT Soil Boring
- B-1 Soil Boring ID

- NOTES:**
1. Boring locations were staked by PATRIOT. All locations are shown as approximate.
 2. All locations were determined in the field with references to existing landmarks.
 3. Image Source: Google Earth
 4. Scale as shown.

Figure 2
Soil Boring Location Map

Project: Oolitic Drive Residences 922 North Oolitic Drive Bloomington, Indiana		Drawn By: J. DuMond
Project Number: 24-0455-11	Approved: M. Jonard	
Date: April 23, 2024	DWG: 24-0455-11_geo	



Patriot Engineering & Environmental, Inc.

LOG OF BORING B-1

(Page 1 of 1)



Oolitic Drive Residences
922 North Oolitic Drive
Bloomington, Indiana

Client Name : RCH LLC
Project Number : 24-0455-11G
Logged By : J. Rogers
Start Date : 04/17/2024
Drilling Method : HSA

Driller : E. Thomas
Sampling : Splitspoon
Approx. Elevation : +/- 881 feet
Latitude : 39°10'32.20"N
Longitude : 86°33'11.58"W

Depth (Feet)	Elevation (Feet)	Water Level	USCS	GRAPHIC	Water Levels					REMARKS	
					▼ During Drilling - Dry	▽ After Completion - Dry	◆ After 24 Hours - N/A	Samples	Rec %		SPT Results
DESCRIPTION											
0	881				TOPSOIL (4") Red, moist to very moist, stiff to hard, SILTY CLAY	1	100	4/4/7	2.3	24	Boring caved to 8.5 feet upon auger removal.
5	875		CL			2	67	4/6/7	1.9	23	
10	870					3	33	6/10/13	2.7	24	
10	870					4	94	6/7/8	4.5	22	
15	865				Gray, highly weathered, LIMESTONE	5	17	50-3"			Auger refusal encountered at 13.5 feet.
15	865				Splitspoon refusal encountered at 13.8 feet.						Groundwater was not encountered during drilling, nor upon completion.
20	860										
25											

05-02-2024 C:\Users\mjonard\Patriot_Engineering\GEO - Documents\Mtech\2024 Mtech\0455-11G\b1.bor



LOG OF BORING B-2

(Page 1 of 1)

Oolitic Drive Residences
922 North Oolitic Drive
Bloomington, Indiana

Client Name : RCH LLC
Project Number : 24-0455-11G
Logged By : J. Rogers
Start Date : 04/17/2024
Drilling Method : HSA

Driller : E. Thomas
Sampling : Splitspoon
Approx. Elevation : +/- 883 feet
Latitude : 39°10'32.44"N
Longitude : 86°33'11.73"W

Depth (Feet)	Elevation (Feet)	Water Level	USCS	GRAPHIC	Water Levels					REMARKS	
					▼ During Drilling - Dry	▽ After Completion - Dry	◆ After 24 Hours - N/A	Samples	Rec %		SPT Results
DESCRIPTION											
0	883				TOPSOIL (8")						
			CL		Brown, very moist, stiff, SILTY CLAY with trace gravel	1	100	4/5/7		26	Boring caved to 5 feet upon auger removal.
5			CL		Red, very moist, stiff to very stiff, SILTY CLAY	2	89	4/7/8	2.5	26	
			CH		Red, very moist, stiff to very stiff, CLAY	3	100	4/6/8	3.0	37	
10					Gray, highly weathered LIMESTONE	4	50	4/18/50-4"		28	
12					Auger refusal encountered at 12 feet						Groundwater was not encountered during drilling, nor upon completion.
15											
20											
25											



LOG OF BORING B-3

(Page 1 of 1)

Oolitic Drive Residences
922 North Oolitic Drive
Bloomington, Indiana

Client Name : RCH LLC
Project Number : 24-0455-11G
Logged By : J. Rogers
Start Date : 04/17/2024
Drilling Method : HSA

Driller : E. Thomas
Sampling : Splitspoon
Approx. Elevation : +/- 878 feet
Latitude : 39°10'31.98"N
Longitude : 86°33'11.69"W

Depth (Feet)	Elevation (Feet)	Water Level	USCS	GRAPHIC	Water Levels					REMARKS	
					▼ During Drilling - Dry	▽ After Completion - Dry	◆ After 24 Hours - N/A	Samples	Rec %		SPT Results
DESCRIPTION											
0	878				TOPSOIL (4")						
			CL		Red, moist, medium stiff, SILTY CLAY	1	17	9/5/3		21	Boring caved to 2 feet upon auger removal.
3.75			CL		Red, moist, medium stiff, SILTY CLAY with some gravel and asphalt (FILL)	2	44	1/3/3		21	
5			CH		Red, very moist, hard, CLAY with trace limestone	3	33	4/50-4"		40	
8.70					Gray, highly weathered, LIMESTONE	4	44	50-4"			
10											
12					Auger refusal encountered at 12 feet.						Groundwater was not encountered during drilling, nor upon completion.
15											
20											
25											



LOG OF BORING B-4

(Page 1 of 1)

Oolitic Drive Residences
922 North Oolitic Drive
Bloomington, Indiana

Client Name : RCH LLC
Project Number : 24-0455-11G
Logged By : J. Rogers
Start Date : 04/17/2024
Drilling Method : HSA

Driller : E. Thomas
Sampling : Splitspoon
Approx. Elevation : +/- 877 feet
Latitude : 39°10'31.60"N
Longitude : 86°33'11.65"W

Depth (Feet)	Elevation (Feet)	Water Level	USCS	GRAPHIC	Water Levels			Samples	Rec %	SPT Results	qp tsf	w %	REMARKS
					▼ During Drilling - Dry	▽ After Completion - Dry	◆ After 24 Hours - N/A						
DESCRIPTION													
0	877				TOPSOIL (3") Brown, slightly moist, stiff, SILTY CLAY with some asphalt (FILL)								
875			CL			1	44	4/4/6			16		
					ASPHALT and GRAVEL (FILL)								
5						2	72	11/13/6			6		
					Red, very moist, stiff to very stiff, CLAY								
870						3	50	4/6/7	3.9		28	Boring caved to 6 feet upon auger removal.	
						4	72	8/11/9	3.6	31			
10													
			CH			5	100	7/13/10		27			
865													
						6	72	7/10/12		26			
15													
860													
20					Boring terminated at 20 feet.							Groundwater was not encountered during drilling, nor upon completion.	
855													
25													



LOG OF BORING B-5

(Page 1 of 1)

Oolitic Drive Residences
922 North Oolitic Drive
Bloomington, Indiana

Client Name : RCH LLC
Project Number : 24-0455-11G
Logged By : J. Rogers
Start Date : 04/17/2024
Drilling Method : HSA

Driller : E. Thomas
Sampling : Splitspoon
Approx. Elevation : +/- 878 feet
Latitude : 39°10'31.17"N
Longitude : 86°33'12.62"W

Depth (Feet)	Elevation (Feet)	Water Level	USCS	GRAPHIC	Water Levels					REMARKS		
					▼ During Drilling - 13.0 feet	▽ After Completion - Dry	◆ After 24 Hours - N/A	Samples	Rec %		SPT Results	qp tsf
DESCRIPTION												
0	878				TOPSOIL (5") Brown, moist to very moist, soft to medium stiff, SILTY CLAY with trace gravel and organics (FILL)							
3.75			CL		1	33	1/1/24		21	Boring caved to 5 feet upon auger removal.		
5					2	56	2/2/2		19			
6.75					3	33	4/4/4		24			
8.75					4	39	3/3/4		21			
13.75		▼	CL		5	100	1/3/3		29			
18.75					6	100	4/6/6		21			
20					Boring terminated at 20 feet.							
25												



LOG OF BORING B-6

(Page 1 of 1)

Oolitic Drive Residences
922 North Oolitic Drive
Bloomington, Indiana

Client Name : RCH LLC
Project Number : 24-0455-11G
Logged By : J. Rogers
Start Date : 04/17/2024
Drilling Method : HSA

Driller : E. Thomas
Sampling : Splitspoon
Approx. Elevation : +/- 878 feet
Latitude : 39°10'31.23"N
Longitude : 86°33'11.77"W

Depth (Feet)	Elevation (Feet)	Water Level	USCS	GRAPHIC	Water Levels					REMARKS	
					▼ During Drilling - Dry	▽ After Completion - Dry	◆ After 24 Hours - N/A	Samples	Rec %		SPT Results
DESCRIPTION											
0	878				TOPSOIL (5")						
			CL		Brown, moist, stiff, SILTY CLAY with trace asphalt (FILL)	1	94	4/5/5		21	Boring caved to 8 feet upon auger removal.
3.75			CL		Brown, moist, medium stiff, SILTY CLAY with trace asphalt (FILL)	2	56	4/5/5			
5			CL		Brown, moist, medium stiff, SILTY CLAY with trace asphalt (FILL)	3	33	4/4/3		19	
8.7			CL		Brown, moist, medium stiff, SILTY CLAY with some gravel and brick (FILL)	4	17	1/3/2			
10			CH		Red, very moist, stiff to hard, CLAY	5	67	9/11/12	3.3	32	
15						6	100	4/9/12	3.0	37	
20					Boring terminated at 20 feet.						Groundwater was not encountered during drilling, nor upon completion.
25	855										

BORING LOG KEY

UNIFIED SOIL CLASSIFICATION SYSTEM (USCS) FIELD CLASSIFICATION SYSTEM FOR SOIL EXPLORATION

NON-COHESIVE SOILS (Silt, Sand, Gravel, and Combinations)

Density	Field Identification (SPT Blows/ft)	Grain Size Terminology		
		<u>Soil Fraction</u>	<u>Particle Size</u>	<u>US Standard Sieve Size</u>
Very Loose	0 - 4	Boulders	> 12 inches	> 12 inches
Loose	5 - 10	Cobbles	3 - 12 inches	3 - 12 inches
Medium Dense	11 - 30	Gravel: Coarse	¾ - 3 inches	¾ - 3 inches
Dense	31 - 50	Small	4.76 mm - ¾ inch	No. 4 - ¾ inches
Very Dense	> 51	Sand: Coarse	2.00 - 4.76 mm	No. 10 - No. 4
		Medium	0.42 - 2.00 mm	No. 40 - No. 10
		Fine	0.074 - 0.42 mm	No. 200 - No. 40
		Silt	0.005 - 0.074 mm	< No. 200
		Clay	< 0.005 mm	< No. 200

RELATIVE PROPORTIONS FOR SOILS

<u>Descriptive Term</u>	<u>Percent</u>
Trace	1 - 10
Little	11 - 20
Some	21 - 35
And	36 - 50

COHESIVE SOILS

(Clay, Silt and Combinations)

<u>Consistency</u>	<u>Unconfined Compressive Strength (tons/ft²)</u>	<u>Field Identification (SPT Blows/ft)</u>
Very Soft	Less than 0.25	0 - 2
Soft	0.25 - < 0.5	3 - 4
Medium Stiff	0.5 - < 1.0	5 - 8
Stiff	1.0 - < 2.0	9 - 15
Very Stiff	2.0 - < 4.0	16 - 30
Hard	Over 4.0	> 30

Classification: Provided on Boring Logs are made by visual inspection.


Standard Penetration Test: Driving a 2 inch outer-diameter (O.D.) by 1½ inch inner-diameter (I.D.) split-spoon sampler a total of 18 inches into undisturbed soil with the number of blows of a 140 pound hammer free-falling a distance of 30 inches recorded for each 6 inches of penetration. The sum of blows for the final 12 inches of penetration is the Standard Penetration Test result commonly referred to as the "N"-value (or blow-count).

Strata Changes: In the column "Descriptions" on the Boring Logs the horizontal lines represent strata changes. A solid line (——) represents an observed change, a dashed line (- - - -) represents an estimated change.

Groundwater: Observations were made at the times indicated on the Boring Logs. Fluctuations in the groundwater level should be expected over time due to variations in rainfall and other environmental or physical factors. *Groundwater symbols:* (▼)-observed groundwater level and/or elevation during drilling; (▽)-observed groundwater level and/or elevation upon completion of boring.

Unified Soil Classification System (USCS)


Major Divisions		Group Symbol	Typical Names	Classification Criteria for Coarse-Grained Soils				
Coarse-grained soils (more than half of material is larger than No. 200)	Gravels (more than half of coarse fraction is larger than No. 4 sieve size)	Clean gravels (little or no fines)	GW	Well-graded gravels, gravel-sand mixtures, little or no fines	$C_u \geq 4$ $1 \leq C_c \leq 3$	$C_u = \frac{D_{60}}{D_{10}}$	$C_c = \frac{D_{20}^2}{D_{10} D_{60}}$	
		Gravels with fines (appreciable amount of fines)	GP	Poorly graded gravels, gravel-sand mixtures, little or no fines	Not meeting all gradation requirements for GW ($C_u < 4$ or $1 > C_c > 3$)			
			GM $\frac{U}{C}$	Silty gravels, gravel-sand-silt mixtures	Atterberg limits below A line or $P_L < 4$		Above A line with $4 < P_L < 7$ are borderline cases requiring use of dual symbols	
			GC	Clayey gravels, gravel-sand-clay mixtures	Atterberg limits above A line or $P_L > 7$			
	Sands (more than half of coarse fraction is smaller than No. 4 sieve size)	Clean sands (little or no fines)	SW	Well-graded sands, gravelly sands, little or no fines	$C_u \geq 6$ $1 \leq C_c \leq 3$	$C_u = \frac{D_{60}}{D_{10}}$	$C_c = \frac{(D_{30})^2}{D_{10} D_{60}}$	
		Sands with fines (appreciable amount of fines)	SP	Poorly graded sands, gravelly sands, little or no fines	Not meeting all gradation requirements for SW ($C_u < 6$ or $1 > C_c > 3$)			
			SM $\frac{U}{C}$	Silty sands, sand-silt mixtures	Atterberg limits below A line or $P_L < 4$		Limits plotting in hatched zone with $4 \leq P_L \leq 7$ are borderline cases requiring use of dual symbols	
			SC	Clayey sands, sand-clay mixtures	Atterberg limits above A line with $P_L > 7$			
			Silt and clays (liquid limit <50)	ML	Inorganic silts and very fine sands, rock flour, silty or clayey fine sands, or clayey silts with slight plasticity	<ol style="list-style-type: none"> Determine percentages of sand and gravel from grain size curve. Depending on percentages of fines (fraction smaller than 200 sieve size), coarse-grained soils are classified as follows: Less than 5% - GW, GP, SW, SP More than 12% - GM, GC, SM, SC 5-12% - Borderline cases requiring dual symbols 		
		CL		Inorganic clays of low to medium plasticity, gravelly clays, sandy clays, silty clays, lean clays				
OL	Organic silts and organic silty clays of low plasticity							
Silt and clays (liquid limit >50)	MH	Inorganic silts, micaceous or diatomaceous fine sandy or silty soils, elastic silts						
	CH	Inorganic clays or high plasticity, fat clays						
	OH	Organic clays of medium to high plasticity, organic silts						
	PT	Peat and other highly organic soils						
Highly organic soils								



APPENDIX B

SEISMIC SITE CLASS EVALUATION

 This is a beta release of the new ATC Hazards by Location website. Please [contact us](#) with feedback.

 The ATC Hazards by Location website will not be updated to support ASCE 7-22. [Find out why.](#)


ATC Hazards by Location

Search Information


Address: 922 N Oolitic Dr, Bloomington, IN 47404, USA
Coordinates: 39.175149, -86.5534332
Elevation: 879 ft
Timestamp: 2024-05-03T13:50:55.486Z
Hazard Type: Seismic
Reference Document: IBC-2012
Risk Category: II
Site Class: C



MCE_R Horizontal Response Spectrum



Design Horizontal Response Spectrum



Basic Parameters

Name	Value	Description
S_S	0.225	MCE _R ground motion (period=0.2s)
S_1	0.107	MCE _R ground motion (period=1.0s)
S_{MS}	0.269	Site-modified spectral acceleration value
S_{M1}	0.181	Site-modified spectral acceleration value
S_{DS}	0.18	Numeric seismic design value at 0.2s SA
S_{D1}	0.121	Numeric seismic design value at 1.0s SA

Additional Information

Name	Value	Description
SDC	B	Seismic design category
F_a	1.2	Site amplification factor at 0.2s
F_v	1.693	Site amplification factor at 1.0s
CR_S	0.9	Coefficient of risk (0.2s)
CR_1	0.854	Coefficient of risk (1.0s)
PGA	0.107	MCE _G peak ground acceleration
F_{PGA}	1.2	Site amplification factor at PGA
PGA_M	0.128	Site modified peak ground acceleration
T_L	12	Long-period transition period (s)
$SsRT$	0.225	Probabilistic risk-targeted ground motion (0.2s)
$SsUH$	0.25	Factored uniform-hazard spectral acceleration (2% probability of exceedance in 50 years)
SsD	1.5	Factored deterministic acceleration value (0.2s)
$S1RT$	0.107	Probabilistic risk-targeted ground motion (1.0s)
$S1UH$	0.125	Factored uniform-hazard spectral acceleration (2% probability of exceedance in 50 years)
$S1D$	0.6	Factored deterministic acceleration value (1.0s)

PGAd	0.6	Factored deterministic acceleration value (PGA)
------	-----	---

The results indicated here DO NOT reflect any state or local amendments to the values or any delineation lines made during the building code adoption process. Users should confirm any output obtained from this tool with the local Authority Having Jurisdiction before proceeding with design.

Please note that the ATC Hazards by Location website will not be updated to support ASCE 7-22. [Find out why.](#)

Disclaimer

Hazard loads are provided by the U.S. Geological Survey [Seismic Design Web Services](#).

While the information presented on this website is believed to be correct, ATC and its sponsors and contributors assume no responsibility or liability for its accuracy. The material presented in the report should not be used or relied upon for any specific application without competent examination and verification of its accuracy, suitability and applicability by engineers or other licensed professionals. ATC does not intend that the use of this information replace the sound judgment of such competent professionals, having experience and knowledge in the field of practice, nor to substitute for the standard of care required of such professionals in interpreting and applying the results of the report provided by this website. Users of the information from this website assume all liability arising from such use. Use of the output of this website does not imply approval by the governing building code bodies responsible for building code approval and interpretation for the building site described by latitude/longitude location in the report.

APPENDIX C

GENERAL QUALIFICATIONS

**STANDARD CLAUSE FOR UNANTICIPATED
SUBSURFACE CONDITIONS**

GENERAL QUALIFICATIONS
of Patriot Engineering's Geotechnical Engineering Investigation

This report has been prepared at the request of our client for his use on this project. Our professional services have been performed, findings obtained, and recommendations prepared in accordance with generally accepted geotechnical engineering principles and practices. This warranty is in lieu of all other warranties either expressed or implied.

The scope of our services did not include any environmental assessment or investigation for the presence or absence of wetlands, hazardous or toxic materials in the soil, groundwater, or surface water within or beyond the site studied. Any statements in this report or on the test borings logs regarding vegetation types, odors or staining of soils, or other unusual conditions observed are strictly for the information of our client and the owner.

This report may not contain sufficient information for purposes of other parties or other uses. This company is not responsible for the independent conclusions, opinions or recommendations made by others based on the field and laboratory data presented in this report. Should there be any significant differences in structural arrangement, loading or location of the structure, our analysis should be reviewed.

The recommendations provided herein were developed from the information obtained in the test borings, which depict subsurface conditions only at specific locations. The analysis, conclusions, and recommendations contained in our report are based on site conditions as they existed at the time of our exploration. Subsurface conditions at other locations may differ from those occurring at the specific drill sites. The nature and extent of variations between borings may not become evident until the time of construction. If, after performing on-site observations during construction and noting the characteristics of any variation, substantially different subsurface conditions from those encountered during our explorations are observed or appear to be present beneath excavations, we must be advised promptly so that we can review these conditions and reconsider our recommendations where necessary.

If there is a substantial lapse of time between the submission of our report and the start of work at the site, or if conditions have changed due to natural causes or construction operations at or adjacent to the site, we urge that our report be reviewed to determine the applicability of the conclusions and recommendations considering the changed conditions and time lapse.

We urge that Patriot be retained to review those portions of the plans and specifications that pertain to earthwork and foundations to determine whether they are consistent with our recommendations. In addition, we are available to observe construction, particularly the compaction of structural backfill and preparation of the foundations, and such other field observations as may be necessary.

In order to fairly consider changed or unexpected conditions that might arise during construction, we recommend the following verbiage (Standard Clause for Unanticipated Subsurface Conditions) be included in the project contract.

STANDARD CLAUSE FOR UNANTICIPATED SUBSURFACE CONDITIONS

"The owner has had a subsurface exploration performed by a soils consultant, the results of which are contained in the consultant's report. The consultant's report presents his conclusions on the subsurface conditions based on his interpretation of the data obtained in the exploration. The contractor acknowledges that he has reviewed the consultant's report and any addenda thereto, and that his bid for earthwork operations is based on the subsurface conditions as described in that report. It is recognized that a subsurface exploration may not disclose all conditions as they actually exist and further, conditions may change, particularly groundwater conditions, between the time of a subsurface exploration and the time of earthwork operations. In recognition of these facts, this clause is entered in the contract to provide a means of equitable additional compensation for the contractor if adverse unanticipated conditions are encountered and to provide a means of rebate to the owner if the conditions are more favorable than anticipated.

At any time during construction operations that the contractor encounters conditions that are different than those anticipated by the soils consultant's report, he shall immediately (within 24 hours) bring this fact to the owner's attention. If the owner's representative on the construction site observes subsurface conditions which are different than those anticipated by the consultant's report, he shall immediately (within 24 hours) bring this fact to the contractor's attention. Once a fact of unanticipated conditions has been brought to the attention of either the owner or the contractor, and the consultant has concurred, immediate negotiations will be undertaken between the owner and the contractor to arrive at a change in contract price for additional work or reduction in work because of the unanticipated conditions. The contract agrees that the following unit prices would apply for additional or reduced work under the contract. For changed conditions for which unit prices are not provided, the additional work shall be paid for on a time and materials basis."

Another example of a changed conditions clause can be found in paper No. 4035 by Robert F. Borg, published in ASCE Construction Division Journal, No. CO2, September 1964, page 37.

**BLOOMINGTON BOARD OF ZONING APPEALS
STAFF REPORT****CASE #: V-14-24/VAR-2024-04-0031
DATE: May 23, 2024****Location: 922 N Oolitic Dr (parcel # 53-05-32-201-077.059-005) (Lot 59 of Forest Homes)**

PETITIONER: Ruby Creek Homes
11990 E 1400 N, Oden, IN 47562**CONSULTANTS:** Melvin Graber
11990 E 1400 N, Oden, IN 47562

REQUEST: Variance from Karst Preservation standards to allow disturbance within 25' of the last closed contour of a karst feature for a property in the Residential Medium Lot (R2) zoning district.

REPORT: This 0.19-acre property is located at 922 N Oolitic Dr. The property is zoned Residential Medium Lot (R2). Surrounding zones are all Residential Medium Lot (R2) and surrounding land uses are all Dwelling, Single Family (detached).

Previous to the current owner, this lot of record, along with the Forest Homes Lots 57 and 58 (914 and 918 N Oolitic), were owned by the same owner and two mobile homes sat on all three lots for many years.

There is a karst feature, a sinkhole, located on this property. Existing elevations on this site range from 876 feet to 882 feet. There is currently no stormwater infrastructure at or near this site.

Chapter 4 of the Unified Development Ordinance (UDO), Title 20 of the Bloomington Municipal Code) states that no land-disturbing activity, mowing, or temporary or permanent structure shall be allowed within the sinkhole nor within 25 feet of the last closed contour of the sinkhole. Title 20 of the UDO defines the sinkhole as the last closed contour line of the feature on the City's geographic information system. Historic contour mapping shows that this entire property located at 922 N Oolitic falls within the last closed contours and 25 foot buffer of the karst feature, which is at an elevation of 882 feet, which means that according to the UDO, the entire lot cannot be disturbed. Since this entire site lies within the area shown to be within the last closed contour of the karst feature, a variance must be granted to allow any disturbance on this property.

The petitioner is requesting a variance from the karst preservation standards to allow disturbance within 25' of the last closed contour of the karst feature.

As part of this variance request, a report of geotechnical engineering exploration was submitted. The report confirmed that a sinkhole is present on the site and it provided information about soil composition in two locations on this property through analysis of soil borings. The report also provided sinkhole remediation methods of treatment and construction recommendations for placing a single family structure on the site.

CRITERIA AND FINDINGS FOR DEVELOPMENT STANDARDS VARIANCE**20.06.080(b)(3)(E) Standards for Granting Variances from Development Standards:**

A variance from the development standards of the Unified Development Ordinance may be approved only upon determination in writing that each of the following criteria is met:

- 1) *The approval will not be injurious to the public health, safety, morals, and general welfare of the community.*

PROPOSED FINDING: The granting of the variance will not be injurious to the public health, safety, morals, or general welfare of the community. A number of structures have existed in and around this karst feature for many years with no collapse. Proper testing of and restoration of the site will be required before building construction is allowed in order to maximize water infiltration on the site and ensure that water is not diverted off site, and to make sure that the site is safe for construction.

- 2) *The use and value of the area adjacent to the property included in the Development Standards Variance will not be affected in a substantially adverse manner.*


PROPOSED FINDING: No adverse impacts to the use and value of surrounding properties as a result of the requested variance are found. At least half of this property is located four to eight feet in elevation higher than the apparent lowest point of the sinkhole. Current site elevation conditions show that the portions of the karst feature that are most sensitive are found on the adjacent property to the south of this property. With the remediation of the sinkhole, drainage analysis and the installation of drainage solutions, impact to surrounding properties should be mitigated.

- 3) *The strict application of the terms of the Unified Development Ordinance will result in practical difficulties in the use of the property; that the practical difficulties are peculiar to the property in question; that the Development Standards Variance will relieve the practical difficulties.*

PROPOSED FINDING: The strict application of the terms of the Unified Development Ordinance will result in practical difficulties in the use of the property because it renders the entire site unbuildable. There has been development within the last closed contours of this feature for a number of years without any indications of negative impact. The practical difficulties are peculiar to the property in question because it is uncommon for an entire property to be located within a UDO-defined sinkhole, but because the properties in this area are smaller and closer together, the extent of the last closed contour of the sinkhole renders the entire site unbuildable.


RECOMMENDATION: The Department recommends that the Board of Zoning Appeals adopt the proposed findings and approve **V-14-24/ VAR-2024-04-0031, with the following conditions:**


1. Because the area around the last closed contour of the sinkhole has created obvious steep slopes on the site, construction of the home should occur south of the 878 contour line.
2. Implementation of sinkhole remediation as outlined in the attached geotechnical report, is required – at all three properties (914, 918 and 922 N Oolitic) - before a Certificate of Zoning Compliance will be issued.
3. Submission of a drainage and water flow analysis post-sinkhole remediation is required before a Certificate of Zoning Compliance will be issued. The report must be approved by City of Bloomington Planning & Transportation and Utility Departments.
4. Implementation of design and construction recommendations provided in the attached geotechnical report is required before a Certificate of Zoning Compliance will be issued.
5. Testing of soil and water contamination testing and provision of any necessary remediation identified related to those tests is required before a Certificate of Zoning Compliance will be issued.
6. A Zoning Commitment shall be recorded indicating the presence of the karst feature and describing the Karst Conservancy Easement before a Certificate of Zoning Compliance will be issued.



Map Legend


- Addresses
- ⊙ Sinkholes
- ▭ Bloomington Municipal Boundary
- ▭ Parcels
- Contours 2021






Map Legend

- Addresses
- Parcels
- Sinkholes
- Contours 2021
- Bloomington Municipal Boundary
- Planned Unit Development
- Residential Medium Lot
- Mixed-Use Employment





To Whom it may concern,

Ruby Creek Homes LLC (RCH) is requesting a variance from code UDO 20.04.030 (g) Pursuant to Indiana Code 36-7-4-918.5.

Project Location

914, 918, 922 N Oolitic Dr.

(See Attached Survey)

Scope of Project

In 2023, 2 deteriorated homes were removed from said properties (Demo Permit #s R-23-610, R-23-612) for the:

Purpose of

New Home Construction

See Attached Site Plan

Difficulties

The strict application of UDO 20.04.030 (g) renders the entire properties undevelopable, for which use it was previously intended.

See Attached - Forrest Homes Development Recording 1927

Granting the requested variance would:

Improve neighboring Property values

And would be an asset rather than a liability to public health safety and general welfare of the community by providing much needed and deficient "Affordable Housing".

Site Plans for New Home Const.

922, 918 Oolitic Drive, Lots 58, 59

NOTE FROM STAFF: plans will likely have to change per conditions of variance -KAG

Oolitic Dr.




918

922

Lot 58

Lot 59



Scale 1"=20'

Alley

NOTE FROM STAFF: plans will likely have to change per conditions of variance -KAG



Camera 3

OFFICE: 812-466-4328
CELL: 812-466-4328
EMAIL: khwagner@skc.com
ADDRESS: 8227 N 725 E
COUNCIL: 15-47502

DRAWINGS PROVIDED BY:
Ken Wagner
8227 N 725 E
COUNCIL 15-47502
khwagner@skc.com

DATE:
1/20/2023

SCALE:

SHEET:

P-1

Project Overview

Maple - C

New Plans For.....

DRAWINGS PROVIDED BY:
Ken Weiler
8227 N 725 E
Orem, UT 84052
812-466-6328
khvagler88@icloud.com


DATE:

120100/23

SCALE:

SHEET:

OWNER: [REDACTED]
CONTRACT NO.: [REDACTED]
DATE: [REDACTED]
PROJECT: [REDACTED]
DRAWING NO.: [REDACTED]
SHEET NO.: [REDACTED]



LIVING AREA
1521 SQ FT

1st Floor

FRAMING NOTES

- ALL EXTERIOR WALLS ARE SHOWN AS 4" WALLS UNLESS NOTED OTHERWISE
- ALL INTERIOR WALLS ARE SHOWN AS 5 1/2" WALLS UNLESS NOTED OTHERWISE
- 4" 1/2" WALLS UNLESS NOTED OTHERWISE
- ALL EXTERIOR WINDOWS TO BE [REDACTED]
- ALL EXTERIOR DOORS TO BE [REDACTED]
- ALL WINDOWS TO BE [REDACTED]
- ALL DOORS TO BE [REDACTED]
- ALL WINDOW HEADS AT 8" UNLESS NOTED OTHERWISE


DRAWINGS PROVIDED BY:
Ken Wailer
8227 N 725 E
Orem UT 84052
812-466-6328
khwailer88@icloud.com

DATE:


12/01/23

SCALE:


SHEET:




Elevation 1



Elevation 2



Elevation 4



Elevation 3

THESE PLANS ARE PROVIDED AS A SERVICE TO OUR CLIENTS AND ARE NOT TO BE USED FOR ANY OTHER PROJECT WITHOUT THE WRITTEN CONSENT OF THE ARCHITECT. THE ARCHITECT IS NOT RESPONSIBLE FOR ANY ERRORS OR OMISSIONS IN THESE PLANS. THE CLIENT IS RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND FOR VERIFYING THE ACCURACY OF ALL INFORMATION PROVIDED TO THE ARCHITECT. THE ARCHITECT'S LIABILITY IS LIMITED TO THE DESIGN OF THE PLANS AND DOES NOT EXTEND TO THE CONSTRUCTION OF THE PROJECT. THE ARCHITECT IS NOT TO BE HELD RESPONSIBLE FOR ANY DELAYS OR COST OVERRUNS CAUSED BY THE CLIENT OR OTHER THIRD PARTIES.


DRAWINGS PROVIDED BY:
Ken Waibel
8227 N 725 E
Orem UT 84052
812-466-6328
khwaibel88@slc.email

DATE:
12/01/23


SCALE:

SHEET:

ALL DIMENSIONS UNLESS OTHERWISE SPECIFIED
CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE
LATEST EDITIONS OF THE INTERNATIONAL RESIDENTIAL
CODE BOOKS AND ALL APPLICABLE LOCAL ORDINANCES
AND CODES. ALL DIMENSIONS SHALL BE TO FACE UNLESS
OTHERWISE SPECIFIED. ALL DIMENSIONS SHALL BE TO
CENTERLINE UNLESS OTHERWISE SPECIFIED. ALL DIMENSIONS
SHALL BE TO FACE UNLESS OTHERWISE SPECIFIED.



Foundation



Attic











REPORT OF GEOTECHNICAL ENGINEERING EXPLORATION

**OOLITIC DRIVE RESIDENCES
BLOOMINGTON, INDIANA**

PREPARED FOR:

**RCH, LLC
1190 EAST 1400 NORTH
ODON, INDIANA 47562**

**Patriot Engineering and Environmental, Inc.
2006 South Yost Avenue
Bloomington, Indiana 47403**

May 6, 2024



May 6, 2024

Mr. Melvin Graber
RCH, LLC
11990 East 1400 North
Odon, Indiana 47562

Re: **Report of Geotechnical Engineering Exploration
Oolitic Drive Residences
922 North Oolitic Drive
Bloomington, Indiana
Patriot Project No.: 24-0455-11G**

Dear Melvin:

Attached is the report of our geotechnical engineering exploration for the above referenced project. This exploration was completed in general accordance with our Proposal No. P24-0688-11G dated March 25, 2024.



This report includes detailed and graphic logs of six (6) soil borings drilled at the proposed project site. Also included in the report are the results of laboratory tests performed on samples obtained from the site, and geotechnical recommendations pertinent to the site development, foundation design, and construction.

We appreciate the opportunity to perform this geotechnical engineering exploration and are looking forward to working with you during the construction phase of the project. If you have any questions regarding this report or if we may be of any additional assistance regarding any geotechnical aspect of the project, please do not hesitate to contact our office.

Respectfully submitted,
Patriot Engineering and Environmental, Inc.



Mark Jonard, E.I.
Geotechnical Engineer



William D. Dubois, P.E.
Senior Principal Engineer

TABLE OF CONTENTS

1.0 INTRODUCTION	1
1.1 General	1
1.2 Purpose and Scope	1
2.0 PROJECT INFORMATION	1
3.0 SITE AND SUBSURFACE CONDITIONS	2
3.1 Site Conditions	2
3.2 General Subsurface Conditions	2
3.3 Groundwater Conditions	3
4.0 DESIGN RECOMMENDATIONS	4
4.1 Basis	4
4.2 Overall Site Evaluation.....	4
4.3 Foundations	5
4.4 Floor Slabs	7
4.5 Seismic Considerations	7
5.0 CONSTRUCTION CONSIDERATIONS	8
5.1 Site Preparation.....	8
5.2 Sinkhole Remediation.....	9
5.3 Foundation Excavations	10
5.4 Structural Fill and Fill Placement Control.....	11
5.5 Groundwater Considerations	12
6.0 EXPLORATIONAL PROCEDURES	13
6.1 Field Work	13
6.2 Laboratory Testing.....	13
7.0 ILLUSTRATIONS	14

APPENDICES

Appendix A:	Site Vicinity Map (Figure No. 1)
	Boring Location Map (Figure No. 2)
	Boring Logs
	Boring Log Key
	Unified Soil Classification System (USCS)
Appendix B:	Seismic Site Class Evaluation
Appendix C:	General Qualifications
	Standard Clause for Unanticipated Subsurface Conditions

REPORT OF GEOTECHNICAL ENGINEERING EXPLORATION

**Oolitic Drive Residences
922 Oolitic Drive
Bloomington, Indiana
Patriot Project No.: 24-0455-11G**

1.0 INTRODUCTION

1.1 General

RCH, LLC is planning the construction of a three (3) small single-family homes to be located at the three (3) lots at 922 North Oolitic Drive in Bloomington, Indiana. The results of our geotechnical engineering exploration for the project are presented in this report.

1.2 Purpose and Scope

The purpose of this exploration is to determine the general near surface and subsurface conditions within the project area and to develop the geotechnical engineering recommendations necessary for the design and construction of the proposed structures. This was achieved by drilling soil borings, and by conducting laboratory tests on samples taken from the borings. This report contains the results of our findings, an engineering interpretation of these results with respect to the available project information, and recommendations to aid in the design and construction of the proposed facility.

2.0 PROJECT INFORMATION

The proposed project is located along Oolitic Drive in Bloomington, Indiana. The project consists of three (3) single-family homes being built. These homes will be one (1)-story structures of slab-on-grade construction, approximately 32 feet by 48 feet of in plan dimension.

No structural loading information is available to us at the time of this report, but based on similar projects in the area, we can estimate that the proposed structures will have wall loads not exceeding 1,500 pounds per lineal feet (plf), isolated column loads not exceeding 60 kips, and that floor loads will not exceed 150 pounds per square foot (psf). Additionally, based on visual observations of the existing site, it is assumed that any grade raise fill to complete the construction of building pads, finished pavement subgrades, etc., will not exceed 2 feet above the existing ground surface.

3.0 SITE AND SUBSURFACE CONDITIONS

3.1 Site Conditions

The project site is presently an approximately 0.6 acres used for residential purposes. There were previously two (2) modular homes that were removed prior to our mobilization. The surrounding area is generally an area of residential development. The topography in the area proposed for construction is sloped down towards the center of the site, where a recorded sinkhole, per the Indiana Sinkhole Inventory provided by the Indiana Geological Survey, is present. Although the proposed buildings are not planned to be placed above the sinkhole, remediation is required for the project.

3.2 General Subsurface Conditions

Our interpretation of the subsurface conditions is based upon six (6) soil borings drilled at the approximate locations shown on the Boring Location Map (Figure No. 2) in Appendix "A". All depths discussed below refer to depths below the existing ground surface. Based on the results of the soil borings completed at the site, the following subsurface profile is presented. A description of each general soil unit has been identified and is described below:

Topsoil – Topsoil, a surficial layer of material that is a blend of silts, sands, and clays, with varying amounts of organic matter, was encountered at the ground surface at all of the six (6) boring locations. The topsoil layer was about 3 to 8 inches thick in the borings.

Silty Clay (CL) - The surficial layer is generally underlain by brown, slightly moist to very moist, soft to very stiff, silty clay. The silty clay layers extended to depths of 6 to 13.5 feet below the existing ground surface. The natural moisture content of this material ranges from 16 to 29 percent (%). The silty clay layers have unconfined compressive strengths, as determined by a hand penetrometer, of 1.9 to 4.5 tons per square foot (tsf). Standard Penetration Test N-values in this material varied from 4 to 23 blows per foot (bpf). Additionally, fill material, such as asphalt, gravel, brick and organics, was observed in multiple borings to varying depths (see the Table 1 below).

Clay (CH) - The silty clay layer is underlain by red, moist to very moist, medium stiff to hard, *High plasticity* clay. The clay layers extended to depths of 10 to 20 feet below the existing ground surface. The natural moisture content of this material ranges from 26 to 40 %. The silty clay layers have unconfined compressive strengths of 3.0 to 3.9 tsf. Standard Penetration Test N-values in this material varied from 13 to greater than 50 bpf.

Limestone – Below the clay layers at auger refusal, highly weather limestone was present.

The soil conditions described above are general, and some variations in the descriptions should be expected; for more specific information, please refer to the boring logs presented in Appendix “A”. It should be noted that the dashed stratification lines shown on the soil boring logs indicate approximate transitions between soil types. In-situ stratification changes could occur gradually or at different depths.

As previously mentioned, soft clays and unsuitable fill material were encountered in four (4) of the six (6) borings, at depths up to 13.5 feet below the existing ground surface. The following table presents the extent of the unsuitable soils encountered in the borings:

Table No. 1: Summary of Unsuitable Soils Encountered in Borings

Boring Number	Soil Classification	Approximate Depth of Unsuitable Soils (feet) ⁽¹⁾
B-3	Silty Clay (CL) with some asphalt and gravel (FILL)	3.5 to 6
B-4	Silty Clay (CL) with some asphalt (FILL)	0 to 3.5
	Asphalt and Gravel (FILL)	3.5 to 6
B-5	Soft Silty Clay (CL) with a trace of gravel and organics (FILL)	0 to 6
B-6	Silty Clay (CL) with a trace of asphalt (FILL)	0 to 6
	Silty Clay (CL) with some gravel and brick (FILL)	6 to 13.5

⁽¹⁾ Represents depth below existing ground surface.

3.3 Groundwater Conditions

The term groundwater pertains to any water that percolates through the soil found on site. This includes any overland flow that permeates through a given depth of soil, perched water, and water that occurs below the “water table”, a zone that remains saturated and water-bearing year round.

Groundwater was observed during drilling in one (1) of the soil borings (B-5) performed at the site at depths of 13 feet below the existing ground surface. Groundwater was not observed in the remaining borings during drilling. Immediately after the borings were completed and the augers were removed from the boreholes, groundwater was not observed.

It should be recognized that fluctuations in the groundwater level should be expected over time due to variations in rainfall and other environmental or physical factors. ***The true static groundwater level can only be determined through observations made in cased holes over a long period of time, the installation of which was beyond the scope of this exploration.***

4.0 DESIGN RECOMMENDATIONS

4.1 Basis

Our recommendations are based on data presented in this report, which include soil borings, laboratory testing, and our experience with similar projects. Subsurface variations that may not be indicated by a dispersive exploratory boring program can exist on any site. If such variations or unexpected conditions are encountered during construction, or if the project information is incorrect or changed, we should be informed immediately since the validity of our recommendations may be affected.

4.2 Overall Site Evaluation

The borings indicate that the site is mostly underlain by clayey (CL) soils with fill materials observed in multiple borings. In general, the areas near soil borings performed may be suitable for the anticipated development following removal of the fill material. The soils will then be suitable for shallow foundations, and for support of floor slabs and pavements with these undercuts and soil replacement with compacted structural fill of the near surface soils. Additional Concerns for construction are listed below.

Expansive (Highly Plastic) Clays

Four (4) of the six (6) borings encountered highly plastic (expansive) clays (CH) at depths typically between about 6 and 20 feet below the existing ground surface. Expansive soils undergo volume changes upon wetting and drying. Expansive soils tend to shrink on drying and expand when the degree of saturation increases. However, the primary factors

that govern the amount of expansion of the soils are the availability of moisture and the amount and type of clay particles in the soil.

In Indiana, typically expansive soils within the upper 5 to 10 feet of the surface grade are influenced most by climatic environmental factors, which affect the water content of the soils and hence cause the soils to shrink and swell. This range of influence is generally referred to as the active zone. Foundations, floor slabs, pavements and subsurface utilities placed on or in this active zone of highly plastic (expansive) clays can be subjected to detrimental effects of shrink and swell; which can cause unsuitable total and/or differential settlements, along with cracking. Therefore, we recommend that foundations, floor slabs, pavements, other infrastructure not bear or be placed directly on highly plastic clays (CH). Positive drainage of surface water both during construction and after construction is complete will be especially important to reduce the amount of surface water that is allowed to permeate into the subgrade soils and subsequently reduce the potential for unsuitable shrinking or swelling of the underlying highly plastic clays. Water and drainage lines should be located such that if any leakage occurs, water will not be readily accessible to foundations, floor slabs and/or pavement sections. Additionally, the installation and use of an irrigation system at the parcel is highly discouraged.

Karst

The project site is located within a region known for karstic features. Karstic areas are typically associated with the development of solution features within the soluble carbonate bedrock leading to formation of sinkholes. A sinkhole is described as “Closed depression in soil or bedrock formed by the erosion and transport of earth material from below the land surface.” Sinkholes may develop within karstic areas as a result of soil fines migrating from the overburden soil by infiltrating water flowing downward into the bedrock through solution features/channels, such as voids and clay seams within the rock. Sinkholes may consist of a relatively localized weathered feature or larger features resulting from a collapse within a void formed in the overburden soils as a result of loss of the fine soils into the bedrock features. A sinkhole was observed on-site, as well as confirmed by the Indiana Sinkhole Inventory provided by the Indiana Geological Survey. Recommendations for remediation can be found in Section 5.2. If further evaluation of karst is desired, *Patriot* can provide geophysical testing services.

4.3 Foundations

As previously mentioned, unsuitable fill material was encountered in four (4) of the six (6) to depths up to 13.5 feet below existing grade and it is highly likely that potential existing fill

materials could be present within the project area due to previous construction activities. ***If soft clays, existing fill materials, or other unsuitable materials are encountered at the footing level or below, they must be undercut 3 feet below the bottom of the foundation and replaced with well-compacted structural fill prior to construction of foundations or the footings can be extended to suitable natural soils.*** Following the excavation of the footing areas, the foundations subgrade should be visually inspected by a *Patriot* representative and probed at multiple locations at isolated footings and at every 10 feet (maximum) along wall footings using a Dynamic Cone Penetrometer (DCP) to a minimum depth of 5 feet below the footing subgrade to verify that the underlying soil has a SPT blow count of 7 or more or unconfined compressive strength of 1.0 tsf or more. Any unsuitable soils encountered at the footing subgrade or below should be removed and replaced with well-compacted structural fill.

Provided the above recommendations are followed, the proposed structure can be supported on spread footings bearing on the medium stiff to very stiff silty clay encountered at shallow depths or on new well-compacted structural fill overlying the same. These footings should be proportioned using a net allowable soil bearing pressure not exceeding 2,000 pounds per square foot (psf) for column footings or 1,500 psf for wall (strip) footings. For proper performance at the recommended design bearing pressure, foundations must be constructed in compliance with the recommendations for footing excavation inspection that are discussed in Section 5.0 “*Construction Considerations*”.

In using the above net allowable soil bearing pressures, the weight of the foundation and backfill over the foundation need not be considered. Hence, only loads applied at or above the minimum finished grade adjacent to the footing need to be used for dimensioning the foundations. Each new foundation should be positioned so it does not induce significant pressure on adjacent foundations; otherwise the stress overlap must be considered in the design.

All exterior foundations and foundations in unheated areas should be located at a depth of at least 24 inches below final exterior grade for frost protection. We recommend that wall (strip) footings be at least 18 inches wide and column footings be at least 24 inches wide for bearing capacity considerations.

We estimate that the total foundation settlement should not exceed approximately 1 inch and that differential settlement should not exceed about $\frac{3}{4}$ inch. Careful field control during construction is necessary to minimize the actual settlement that will occur.

Positive drainage of surface water, including downspout discharge, should be maintained away from structure foundations to avoid wetting and weakening of the foundation soils both during construction and after construction is complete.

4.4 Floor Slabs

The near surface or shallow subgrade soils encountered within the proposed building footprint generally consist of medium stiff to stiff silty clay and fill material. While the silty clay material is suitable for floor slab support, the fill material is not. ***If soft clays, existing fill materials, or other unsuitable materials are encountered at the floor slab subgrade, they must be undercut and replaced with well-compacted structural fill prior to construction of floor slabs.***

We recommend that all floor slabs be designed as "floating", that is, fully ground supported and not structurally connected to walls or foundations. This is to minimize the possibility of cracking and displacement of the floor slabs because of differential movements between the slab and the foundation. Although the movements are estimated to be within the tolerable limits for the structural safety, such movements could be detrimental to the slabs if they were rigidly connected to the foundations. Additionally, we recommend that all slabs should be liberally jointed and designed with the appropriate reinforcement for the anticipated loading conditions.

The building floor slabs should be supported on a minimum 6 inch thick well-compacted granular base course (i.e. Indiana Department of Transportation (INDOT) No. 53 crushed stone) bearing on a suitably prepared subgrade (Refer to Section 5.0 "*Construction Considerations*"). The granular base course is expected to help distribute loads and equalize moisture conditions beneath the slab.

Provided that the recommendations above for floor slab design and construction are followed, a modulus of subgrade reaction, "K₃₀" value of 75 pounds per cubic inch (pci), is recommended for the design of ground supported floor slabs. It should be noted that the "K₃₀" modulus is based on a 30 inch diameter plate load empirical relationship.

4.5 Seismic Considerations

For structural design purposes, we recommend using a ***Site Classification of "C"*** as defined by the Indiana Building Code (modified 2012 International Building Code (IBC)). Furthermore, along with using a Site Classification of "C", we recommend the use of the

maximum considered spectral response acceleration and design spectral response acceleration coefficients provided in Table No. 2 below. Refer to Appendix “B” for “*Seismic Site Class Evaluation*” report summary.

Table No. 2: Seismic Design Spectral Response Acceleration Coefficients

Period (seconds)	Maximum Considered Spectral Response Acceleration Coefficient	Soil Factor	Design Spectral Response Acceleration Coefficient
0.2	$S_S = 0.225 \text{ g}$	1.20	$S_{DS} = 0.180 \text{ g}$
1.0	$S_1 = 0.107 \text{ g}$	1.69	$S_{D1} = 0.121 \text{ g}$

These values were obtained from the “*Earthquake Ground Motion Parameters*” program for seismic design, developed by the United States Geological Survey (USGS) Earthquake Hazard Program, utilizing latitude 39.175149° north and longitude 86.5534332° west as the designation for identifying the location of the parcel. Other earthquake resistant design parameters should be applied consistent with the minimum requirements of the Indiana Building Code.

5.0 CONSTRUCTION CONSIDERATIONS

5.1 Site Preparation

All areas that will support foundations, floors, pavements or newly placed structural fill must be properly prepared. All loose surficial soil or “topsoil” and other unsuitable materials must be removed. Unsuitable materials include: frozen soil, relatively soft material, relatively wet soils, deleterious material, or soils that exhibit a high organic content.

Approximately 3 to 8 inches of loose surficial topsoil was encountered in the borings. The topsoil was measured at discrete locations as shown on the Boring Location Map (Figure No. 2) in Appendix “A”. The topsoil thickness measured at the boring locations may or may not be representative of the overall average topsoil thickness at the site. Therefore, it is possible that the actual stripping depth could significantly vary from this data. The data presented should be viewed only as a guide to the minimum stripping depth that will be

required to remove organic material at the surface. Additional field exploration by *Patriot* would be required to provide an accurate estimate of the stripping depth. This limited data indicates that a minimum stripping depth will be required to remove the organic material at the surface, followed by the potential for additional stripping and/or scarification and recompaction as may be required to achieve suitable subgrade support. ***Additionally, if saturated conditions exist with the surface soils, light tracked equipment could be required to avoid pushing organics deeper into the suitable subgrade soils.*** A *Patriot* representative should verify the stripping depth at the time grading operations occur.

Prior to construction of floor slabs, pavements or the placement of new structural fill, the exposed subgrade must be evaluated by a Patriot representative; which will include proofrolling of the subgrade. Proofrolling should consist of repeated passes of a loaded, pneumatic-tired vehicle such as a tandem-axle dump-truck or scraper. The proofrolling operations should be observed by a *Patriot* representative, and the proofrolling vehicle should be loaded as directed by *Patriot*. Any area found to rut, pump, or deflect excessively should be compacted in-place or, if necessary, undercut and replaced with structural fill, compacted as specified in Section 5.3 “*Structural Fill and Fill Placement Control*”.

Care must be exercised during grading and fill placement operations. ***The combination of heavy construction equipment traffic and excess surface moisture can cause pumping and deterioration of the near surface soils. The severity of this potential problem depends to a great extent on the weather conditions prevailing during construction.*** The contractor must exercise discretion when selecting equipment sizes and also make a concerted effort to control construction traffic and surface water while the subgrade soils are exposed. We recommend that heavy construction equipment (i.e. dump trucks, scrapers, etc.) be rerouted away from the building and pavement areas. If such problems do arise, the operations in the affected area should be halted and the *Patriot* representative contacted to evaluate the condition.

5.2 Sinkhole Remediation

The actual method used for the treatment of sinkholes is typically dependent on the depth to bedrock and the intended purpose of the area subjected to remediation. Several acceptable methods of treatment are discussed below.

If the depth to the top of bedrock is greater than 15 feet the following should be performed:

- Remove all debris from the hole

- Line hole with geotextile fabric (Mirafi 160N or equivalent), the geotextile fabric should be placed so that there is enough excess fabric to completely wrap the stone
- Backfill with No. 2 Crushed Limestone
- Wrap stone in geotextile fabric
- Place min 2 feet thick compacted clay soil cap, clay soil should be compacted to 100% of Standard Proctor maximum dry density

Please refer to Illustration A at the end of this report.

If the depth to the top of bedrock is less than 15 feet the following should be performed:

- Remove all debris from the hole
- Excavate to the top of the bedrock
- Line hole with geotextile fabric (Mirafi 160N or equivalent), the geotextile fabric should be placed so that there is enough excess fabric to completely wrap the stone
- Backfill with No. 2 Crushed Limestone
- Wrap stone in geotextile fabric
- Place 1 foot of compacted crushed limestone (DGA), compacted to 100% of standard proctor maximum dry density
- Place min 2 feet thick compacted clay soil cap, clay soil should be compacted to 100% of Standard Proctor maximum dry density
- Or instead of crushed limestone and soil cap, place 1-foot reinforced concrete cap

Please refer to Illustrations B and C at the end of this report.

5.3 Foundation Excavations

Upon completion of the foundation excavations and prior to the placement of reinforcing steel, a *Patriot* representative should check the exposed subgrade to confirm that a bearing surface of adequate strength has been reached. Any localized soft soil zones encountered at the bearing elevations should be further excavated until adequate support soils are encountered. The cavity should be backfilled with structural fill as defined below, or the footing can be poured at the excavated depth. Structural fill used as backfill beneath footings should be limited to lean concrete, well-graded sand and gravel, or crushed stone placed and compacted in accordance with Section 5.3 “*Structural Fill and Fill Placement Control*”.

If it is necessary to support spread footings on structural fill, the fill pad must extend laterally a minimum distance beyond the edge of the footing. The minimum structural pad

width would correspond with a point at which an imaginary line extending downward from the outside edge of the footing at a 1H:2V (horizontal: vertical) slope intersects the surface of the natural soils. For example, if the depth to the bottom of excavation is 4 feet below the bottom of the foundation, the excavation would need to extend laterally beyond the edge of the footing at least 2 feet, as shown in Illustration "A" found at the conclusion of this report.

Excavation slopes should be maintained within all requirements set-forth by the Occupational Safety and Health Standards (OSHA), but specifically Section 1926 Subpart "P" – "Excavations". We recommend that any surcharge fill or heavy equipment be kept at least 5 feet away from the edge of the excavation.

Construction traffic on the exposed surface of the bearing soil will potentially cause some disturbance of the subgrade and consequently loss of bearing capacity. However, the degree of disturbance can be minimized by proper protection of the exposed surface.

5.4 Structural Fill and Fill Placement Control

Structural fill, defined as any fill which will support structural loads, should be clean and free of organic material, debris, deleterious materials and frozen soils. Samples of the proposed fill materials should be tested prior to initiating the earthwork and backfilling operations to determine the classification, the natural and optimum moisture contents and maximum dry density and overall suitability as a structural fill. **Structural fill should have a liquid limit less than 40 and a plasticity index less than 20.**

All structural fill beneath floor slabs, adjacent to foundations and over foundations, should be compacted to at least 95 percent (%) of its maximum Standard Proctor dry density (ASTM D-698). This minimum compaction requirement should be increased to 100 percent (%) of the maximum Standard Proctor dry density for fill supporting footings, provided these are designed as outlined Section 4.0 "Design Recommendations".

Structural fill supporting, around and over utilities should be compacted to at least 95 percent (%) of its maximum Standard Proctor dry density (ASTM D-698) for utilities underlying structural areas (i.e. buildings, pavements, sidewalks, etc.). However, the minimum compaction requirement can be reduced for backfill around and over the utilities to 90 percent (%) of the maximum Standard Proctor dry density where utilities underlie greenbelt areas (i.e. grassy lawns, landscaping, etc.). It is recommended that a

clean well-graded granular material be utilized as the bedding material, as well as the backfill material around and over the utility lines.

In cut areas, where pavement sections are planned, the upper 10 inches of subgrade should be scarified and compacted to a dry density of at least 100 percent (%) of the Standard Proctor maximum dry density (ASTM D-698). Any grade-raise fill placed within 1 foot of the base of the pavement section should also be compacted to at least 100 percent (%) of the Standard Proctor maximum dry density. This can be reduced to 95 percent (%) for structural fill placed more than 1 foot below the base of the pavement section.

To achieve the recommended compaction of the structural fill, we suggest that the fill be placed and compacted in layers not exceeding 8 inches in loose thickness (the loose lift thickness should be reduced to 6 inches when utilizing small hand compactors) and within the range of 2 percentage (%) points below or above the optimum moisture content value. All fill placement should be monitored by a *Patriot* representative. ***Each lift should be tested for proper compaction at a frequency of at least one (1) test every 2,500 square feet (ft²) per lift for the building areas, at least one (1) test every 10,000 square feet (ft²) per lift for the parking and roadway areas, and at a frequency of at least one (1) test for every 50 lineal feet of utility installation.***

5.5 Groundwater Considerations

Groundwater was observed during our field activities at depths between 13 feet below the existing ground surface (Refer to Section 3.3 “*Groundwater Conditions*”); which is expected to be below the anticipated foundation excavation depths. Depending on seasonal conditions, localized and sporadic groundwater infiltration may occur into the building foundation excavations on this site.

Groundwater inflow into shallow excavations **above** the groundwater table is expected to be adequately controlled by conventional methods such as gravity drainage and/or pumping from sumps. More significant inflow can be expected in deeper excavations **below** the groundwater table requiring more aggressive dewatering techniques, such as well or wellpoint systems. For groundwater to have minimal effects on the construction, foundation excavations should be constructed and poured in the same day, if possible.

6.0 EXPLORATIONAL PROCEDURES

6.1 Field Work

A total of six (6) soil borings were drilled, sampled, and tested at the project site on April 17, 2024 at the approximate locations shown on the Boring Location Map (Figure No. 2) in Appendix "A". The soil borings were drilled to depths of 20 feet in the proposed building area. All depths are given as feet below the existing ground surface.

The borings were advanced using 3¼ inch inside diameter hollow-stem augers. Samples were recovered in the undisturbed material below the bottom of the augers using the standard drive sample technique in accordance with ASTM D 1586-74. A 2 inch outside diameter by 1³/₈ inch inside diameter split-spoon sampler was driven a total of 18 inches with the number of blows of a 140 pound hammer falling 30 inches recorded for each 6 inches of penetration. The sum of blows for the final 12 inches of penetration is the Standard Penetration Test result commonly referred to as the N-value (or blow-count). Split-spoon samples were recovered at 2.5 feet intervals, beginning at a depth of 1 foot below the existing surface grade, extending to a depth of 10 feet, and at 5 feet intervals thereafter to the termination of the boring.

Water levels were monitored at each borehole location during drilling and upon completion of the boring. The boreholes were backfilled with auger cuttings prior to demobilization for safety considerations.

Upon completion of the boring program, all of the samples retrieved during drilling were returned to *Patriot's* soil testing laboratory where they were visually examined and classified. A laboratory-generated log of each boring was prepared based upon the driller's field log, laboratory test results, and our visual examination. Test boring logs and a description of the classification system are included in Appendix "A" in this report. Indicated on each log are: the primary strata encountered, the depth of each stratum change, the depth of each sample, the Standard Penetration Test results, groundwater conditions, and selected laboratory test data. The laboratory logs were prepared for each boring giving the appropriate sample data and the textural description and classification.

6.2 Laboratory Testing


Representative samples recovered in the borings were selected for testing in the laboratory to evaluate their physical properties and engineering characteristics. Laboratory analysis included: natural moisture content determinations (ASTM D 2216) and an

estimate of the unconfined compressive strength (q_u) of the cohesive soil samples utilizing a calibrated hand penetrometer (q_p) were obtained. The results of laboratory tests are summarized in Section 3.2 “*General Subsurface Conditions*”. Soil descriptions on the boring logs are in accordance with the Unified Soil Classification System (USCS).

7.0 ILLUSTRATIONS

See Illustrations “D” and “E” on the following pages. These illustrations are presented for reference for the remediation and backfill of sinkholes presented in Section 5.2.

See Illustrations “D” and “E” on the following pages. These illustrations are presented to further visually clarify several of the construction considerations presented in Section 5.3 “*Foundation Excavations*”.




Patriot Engineering & Environmental, Inc.

Project: Oolitic Drive Residences
922 North Oolitic Drive
Bloomington, Indiana

Drawn By: J. DuMond
Approved: B. Lauletta
DWG: 24-0455-11_detail

Project Number: 24-0455-11G
Date: May 2, 2024

Illustration A
Treatment Method for
Deep Sink Holes




Patriot Engineering & Environmental, Inc.

Project: Oolitic Drive Residences
922 North Oolitic Drive
Bloomington, Indiana

Drawn By: J. DuMond
Approved: B. Lauletta
DWG: 24-0455-11_detail

Project Number: 24-0455-11G
Date: May 2, 2024

Illustration B
Treatment Method for Sink Holes




SOIL OVERBURDEN <15'



Project: Oolitic Drive Residences 922 North Oolitic Drive Bloomington, Indiana	
Project Number: 24-0455-11G	Drawn By: J. DuMond
Date: May 2, 2024	Approved: B. Lauletta
	DWG: 24-0455-11_detail

Illustration C
Treatment Method for
Sink Holes



*d IS DEPTH TO SUITABLE SOILS

* IN COMPLIANCE WITH OSHA STANDARDS




**PATRIOT ENGINEERING
and Environmental, Inc.**
Engineering Value for Project Success
Consulting Environmental, Geotechnical
and Materials Engineers

Excavation for Footings In an Area of Fill ILLUSTRATION D

job. no.:

figure:



**PATRIOT ENGINEERING
and Environmental, Inc.**
Engineering Value for Project Success
Consulting Environmental, Geotechnical
and Materials Engineers

Excavation Near Existing
In Use Foundations
ILLUSTRATION E

job. no.:

figure:

APPENDIX A

SITE VICINITY MAP (FIGURE NO. 1)

BORING LOCATION MAP (FIGURE NO. 2)

BORING LOGS

BORING LOG KEY

**UNIFIED SOIL CLASSIFICATION SYSTEM
(USCS)**



Image Source:
USGS Bloomington Topo 2022

Figure 1

Site Vicinity Map



Patriot Engineering &
Environmental, Inc.

Project: Oolitic Drive Residences
922 North Oolitic Drive
Bloomington, Indiana

Project Number: 24-0455-11	Drawn By: J. DuMond
Date: April 23, 2024	Approved: M. Jonard
	DWG: 24-0455-11_geo



LEGEND

- PATRIOT Soil Boring
- B-1 Soil Boring ID

NOTES:

1. Boring locations were staked by PATRIOT. All locations are shown as approximate.
2. All locations were determined in the field with references to existing landmarks.
3. Image Source: Google Earth
4. Scale as shown.

Figure 2
Soil Boring Location Map

Project: Oolitic Drive Residences 922 North Oolitic Drive Bloomington, Indiana		Drawn By: J. DuMond
Project Number: 24-0455-11	Approved: M. Jonard	
Date: April 23, 2024	DWG: 24-0455-11_geo	



Patriot Engineering & Environmental, Inc.



LOG OF BORING B-1

(Page 1 of 1)

Oolitic Drive Residences
922 North Oolitic Drive
Bloomington, Indiana

Client Name : RCH LLC
Project Number : 24-0455-11G
Logged By : J. Rogers
Start Date : 04/17/2024
Drilling Method : HSA

Driller : E. Thomas
Sampling : Splitspoon
Approx. Elevation : +/- 881 feet
Latitude : 39°10'32.20"N
Longitude : 86°33'11.58"W

Depth (Feet)	Elevation (Feet)	Water Level	USCS	GRAPHIC	Water Levels					REMARKS	
					▼ During Drilling - Dry	▽ After Completion - Dry	◆ After 24 Hours - N/A	Samples	Rec %		SPT Results
DESCRIPTION											
0	881				TOPSOIL (4") Red, moist to very moist, stiff to hard, SILTY CLAY						
					1	100	4/4/7	2.3	24		
					2	67	4/6/7	1.9	23		
5	875		CL		3	33	6/10/13	2.7	24		
					4	94	6/7/8	4.5	22	Boring caved to 8.5 feet upon auger removal.	
10	870				5	17	50-3"			Auger refusal encountered at 13.5 feet.	
					Gray, highly weathered, LIMESTONE						
15	865				Splitspoon refusal encountered at 13.8 feet.						Groundwater was not encountered during drilling, nor upon completion.
20	860										
25											

05-02-2024 C:\Users\mjonard\Patriot_Engineering\GEO - Documents\Mtech\2024 Mtech\0455-11G\b1.bor



LOG OF BORING B-2

(Page 1 of 1)

Oolitic Drive Residences
922 North Oolitic Drive
Bloomington, Indiana

Client Name : RCH LLC
Project Number : 24-0455-11G
Logged By : J. Rogers
Start Date : 04/17/2024
Drilling Method : HSA

Driller : E. Thomas
Sampling : Splitspoon
Approx. Elevation : +/- 883 feet
Latitude : 39°10'32.44"N
Longitude : 86°33'11.73"W

Depth (Feet)	Elevation (Feet)	Water Level	USCS	GRAPHIC	Water Levels					REMARKS	
					▼ During Drilling - Dry	▽ After Completion - Dry	◆ After 24 Hours - N/A	Samples	Rec %		SPT Results
DESCRIPTION											
0	883				TOPSOIL (8")						
			CL		Brown, very moist, stiff, SILTY CLAY with trace gravel	1	100	4/5/7		26	Boring caved to 5 feet upon auger removal.
5			CL		Red, very moist, stiff to very stiff, SILTY CLAY	2	89	4/7/8	2.5	26	
			CH		Red, very moist, stiff to very stiff, CLAY	3	100	4/6/8	3.0	37	
10					Gray, highly weathered LIMESTONE	4	50	4/18/50-4"		28	
12					Auger refusal encountered at 12 feet						Groundwater was not encountered during drilling, nor upon completion.
15											
20											
25											



LOG OF BORING B-3

(Page 1 of 1)

Oolitic Drive Residences
922 North Oolitic Drive
Bloomington, Indiana

Client Name : RCH LLC
Project Number : 24-0455-11G
Logged By : J. Rogers
Start Date : 04/17/2024
Drilling Method : HSA

Driller : E. Thomas
Sampling : Splitspoon
Approx. Elevation : +/- 878 feet
Latitude : 39°10'31.98"N
Longitude : 86°33'11.69"W

Depth (Feet)	Elevation (Feet) 878	Water Level	USCS	GRAPHIC	Water Levels					REMARKS	
					▼ During Drilling - Dry	▽ After Completion - Dry	◆ After 24 Hours - N/A	Samples	Rec %		SPT Results
DESCRIPTION											
0				TOPSOIL (4")							
			CL	Red, moist, medium stiff, SILTY CLAY	1	17	9/5/3		21	Boring caved to 2 feet upon auger removal.	
3.75			CL	Red, moist, medium stiff, SILTY CLAY with some gravel and asphalt (FILL)	2	44	1/3/3		21		
5			CH	Red, very moist, hard, CLAY with trace limestone	3	33	4/50-4"		40		
8.70				Gray, highly weathered, LIMESTONE	4	44	50-4"				
10											
12				Auger refusal encountered at 12 feet.						Groundwater was not encountered during drilling, nor upon completion.	
15											
20											
25											



LOG OF BORING B-4

(Page 1 of 1)

Oolitic Drive Residences
922 North Oolitic Drive
Bloomington, Indiana

Client Name : RCH LLC
Project Number : 24-0455-11G
Logged By : J. Rogers
Start Date : 04/17/2024
Drilling Method : HSA

Driller : E. Thomas
Sampling : Splitspoon
Approx. Elevation : +/- 877 feet
Latitude : 39°10'31.60"N
Longitude : 86°33'11.65"W

Depth (Feet)	Elevation (Feet)	Water Level	USCS	GRAPHIC	Water Levels			Samples	Rec %	SPT Results	qp tsf	w %	REMARKS
					▼ During Drilling - Dry	▽ After Completion - Dry	◆ After 24 Hours - N/A						
DESCRIPTION													
0	877				TOPSOIL (3") Brown, slightly moist, stiff, SILTY CLAY with some asphalt (FILL)								
875			CL			1	44	4/4/6			16		
					ASPHALT and GRAVEL (FILL)								
5						2	72	11/13/6			6		
					Red, very moist, stiff to very stiff, CLAY								
870						3	50	4/6/7	3.9		28	Boring caved to 6 feet upon auger removal.	
						4	72	8/11/9	3.6	31			
10													
865			CH			5	100	7/13/10		27			
15						6	72	7/10/12		26			
860													
20					Boring terminated at 20 feet.							Groundwater was not encountered during drilling, nor upon completion.	
855													
25													



LOG OF BORING B-5

(Page 1 of 1)

Oolitic Drive Residences
922 North Oolitic Drive
Bloomington, Indiana

Client Name : RCH LLC
Project Number : 24-0455-11G
Logged By : J. Rogers
Start Date : 04/17/2024
Drilling Method : HSA

Driller : E. Thomas
Sampling : Splitspoon
Approx. Elevation : +/- 878 feet
Latitude : 39°10'31.17"N
Longitude : 86°33'12.62"W

Depth (Feet)	Elevation (Feet)	Water Level	USCS	GRAPHIC	Water Levels					REMARKS
					▼ During Drilling - 13.0 feet	▽ After Completion - Dry	◆ After 24 Hours - N/A	Samples	Rec %	
DESCRIPTION										
0	878				TOPSOIL (5") Brown, moist to very moist, soft to medium stiff, SILTY CLAY with trace gravel and organics (FILL)					
3.75			CL		1	33	1/1/24		21	Boring caved to 5 feet upon auger removal.
5					2	56	2/2/2		19	
6.75					3	33	4/4/4		24	
8.75					4	39	3/3/4		21	
13.75		▼	CL		5	100	1/3/3		29	
16.75					6	100	4/6/6		21	
20					Boring terminated at 20 feet.					
25										



LOG OF BORING B-6

(Page 1 of 1)

Oolitic Drive Residences
922 North Oolitic Drive
Bloomington, Indiana

Client Name : RCH LLC
Project Number : 24-0455-11G
Logged By : J. Rogers
Start Date : 04/17/2024
Drilling Method : HSA

Driller : E. Thomas
Sampling : Splitspoon
Approx. Elevation : +/- 878 feet
Latitude : 39°10'31.23"N
Longitude : 86°33'11.77"W

Depth (Feet)	Elevation (Feet)	Water Level	USCS	GRAPHIC	Water Levels					REMARKS		
					▼ During Drilling - Dry	▽ After Completion - Dry	◆ After 24 Hours - N/A	Samples	Rec %		SPT Results	qp tsf
DESCRIPTION												
0	878				TOPSOIL (5")							
			CL		Brown, moist, stiff, SILTY CLAY with trace asphalt (FILL)	1	94	4/5/5		21	Boring caved to 8 feet upon auger removal.	
3.75			CL		Brown, moist, medium stiff, SILTY CLAY with trace asphalt (FILL)	2	56	4/5/5				
5			CL		Brown, moist, medium stiff, SILTY CLAY with trace asphalt (FILL)	3	33	4/4/3		19		
8.70			CL		Brown, moist, medium stiff, SILTY CLAY with some gravel and brick (FILL)	4	17	1/3/2				
10			CL		Brown, moist, medium stiff, SILTY CLAY with some gravel and brick (FILL)	5	67	9/11/12	3.3	32		
15	865		CH		Red, very moist, stiff to hard, CLAY	6	100	4/9/12	3.0	37		
20	860		Boring terminated at 20 feet.					Groundwater was not encountered during drilling, nor upon completion.				
25	855											

BORING LOG KEY

UNIFIED SOIL CLASSIFICATION SYSTEM (USCS) FIELD CLASSIFICATION SYSTEM FOR SOIL EXPLORATION

NON-COHESIVE SOILS (Silt, Sand, Gravel, and Combinations)

Density	Field Identification (SPT Blows/ft)	Grain Size Terminology		
		<u>Soil Fraction</u>	<u>Particle Size</u>	<u>US Standard Sieve Size</u>
Very Loose	0 - 4	Boulders	> 12 inches	> 12 inches
Loose	5 - 10	Cobbles	3 - 12 inches	3 - 12 inches
Medium Dense	11 - 30	Gravel: Coarse	¾ - 3 inches	¾ - 3 inches
Dense	31 - 50	Small	4.76 mm - ¾ inch	No. 4 - ¾ inches
Very Dense	> 51	Sand: Coarse	2.00 - 4.76 mm	No. 10 - No. 4
		Medium	0.42 - 2.00 mm	No. 40 - No. 10
		Fine	0.074 - 0.42 mm	No. 200 - No. 40
		Silt	0.005 - 0.074 mm	< No. 200
		Clay	< 0.005 mm	< No. 200

RELATIVE PROPORTIONS FOR SOILS

<u>Descriptive Term</u>	<u>Percent</u>
Trace	1 - 10
Little	11 - 20
Some	21 - 35
And	36 - 50

COHESIVE SOILS

(Clay, Silt and Combinations)

<u>Consistency</u>	<u>Unconfined Compressive Strength (tons/ft²)</u>	<u>Field Identification (SPT Blows/ft)</u>
Very Soft	Less than 0.25	0 - 2
Soft	0.25 - < 0.5	3 - 4
Medium Stiff	0.5 - < 1.0	5 - 8
Stiff	1.0 - < 2.0	9 - 15
Very Stiff	2.0 - < 4.0	16 - 30
Hard	Over 4.0	> 30

Classification: Provided on Boring Logs are made by visual inspection.


Standard Penetration Test: Driving a 2 inch outer-diameter (O.D.) by 1½ inch inner-diameter (I.D.) split-spoon sampler a total of 18 inches into undisturbed soil with the number of blows of a 140 pound hammer free-falling a distance of 30 inches recorded for each 6 inches of penetration. The sum of blows for the final 12 inches of penetration is the Standard Penetration Test result commonly referred to as the "N"-value (or blow-count).

Strata Changes: In the column "Descriptions" on the Boring Logs the horizontal lines represent strata changes. A solid line (——) represents an observed change, a dashed line (- - - -) represents an estimated change.

Groundwater: Observations were made at the times indicated on the Boring Logs. Fluctuations in the groundwater level should be expected over time due to variations in rainfall and other environmental or physical factors. *Groundwater symbols:* (▼)-observed groundwater level and/or elevation during drilling; (▽)-observed groundwater level and/or elevation upon completion of boring.


Unified Soil Classification System (USCS)

Major Divisions		Group Symbol	Typical Names	Classification Criteria for Coarse-Grained Soils				
Coarse-grained soils (more than half of material is larger than No. 200)	Gravels (more than half of coarse fraction is larger than No. 4 sieve size)	Clean gravels (little or no fines)	GW	Well-graded gravels, gravel-sand mixtures, little or no fines	$C_u \geq 4$ $1 \leq C_c \leq 3$	$C_u = \frac{D_{60}}{D_{10}}$	$C_c = \frac{D_{30}^2}{D_{10} D_{60}}$	
		Gravels with fines (appreciable amount of fines)	GM	Silty gravels, gravel-sand-silt mixtures	Atterberg limits below A line or $P_L < 4$			
		GC	Clayey gravels, gravel-sand-clay mixtures					Above A line with $4 < P_L < 7$ are borderline cases requiring use of dual symbols
		GP	Poorly graded gravels, gravel-sand mixtures, little or no fines	Not meeting all gradation requirements for GW ($C_u < 4$ or $1 > C_c > 3$)				
	Sands (more than half of coarse fraction is smaller than No. 4 sieve size)	Clean sands (little or no fines)	SW	Well-graded sands, gravelly sands, little or no fines	$C_u \geq 6$ $1 \leq C_c \leq 3$	$C_u = \frac{D_{60}}{D_{10}}$	$C_c = \frac{(D_{30})^2}{D_{10} D_{60}}$	
		Sands with fines (appreciable amount of fines)	SM	Silty sands, sand-silt mixtures	Atterberg limits below A line or $P_L < 4$			
		SC	Clayey sands, sand-clay mixtures					Limits plotting in hatched zone with $4 \leq P_L \leq 7$ are borderline cases requiring use of dual symbols
		SP	Poorly graded sands, gravelly sands, little or no fines	Not meeting all gradation requirements for SW ($C_u < 6$ or $1 > C_c > 3$)				
				SC	Clayey sands, sand-clay mixtures	Atterberg limits above A line with $P_L > 7$		
				SM	Silty sands, sand-silt mixtures	Atterberg limits below A line or $P_L < 4$		
Fine-grained soils (more than half of material is smaller than No. 200)	Silt and clays (liquid limit <50)	ML	Inorganic silts and very fine sands, rock flour, silty or clayey fine sands, or clayey silts with slight plasticity	<ol style="list-style-type: none"> Determine percentages of sand and gravel from grain size curve. Depending on percentages of fines (fraction smaller than 200 sieve size), coarse-grained soils are classified as follows: Less than 5% - GW, GP, SW, SP More than 12% - GM, GC, SM, SC 5-12% - Borderline cases requiring dual symbols 				
		CL	Inorganic clays of low to medium plasticity, gravelly clays, sandy clays, silty clays, lean clays					
		OL	Organic silts and organic silty clays of low plasticity					
	Silt and clays (liquid limit >50)	MH	Inorganic silts, micaceous or diatomaceous fine sandy or silty soils, elastic silts					
		CH	Inorganic clays or high plasticity, fat clays					
		OH	Organic clays of medium to high plasticity, organic silts					
	Highly organic soils	PT	Peat and other highly organic soils					



APPENDIX B

SEISMIC SITE CLASS EVALUATION

 This is a beta release of the new ATC Hazards by Location website. Please [contact us](#) with feedback.

 The ATC Hazards by Location website will not be updated to support ASCE 7-22. [Find out why.](#)


ATC Hazards by Location

Search Information


Address: 922 N Oolitic Dr, Bloomington, IN 47404, USA
Coordinates: 39.175149, -86.5534332
Elevation: 879 ft
Timestamp: 2024-05-03T13:50:55.486Z
Hazard Type: Seismic
Reference Document: IBC-2012
Risk Category: II
Site Class: C



MCER Horizontal Response Spectrum



Design Horizontal Response Spectrum



Basic Parameters

Name	Value	Description
S_S	0.225	MCE _R ground motion (period=0.2s)
S_1	0.107	MCE _R ground motion (period=1.0s)
S_{MS}	0.269	Site-modified spectral acceleration value
S_{M1}	0.181	Site-modified spectral acceleration value
S_{DS}	0.18	Numeric seismic design value at 0.2s SA
S_{D1}	0.121	Numeric seismic design value at 1.0s SA

Additional Information

Name	Value	Description
SDC	B	Seismic design category
F_a	1.2	Site amplification factor at 0.2s
F_v	1.693	Site amplification factor at 1.0s
CR_S	0.9	Coefficient of risk (0.2s)
CR_1	0.854	Coefficient of risk (1.0s)
PGA	0.107	MCE _G peak ground acceleration
F_{PGA}	1.2	Site amplification factor at PGA
PGA_M	0.128	Site modified peak ground acceleration
T_L	12	Long-period transition period (s)
$SsRT$	0.225	Probabilistic risk-targeted ground motion (0.2s)
$SsUH$	0.25	Factored uniform-hazard spectral acceleration (2% probability of exceedance in 50 years)
SsD	1.5	Factored deterministic acceleration value (0.2s)
$S1RT$	0.107	Probabilistic risk-targeted ground motion (1.0s)
$S1UH$	0.125	Factored uniform-hazard spectral acceleration (2% probability of exceedance in 50 years)
$S1D$	0.6	Factored deterministic acceleration value (1.0s)

PGAd	0.6	Factored deterministic acceleration value (PGA)
------	-----	---

The results indicated here DO NOT reflect any state or local amendments to the values or any delineation lines made during the building code adoption process. Users should confirm any output obtained from this tool with the local Authority Having Jurisdiction before proceeding with design.

Please note that the ATC Hazards by Location website will not be updated to support ASCE 7-22. [Find out why.](#)

Disclaimer

Hazard loads are provided by the U.S. Geological Survey [Seismic Design Web Services](#).

While the information presented on this website is believed to be correct, ATC and its sponsors and contributors assume no responsibility or liability for its accuracy. The material presented in the report should not be used or relied upon for any specific application without competent examination and verification of its accuracy, suitability and applicability by engineers or other licensed professionals. ATC does not intend that the use of this information replace the sound judgment of such competent professionals, having experience and knowledge in the field of practice, nor to substitute for the standard of care required of such professionals in interpreting and applying the results of the report provided by this website. Users of the information from this website assume all liability arising from such use. Use of the output of this website does not imply approval by the governing building code bodies responsible for building code approval and interpretation for the building site described by latitude/longitude location in the report.

APPENDIX C

GENERAL QUALIFICATIONS

**STANDARD CLAUSE FOR UNANTICIPATED
SUBSURFACE CONDITIONS**

GENERAL QUALIFICATIONS
of Patriot Engineering's Geotechnical Engineering Investigation

This report has been prepared at the request of our client for his use on this project. Our professional services have been performed, findings obtained, and recommendations prepared in accordance with generally accepted geotechnical engineering principles and practices. This warranty is in lieu of all other warranties either expressed or implied.

The scope of our services did not include any environmental assessment or investigation for the presence or absence of wetlands, hazardous or toxic materials in the soil, groundwater, or surface water within or beyond the site studied. Any statements in this report or on the test borings logs regarding vegetation types, odors or staining of soils, or other unusual conditions observed are strictly for the information of our client and the owner.

This report may not contain sufficient information for purposes of other parties or other uses. This company is not responsible for the independent conclusions, opinions or recommendations made by others based on the field and laboratory data presented in this report. Should there be any significant differences in structural arrangement, loading or location of the structure, our analysis should be reviewed.

The recommendations provided herein were developed from the information obtained in the test borings, which depict subsurface conditions only at specific locations. The analysis, conclusions, and recommendations contained in our report are based on site conditions as they existed at the time of our exploration. Subsurface conditions at other locations may differ from those occurring at the specific drill sites. The nature and extent of variations between borings may not become evident until the time of construction. If, after performing on-site observations during construction and noting the characteristics of any variation, substantially different subsurface conditions from those encountered during our explorations are observed or appear to be present beneath excavations, we must be advised promptly so that we can review these conditions and reconsider our recommendations where necessary.

If there is a substantial lapse of time between the submission of our report and the start of work at the site, or if conditions have changed due to natural causes or construction operations at or adjacent to the site, we urge that our report be reviewed to determine the applicability of the conclusions and recommendations considering the changed conditions and time lapse.

We urge that Patriot be retained to review those portions of the plans and specifications that pertain to earthwork and foundations to determine whether they are consistent with our recommendations. In addition, we are available to observe construction, particularly the compaction of structural backfill and preparation of the foundations, and such other field observations as may be necessary.

In order to fairly consider changed or unexpected conditions that might arise during construction, we recommend the following verbiage (Standard Clause for Unanticipated Subsurface Conditions) be included in the project contract.

STANDARD CLAUSE FOR UNANTICIPATED SUBSURFACE CONDITIONS

"The owner has had a subsurface exploration performed by a soils consultant, the results of which are contained in the consultant's report. The consultant's report presents his conclusions on the subsurface conditions based on his interpretation of the data obtained in the exploration. The contractor acknowledges that he has reviewed the consultant's report and any addenda thereto, and that his bid for earthwork operations is based on the subsurface conditions as described in that report. It is recognized that a subsurface exploration may not disclose all conditions as they actually exist and further, conditions may change, particularly groundwater conditions, between the time of a subsurface exploration and the time of earthwork operations. In recognition of these facts, this clause is entered in the contract to provide a means of equitable additional compensation for the contractor if adverse unanticipated conditions are encountered and to provide a means of rebate to the owner if the conditions are more favorable than anticipated.

At any time during construction operations that the contractor encounters conditions that are different than those anticipated by the soils consultant's report, he shall immediately (within 24 hours) bring this fact to the owner's attention. If the owner's representative on the construction site observes subsurface conditions which are different than those anticipated by the consultant's report, he shall immediately (within 24 hours) bring this fact to the contractor's attention. Once a fact of unanticipated conditions has been brought to the attention of either the owner or the contractor, and the consultant has concurred, immediate negotiations will be undertaken between the owner and the contractor to arrive at a change in contract price for additional work or reduction in work because of the unanticipated conditions. The contract agrees that the following unit prices would apply for additional or reduced work under the contract. For changed conditions for which unit prices are not provided, the additional work shall be paid for on a time and materials basis."

Another example of a changed conditions clause can be found in paper No. 4035 by Robert F. Borg, published in ASCE Construction Division Journal, No. CO2, September 1964, page 37.

**BLOOMINGTON BOARD OF ZONING APPEALS
STAFF REPORT****CASE #: V-15-24/VAR-2024-04-0032****DATE: May 23, 2024****Location: 803 E Winslow Rd (parcel #53-08-09-400-002.000-009)**

PETITIONER/OWNER: Sarah Nelson
2600 S Henderson St, Bloomington, IN

REQUEST: Variance from fence height standards in the Residential Small Lot (R3) zoning district.

REPORT: This 0.95 acre property is located at 803 E Winslow Street (two properties to the west of the intersection of E Winslow Rd and S Highland Ave) and is zoned Residential Small Lot (R3). Surrounding zoning districts are Residential Small Lot (R3) to the west and north, Residential Medium Lot (R2) to the east and southeast, and Residential Multifamily (RM) to the southwest. Surrounding land uses include detached single-family residential use to the north and east, “place of worship” use to the southeast, Acadia Court leasing office and multifamily residential use to the southwest, and detached single family residential use to the west. The future land use designation for this property is Neighborhood Residential.

The petitioner is requesting to place a six foot tall wooden L-shaped privacy fence at the southwest corner of the property. This privacy fence would be placed eight feet north of the southwest property corner. The fence would extend 40 feet east, parallel to the front property line and it would extend 16 feet to the north along the western property line. The purpose of this requested privacy fence is to block traffic lights and noise from E Winslow Rd and S Acadia Ct.

The property owner is also requesting to place a five foot tall woven wire fence along the West property line. This fence would connect to the north most portion of the aforementioned six foot privacy fence along the west property line and continue north along the property line to the northwest corner of the property. The purpose of the five foot woven wire fence is to delineate the property line and discourage possible trespass from development of the property to the west.

On interior lots, such as 803 E Winslow St, the Unified Development Ordinance (UDO), Title 20 of the Bloomington Municipal Code, states that fences cannot exceed four feet in height forward of the front building wall of the primary structure (which is the space between the front property line and the front building wall of the primary structure). The proposed 6-foot wooden privacy fence in the southwest corner of the property and roughly 46 feet of the proposed five-foot woven wire fence along the western property line would be placed in a location of the property where UDO maximum fence height standards are 4 feet. Therefore, a variance must be granted to allow the requested fence heights on this property.

The petitioner is requesting a variance from fence height standards in the Residential Small Lot (R3) zoning district, to allow a six-foot wooden fence and five-foot woven wire fence forward of the front building wall.

CRITERIA AND FINDINGS FOR DEVELOPMENT STANDARDS VARIANCE

20.06.080(b)(3)(E) Standards for Granting Variances from Development Standards:

A variance from the development standards of the Unified Development Ordinance may be approved only upon determination in writing that each of the following criteria is met:

- 1) *The approval will not be injurious to the public health, safety, morals, and general welfare of the community.*

PROPOSED FINDING: The granting of this variance will not be injurious to the public health, safety, morals, or general welfare of the community. The six foot fence would be set 8 feet north of the multiuse path and sit below the elevation of the multiuse path. It would not interfere with or create a safety hazard for users of the path.

- 2) *The use and value of the area adjacent to the property included in the Development Standards Variance will not be affected in a substantially adverse manner.*

PROPOSED FINDING: No adverse impacts to the use and value of surrounding properties as a result of the requested variance are found. The four-foot fence maximum in the UDO is intended to help promote visibility and allow for a positive interface and interactions between private property and the users of the adjacent public right-of-way. The six foot portion would extend the length of 40 feet along the right-of-way, and is eight feet north of the right-of-way line. The requested five-foot woven wire fence is transparent and thus will not block visibility between the front door of this home and the neighbor to the west.


- 3) *The strict application of the terms of the Unified Development Ordinance will result in practical difficulties in the use of the property; that the practical difficulties are peculiar to the property in question; that the Development Standards Variance will relieve the practical difficulties.*

PROPOSED FINDING: The Department does find that the strict application of the terms of the Unified Development Ordinance will result in practical difficulties in the use of the property and that these practical difficulties are peculiar to the property in question. This property is across the street from Acadia Ct and Acadia apartments, which generates more traffic than an average residential subdivision. Although S Arcadia Ct has been in place for over 10 years, 803 E Winslow Rd was previously protected by significant vegetation from traffic headlights traveling along E Winslow Rd and entering and leaving Acadia Apartment complex. Approval of this variance would allow the placement of a wooden privacy fence that would enable the property to continue to be used as a livable residential dwelling because the fence would be high enough to block the traffic headlights from the intersection of E Winslow Rd and Acadia Ct. that were previously shielded by the vegetation.




The approval of this variance would allow the property owners both increased security of their residential property while also maintaining visibility and connectivity to the neighboring properties and the public ROW as desired by the UDO.


RECOMMENDATION: The Department recommends that the Board of Zoning Appeals adopt the proposed findings and approve case V-15-24/ VAR-2024-04-0032, with the following conditions:


1. The petitioners may only install the types of fencing approved in the packet for this variance, and only at the heights and locations shown.



Map Legend


-  Addresses
-  Parcels
-  Bloomington Municipal Boundary





Map Legend

- Parcels
- Bloomington Municipal Boundary
- Residential Small Lot
- Residential Multifamily
- Contributing
- Parks and Open Space
- Residential Medium Lot



April 22, 2024

I. Reason for Variance Request

- A. Request for variance to remediate the adverse impact of the city's construction of the pathway to the use and enjoyment of the property.
- B. In the late 1960's at the request of the property owner, the local government directed placement of pines outside of the Winslow Road Right-of-Way so they would not interfere with any future plans.
- C. Winslow Road was subsequently widened fully on the North side consuming the existing Right-of-Way to the North.
- D. In 2019 the city obtained additional Right-of-Way to the North of Winslow Road for the pathway. In 2020 the city constructed the pathway removing the trees and underbrush that had provided screening since the early 1970's. This resulted in an open area allowing traffic light and noise to encroach unduly onto Parcel 53-08-09-400-002.000-009.
- E. The house on Parcel 53-08-09-400-002.000-009 was constructed in 1992, when the trees and vegetation were already in place.

II. Background

- A. Pictures #'s 1 and 2 ----looking East from the driveway at 765 E. Winslow Road show stumps of 4 mature 50+/- year old white pines that were cut out of the 40 foot road frontage where we want to put the privacy fence.
- B. We have measured the four foot height along the proposed location of the privacy fence. Four feet is well below the height of headlights.
- C. Pictures 3 and 4 show how open that area is now as seen from our front porch.
- D. Pictures 8 and 9 show the elevation drop from Winslow Road onto the property.
- E. The wooden privacy fence along the South property line would be placed eight feet North of the North edge of the pathway. The location of the privacy fence is across from a business(apartment leasing) and the entrance to a subdivision which generates more traffic. There are no houses across the street and we are not located in a subdivision.

III. Proposed Remediation

- A. We propose to replace the removed vegetation screening with a six foot tall wooden privacy fence to block out traffic lights and noise. In addition, a five foot tall woven wire fence along the West property line is being requested.
- B. The privacy fence would extend from a point eight feet North of the South West property corner running East 40 feet, and from that same point extending North 16 feet along the westerly property line connecting to a five foot tall woven wire fence which will then continue North along the property line to the North West property corner. The purpose of the five foot woven wire fence is to:
 - 1) delineate the property line and, 2) discourage possible trespass from development of the property to the West. Pictures #'s 5 and 6 show the type of woven wire fence to be used. Picture #7 depicts the proposed five foot woven wire attachment to the wooden privacy fence.

IV. Compliance with General Approval Criteria BMC 20.06.080 (b)(3)(E)(i)

- A. The proposed fencing will be fully on Parcel 53-08-09-400-002.000-009. It will not be on or interfere with public property, health, safety, morals, or the general welfare of the community.
- B. The use and value of adjacent areas will not be substantially affected.
- C. The strict application of the UDO will result in the continued practical difficulties in the use of this property (created with the construction of the pathway in 2020 and experienced since). These practical difficulties are peculiar to this parcel only, affecting no other parcels. The requested variance to the development standards (of the existing property development) will relieve the practical difficulties by largely returning the property to its previous state which existed prior to construction of the house in 1992.

PLAT OF SURVEY - ORIGINAL BOUNDARY
 A PART OF THE SOUTHEAST QUARTER OF
 SECTION 9, T8N, R1W, MONROE CO., INDIANA
 JOB No. 111153 Client Name: Sarah Nelson and Roger Stuart

NOTES:
 1. FIELD WORK PERFORMED SEPTEMBER 16 THROUGH NOVEMBER 14, 2022.




2. ALL 5/8" REBAR SET HAVE YELLOW CAP STAMPED "BRJ INC 6892 IN".

3. (R) = RECORDED
 (M) = MEASURED
 (C) = CALCULATED FROM RECORD

(A.G.) = ABOVE GROUND
 (B.G.) = BELOW GROUND

4. BASIS OF BEARINGS: INDIANA STATE PLANE COORDINATES WEST ZONE, US SURVEY FEET.

5. THIS SURVEY IS NOT COMPLETE WITHOUT THE ASSOCIATED REPORT OF SURVEY.



SHEET 1 OF 2

Bloomington • Bedford • Paoli
 1351 West Tapp Road • Bloomington, Indiana 47403 • P. 812.336.9277






BRCJcivil.com


Nelson Parcel No. 53-08-09-400-002.000-009



1" = 40'

Legend:

-  Property Line
-  ROW
-  Proposed Fence



Acadia Court



a view of the front of this property before construction of the multi-use pathway, after the cutting of trees.





shows the elevation change between the street and the home, demonstrating why a four-foot fence is insufficient to block the traffic lights



shows the elevation change between the street and the home, demonstrating why a four-foot fence is insufficient to block the traffic lights

186 an example of the woven wire fencing that will be placed along the west edge of the property



an example of the woven wire fencing that will be placed along the west edge of the property






an example demonstrating of how the wooden privacy fence will connect to the woven wire fencing along the west edge of property



shows the elevation change between the street and the home, demonstrating why a four-foot fence is insufficient to block the traffic lights





a view of the front of this property after construction of the multi-use pathway

BLOOMINGTON BOARD OF ZONING APPEALS
STAFF REPORT
Location: 400 N. Walnut Street

CASE #: V-16-24
DATE: May 23, 2024

PETITIONER: Bloomington Lodge 446 Benevolent Protective Order of Elks, USA
 PO Box 97, Bloomington, IN

CONSULTANTS: Stuart Baggerly
 304 N. Morton Street, Bloomington, IN

REQUEST: Variance from front yard setback requirements for a flagpole in the Mixed-Use Downtown (MD) within the Downtown Core Overlay (DCO) district.

REPORT: This 0.5 acre property is located at the northeast corner of N. Walnut Street and W. 8th Street and is zoned Mixed-Use Downtown (MD) and is within the Downtown Core Overlay (DCO) district. Surrounding land uses include an office to the north, restaurants to the west and south, and single and multifamily residences to the east. The property has been developed with a local chapter of the Benevolent and Protective Order of the Elks Lodge. There are no known regulated environmental features on the property.

The petitioner recently removed a dilapidated flag pole from the front yard of the property and constructed a new concrete pad with 9 new flag poles. The UDO states that flag poles shall be located no closer than 12 feet from the front property line and one foot from side and rear property lines. Four of the nine flag poles that were installed do not meet the 12 foot setback and are 5', 7', 10', and 11' from the front property line. The location of the pad and flagpoles was the only open space on the property that was not encumbered with building or parking area. The location of the poles does not lie in any vision clearance triangles for the intersection. There is no minimum landscape area requirement for this Overlay District. The location of the concrete pad meets all UDO requirements as well.

CRITERIA AND FINDINGS FOR DEVELOPMENT STANDARDS VARIANCE
20.06.080(b)(3)(E) Standards for Granting Variances from Development Standards:

A variance from the development standards of the Unified Development Ordinance may be approved only upon determination in writing that each of the following criteria is met:

- 1) *The approval will not be injurious to the public health, safety, morals, and general welfare of the community.*

PROPOSED FINDING: The granting of the variance will not be injurious to the public health, safety, morals, or general welfare of the community. The location of the flagpoles within the required setback will not have any impact on the public health, safety, morals, or general welfare of the community as they do not present a vision clearance triangle issue.

- 2) *The use and value of the area adjacent to the property included in the Development*

Standards Variance will not be affected in a substantially adverse manner.


PROPOSED FINDING: No adverse impacts to the use and value of surrounding properties as a result of the requested variance to allow the flagpoles in the front setback are found as they present no safety issues with their location.

- 3) *The strict application of the terms of the Unified Development Ordinance will result in practical difficulties in the use of the property; that the practical difficulties are peculiar to the property in question; that the Development Standards Variance will relieve the practical difficulties.*

PROPOSED FINDING: The Department does find that the strict application of the terms of the Unified Development Ordinance will result in practical difficulties in the use of the property as the display of flags for this use is customary and there is limited area on the property to place these flag poles. The practical difficulties are peculiar to the property in question in that the existing building location combined with the desire for visibility of the flag poles limits the potential locations. Additionally, in the current Unified Development Ordinance, Downtown buildings are required to be closer to the street and allowed to have a zero setback, so a building with a much larger sense of mass and scale could be built in the same location. The building itself on this property is taller than the flagpoles and is more impactful in terms of mass and scale than the four poles in the setback area.

RECOMMENDATION: The Department recommends that the Board of Zoning Appeals adopt the proposed findings and approve V-16-24 with the following condition:

1. This approval is for the number and locations of flag poles as submitted. Any future development or placement of additional flag poles must meet all development standards.




Map Legend

- Parcels
- Buildings
- Pavement
- Alley
- Lane
- Hidden Pavement; Hidden Alley
- Other Pavement
- Current
- City Maintained Streets

Street


- G
- M





Map Legend

- Addresses
- Parcels
- Buildings
- Pavement
- Alley
- Current
- City Maintained Streets
- Street Typology**
- General Urban
- Main Street
- Neighborhood Connector
- Neighborhood Residential





Bloomington Lodge No. 446, B. P. O. Elks
BLOOMINGTON, INDIANA 47401

April 25, 2024

Greetings, members of the Bloomington, Indiana Board of Zoning Appeals:

The Bloomington Elks Lodge #446 is in receipt of your notice of violation of zoning with regard to set back from our property line. We do appreciate your taking the time to meet with our counsel, one of our trustees, and representatives of Building Associates. Pursuant to that meeting, we are filing to request a variance hearing.

General Approval Criteria.

- a. The approval will not be injurious to the public health, safety, morals, and general welfare of the community.

The Elks Lodge #446 Tribute to The Services flag installation is what the title implies: A tribute consisting of flags of all branches of the military as well as to the State of Indiana and the United States of America. By no means could this installation be seen as injurious to the public health, safety, morals, and general welfare of our community.


- b. The use and value of the area adjacent to the property included in the development standards *variance* will not be affected in a substantially adverse manner; and


The use and values of the area adjacent to the Elks Lodge #446 Tribute to The Services flag installation can in no way substantially affect the adjacent properties in an adverse manner. Directly to the South of the installation is the now defunct Kahlo night club. To the South West is the ever raucous Kilroys Sports Bar. To the west is the defunct Topos restaurant which has stood empty for years, as well as a Papa Johns Pizza substation, and the now defunct Switchyard Brew Pub. The Installation can hardly be seen as a negative addition to the area.


- c. The strict application of the terms of this UDO will result in practical difficulties in the use of the property; that the practical difficulties are peculiar to the property in question; that the development standards *variance* will relieve the practical difficulties.

The Order of Elks is distinctly American, and as such, we make the flag of our country the symbol of our order. The Order of Elks was founded on February 16, 1868 by a group of veterans of the civil war who were looking for a way to rally together and do good deeds and charitable works for their community. Throughout the history of the Order of Elks it has welcomed members of all branches of

the armed services, as well as like minded members of our community. The Elks Lodge #446 Tribute to The Services flag installation was conceived, designed, and paid for through contributions of various Elks Lodge members. Strict enforcement of the Bloomington UDO would require the destruction of the installation. The result of strict enforcement of the UDO would be dire indeed. While granting this request for a variance will have no negative impact whatsoever on the immediate area, or the status or stature of the City in general.


Candice Crandall, Head Trustee


Avery Hays, 2 year Trustee


Reid Dallas, 3 year Trustee


Melissa Wallace, Secretary





**BLOOMINGTON BOARD OF ZONING APPEALS
STAFF REPORT
LOCATION: 506 E. Wylie Street**

**CASE#: CU-17-24
DATE: May 23, 2024**

PETITIONER: Bloomington Builders LLC & Latitude 39 North Properties, LLC
PO Box 67
Bloomington, IN 47402

REQUEST: The petitioner is requesting Conditional Use approval to allow a “Dwelling, duplex” use in the Residential Small Lot (R3) zoning district.

REPORT: The property is located at 506 E. Wylie Street and is zoned Residential Small Lot (R3). All surrounding properties are zoned Residential Small Lot (R3) and have been developed with single family residences. The property is currently vacant and within the Bryan Park Neighborhood Association area.

The petitioner is proposing to develop the site with a new duplex. The residence would face Wylie Street and be accessed by a driveway along the east side of the residence. Each unit would have its own entry facing Wylie Street with a sidewalk connecting the residence to Wylie Street. There is no sidewalk along this property frontage or sidewalks along adjacent properties. This petition would not be required to install a sidewalk along the property frontage, however new street trees are required and have been shown. The new residence will be two-stories with three bedrooms in each unit.

This petition was presented to both the Bryan Park and Elm Heights Neighborhood Associations. At those meetings neighbors expressed concerns regarding the amount of parking provided, the location of the driveway on the property, tree preservation, and potential for future home ownership of the units. In response to those comments the petitioner has adjusted the location of the driveway on the property to relocate it away from the residence to the west, and extended the length of the driveway. Unfortunately the location of a large Sycamore tree in the center of the property cannot be avoided. Each individual unit in the duplex will have its own entrance and separate utility connection to enable the possibility of future ownership through a condominium design.

The petitioner is requesting conditional use approval to allow the establishment of a “Duplex, dwelling” use on the property.

CRITERIA AND FINDINGS FOR CONDITIONAL USE PERMIT

20.06.040(d)(6)(B) General Compliance Criteria: All petitions shall be subject to review and pursuant to the following criteria and shall only be approved if they comply with these criteria.

- i. *Compliance with this UDO*
- ii. *Compliance with Other Applicable Regulations*
- iii. *Compliance with Utility, Service, and Improvement Standards*
- iv. *Compliance with Prior Approvals*

PROPOSED FINDING: There are use-specific standards that apply to the use “dwelling, duplex” within the R3 zoning district and this petition meets those standards. The property owner does not have any notices of violation on file. Each unit has its own separate exterior entrance and the design of the building incorporates many elements similar to surrounding residences on this block face including- pitched roof, covered porches, and building setback. The structure will contain no more than six bedrooms. Each unit will have its own separate utility meters. The petitioner did attend Bryan Park and Elm Heights Neighborhood Association meetings and presented this petition as required. There are no other known applicable regulations for this petition. There are water and sewer connections available in Wylie Street and no conflicts with connecting to those services have been identified. There are no known prior approvals for this site.

20.06.040(d)(6)(C) ADDITIONAL CRITERIA APPLICABLE TO CONDITIONAL USES

i. Consistency with Comprehensive Plan and Other Applicable Plans

The proposed use and development shall be consistent with and shall not interfere with the achievement of the goals and objectives of the Comprehensive Plan and any other applicable adopted plans and policies.

PROPOSED FINDING: This proposal is in line with the goals of the Comprehensive Plan. The Comprehensive Plan identifies this area as the “Mixed Urban Residential” land use category. The Comprehensive Plan states that the Mixed Urban Residential land use category is largely in older neighborhoods and that redevelopment should be compatible with surroundings. Policy 5.3.1 encourages opportunities for infill and redevelopment across Bloomington with consideration for increased residential densities, complementary design, and underutilized housing types such as accessory dwelling units and duplexes. This location is also well served by existing services and utilities. The proposal also accomplishes many of the design goals of the Comprehensive Plan in relation to compatibility with adjacent structures and has a clear relationship with the adjacent public street through the sidewalk connection from the residence to the sidewalk on the street. The proposal is in line with the Comprehensive Plan.

ii. Provides Adequate Public Services and Facilities

Adequate public service and facility capacity shall exist to accommodate uses permitted under the proposed development at the time the needs or demands arise, while maintaining adequate levels of service to existing development. Public services and facilities include, but are not limited to, streets, potable water, sewer, stormwater management structures, schools, public safety, fire protection, libraries, and vehicle/pedestrian connections and access within the site and to adjacent properties.

PROPOSED FINDING: The site has existing utility connection and no issues have been identified with the proposed connections.

iii. Minimizes or Mitigates Adverse Impacts

- 1. The proposed use and development will not result in the excessive destruction, loss or damage of any natural, scenic, or historic feature of significant importance.*
- 2. The proposed development shall not cause significant adverse impacts on*

- surrounding properties nor create a nuisance by reason of noise, smoke, odors, vibrations, or objectionable lights.*
3. *The hours of operation, outside lighting, and trash and waste collection must not pose a hazard, hardship, or nuisance to the neighborhood.*
 4. *The petitioner shall make a good-faith effort to address concerns of the adjoining property owners in the immediate neighborhood as defined in the pre-submittal neighborhood meeting for the specific proposal, if such a meeting is required.*

PROPOSED FINDING: There are no regulated natural or scenic features that will be impacted. Although there is one tree in the center of the property that the neighborhood expressed a desire to save, the location of the tree in the center of the property does not allow it to be saved and still develop the lot. The building is not located within a historic district. No significant adverse impacts are expected from the creation of the proposed duplex. No changes to trash and waste collection service are expected. Concerns from adjoining property owners were expressed at the respective Neighborhood Meetings and most have been addressed through the changes mentioned previously.


iv. *Rational Phasing Plan*

If the petition involves phases, each phase of the proposed development shall contain all of the required streets, utilities, landscaping, open space, and other improvements that are required to comply with the project's cumulative development to date and shall not depend upon subsequent phases for those improvements.

PROPOSED FINDING: No phasing is proposed with this plan.

RECOMMENDATION: The Department recommends that the Board of Zoning Appeals adopts the proposed findings and recommends approval of CU-17-24 with the following conditions:

1. This conditional use approval is limited to the design shown and discussed in the packet.
2. Street trees not more than 30' from center are required along the property frontage.



Map Legend

- Parcels
- Buildings
- Pavement


- Alley
- Current
- City Maintained Streets


Street Typology

- Neighborhood Connector
- Neighborhood Residential

Functional Classification

- Secondary Arterial
- Primary Collector





Map Legend

- Parcels
- Buildings
- Pavement


- Alley
- Current
- City Maintained Streets

Street Typology

- Neighborhood Connector
- Neighborhood Residential

Functional Classification

- Secondary Arterial
- Primary Collector



506 East Wylie Street, LLC

PO Box 67, Bloomington, Indiana

Petitioner's Statement

506 East Wylie Street Residence


Petitioner: 506 East Wylie Street, LLC, Bloomington, Indiana

Property Description

506 East Wylie Street is a vacant, residential lot near the intersection of East Wylie Street and South Henderson Street in the Bryan Park Neighborhood. The property is zoned R3 (Residential Small Lot). The property is bounded by single family residential uses on all sides as well as multifamily apartments to the Southeast. Adjacent Zoning is R3 on all sides.


Conditional Use Request

506 East Wylie Street, LLC, is filing a request for Conditional Use per the UDO for Dwelling, Duplex construction in R3 Zoning. The proposal meets the design requirements and the development standards in the UDO. The proposal consists of a new 1.5-story structure that includes two 3 bedroom, 3 bath dwelling units. The design reflects the requirements of the UDO in that separate exterior entrances for each unit face East Wylie Street. Additionally, various gable roof pitches reflect similar roof styles found in the surrounding neighborhood. The combination of horizontal "lap style" and vertical board and batten siding also help differentiate each dwelling unit. The building setback and vehicular access is also consistent with other homes along East Wylie Street. New water and sewer service, separate for each unit, has been coordinated with City of Bloomington Utilities and Engineering, and new electrical service, separate for each unit, will be coordinated with Duke Energy. Upon approval, construction would likely begin in December of 2024 with completion expected in the Summer of 2025.



01 VICINITY MAP

SCALE: 1/2" = 1'-0"



02 PROPOSED SITE PLAN

SCALE: 1/8" = 1'-0"

- TREE PLOT**
 - PLANT NEW STREET TREES 10' GREATER THAN 30' FROM CENTERLINE OF TREES
 - THREE TREES PLANTED, WHITE OAK
 - TREES ARE 2" MINIMUM CALIPER SIZE
 - SMALL STREET TREES SELECTED DUE TO O.H. UTILITY LINES
- SIDEWALK**
 - NEW 6' SIDEWALK CONSTRUCTION, APPROXIMATELY 66 LINEAL FEET
 - NEW SIDEWALK CONSTRUCTION TO CONNECT TO EXISTING SIDEWALK
 - 5' TREE PLOT TO BE MAINTAINED BETWEEN STREET CURB AND NEW SIDEWALK CONSTRUCTION

Bloom
 Design + Build
 Design • Construction • Consulting

Scope of Work:
 REFER TO ARCHITECTURAL SHEETS BY OTHERS FOR SCOPE

EAST WYLIE NEW DUPLEX
 East Wylie Street
 Bloomington, IN 47401

Table of Contents:	
SITE PLAN	
Square Feet Totals	
Lot Size	9,834 sf
Building Footprint	4,458 sf
Sidewalk & Driveway	4,058 sf
TOTAL Impervious Surface Area	2,856 sf
Impervious Area Percentage	27.0%


No.	Revision / Issue	Date
1		
2		
3		
4		

Project Phase		Sheet No.
SITE PLAN		SITE
Date		
05.13.2024		
Drawn By: bloom design build		
Scale: Refer to Sheets		

506 East Wylie Street Duplex

Preliminary Plan Set

OWNER:
506 EAST WYLIE STREET, LLC



FIRST FLOOR PLAN
SCALE: 1/4" = 1'-0"

DOOR SCHEDULE								
NO.	SIZE		THICK.	TYPE	MATERIAL	LOCK SET	FRAME	REMARKS
	WIDTH	HEIGHT						
A	3'-0"	7'-0"	1 3/8"	1	FIBER-GLASS	ENTRY	WOOD	HINGE PIN AUTO-CLOSER
B	2'-8"	6'-8"	1 3/4"	2	S.C.-COMP.	PRIVACY	WOOD	
C	2'-4"	6'-8"	1 3/4"	2	S.C.-COMP.	PRIVACY	WOOD	
D	3'-0"	6'-8"	1 3/4"	3	S.C.-COMP.	PASSAGE	WOOD	LOUVERED
E	3'-0"	6'-8"	1 3/4"	2	S.C.-COMP.	PASSAGE	WOOD	
F	2'-6"	6'-8"	1 3/4"	2	S.C.-COMP.	PASSAGE	WOOD	

DOOR TYPES		GENERAL NOTES	
		A.	FINAL DOOR SELECTION BY OWNER.
		B.	INTERIOR DOOR AND WINDOW CASINGS TO BE 2-1/2" WIDE.
		C.	ALL FINAL FINISHES TO BE SELECTED BY OWNER.
		D.	CASEWORK FINISHES TO BE FINALIZED BY OWNER.

WINDOW SCHEDULE							
NO.	SIZE			TYPE	MATERIAL	GLAZING	REMARKS
	WIDTH	HEIGHT	HEAD HT.				
A	2'-6"	5'-0"	8'-0"	D.H.	VNLYL	LOW-E	
B	5'-0"	5'-0"	8'-0"	D.H.	VNLYL	LOW-E	
C	6'-0"	5'-0"	8'-0"	D.H.	VNLYL	LOW-E	EGRESS
D	2'-6"	2'-6"	8'-0"	FIXED	VNLYL	LOW-E	

WINDOW TYPES			

GENERAL NOTES	
A.	PROVIDE SAFETY GLAZING IN HAZARDOUS LOCATION. (R308.4)
B.	PROVIDE EGRESS WINDOWS IN ALL SLEEPING SPACES


ROOM FINISH SCHEDULE						
ROOM NAME	FLOOR	BASE	WALLS	CEILING TYPE	HEIGHT (AFF)	REMARKS
RESIDENTIAL ENTRY	LVT	MDF	P-GWB	P-GWB	9'-0"	
KITCHEN	LVT	MDF	P-GWB	P-GWB	9'-0"	
LIVING/DINING	LVT	MDF	P-GWB	P-GWB	9'-0"	
BEDROOM	LVT	MDF	P-GWB	P-GWB	9'-0"	
BEDROOM CLOSET	LVT	MDF	P-GWB	P-GWB	9'-0"	
BATH	LVT	MDF	P-GWB	P-GWB	9'-0"	
LAUNDRY/MECH. CLOSET	LVT	MDF	P-GWB	P-GWB	9'-0"	
EXIST. UTILITY	EXISTING	EXISTING	EXISTING	GWB	9'-0"	
LEASING OFFICE	EXISTING	EXISTING	EXISTING	P-GWB	9'-0"	
EXIST. BATH @ OFFICE	EXISTING	EXISTING	EXISTING	P-GWB	9'-0"	

GENERAL NOTES:		ROOM FINISH KEY	
A.	WALLS TO BE PAINTED GYPSUM WALL BOARD THROUGHOUT. PAINT SHEEN TO BE 'PEARL (SATIN)'. B. CEILINGS TO BE PAINTED GYPSUM WALLBOARD WITH SMOOTH FINISH. PAINT SHEEN TO BE 'EGGSHELL'. C. PAINTED WOOD WALL BASE THROUGHOUT. PAINT SHEEN TO BE 'SEMI-GLOSS'. D. ALL FINAL FINISHES TO BE SELECTED BY OWNER.	ABBREVIATION:	OPEN TO STRUCTURE
		CPT	CARPET
		VCT	VINYL COMPOSITION TILE
		LVT	LUXURY VINYL TILE FLOORING
		CONC.	FINISHED CONCRETE
		S-CONC	SEALED CONCRETE
		RB	RUBBER BASE
		MDF	MDF BASE
		P-GWB	PAINTED GYPSUM WALLBOARD
		GWB	GYPSUM WALLBOARD, UNFINISHED

- GENERAL FLOOR PLAN NOTES:**
- ALL DIMENSIONS ARE TO FACE OF FRAMING OR CENTER OF STRUCTURE OR OPENING, U.N.O.
 - ALL INTERIOR PARTITION WALLS SHALL BE 2X4'S AT 16" O.C. W/ 1/2" GWB BOTH SIDES W/ SOUND ATTENUATION BATH, U.N.O.
 - EXTEND ALL GYPSUM WALL BOARD (G.W.B.) TO FRAMING ABOVE, U.N.O.
 - PROVIDE ALL NECESSARY TEMPORARY SUPPORT FOR WALLS, FLOORS, AND ROOFS PRIOR TO COMPLETION OF PERMANENT VERTICAL AND LATERAL LOAD SYSTEMS.
 - PROVIDE ALL NECESSARY PERMANENT SUPPORT FOR CABINETS, SHELVING, FIXTURES, ETC.
 - PROVIDE SOUND ATTENUATION BLANKETS IN ALL INTERIOR BEDROOM, BATHROOM, MECH. ROOM, AND LAUNDRY ROOM WALLS.
 - PROVIDE BLOCKINGS FOR THE FUTURE INSTALLATION OF GRAB BARS, AND SHOWER SEATS AT WATER CLOSET, BATHUBS, AND SHOWER AT TYPE S UNIT.

- FLOOR PLAN KEY NOTES:**
- NEW STACKED WASHER & DRYER
 - HANGING ROD & SHELF
 - FIBERGLASS SHOWER W/WALL SURROUND W/ SHOWER CURTAIN ROD
 - 34" H X 36" W VANITY W/SINK AND WALL MIRROR
 - WATER CLOSET
 - TOILET ACCESSORIES: TOWEL BAR AND TOILET PAPER DISPENSER
 - 24" W UNDERCOUNTER DISHWASHER
 - 36" W SINK W/GARBAGE DISPOSAL
 - 36" W STOVE WITH RANGE HOOD ABOVE
 - 36" W REFRIGERATOR
 - 36" H COUNTERTOP
 - 12" D UPPER WALL CABINETS
 - 24" D BASE CABINETS
 - TALL CABINET
 - FURNACE
 - ELECTRICAL PANEL
 - WATER HEATER
 - WASHER CONNECTION BOX
 - HANDRAIL
 - ROOF LINE BELOW, TYP.
 - 1-HOUR SEPARATION WALL: DOUBLE 2X4 W/ 1" AIR GAP, SOUND BATT INSULATION AND 5/8" TYPE 'X' GWB, EACH SIDE. REF. 03/A3.1
 - PORCH COLUMN, SEE ELEVATIONS
 - WALL SCONCE (SEAGULL DARK SKY BARN LIGHT, OR EQ.)
 - PARTIAL HEIGHT WALL
 - 34" H X 48" W VANITY W/SINK AND WALL MIRROR
 - 36" X 48" SHOWER

<NORTH



DOOR SCHEDULE							
NO.	SIZE		THICK.	TYPE	MATERIAL	FRAME	REMARKS
	WIDTH	HEIGHT					
A	3'-0"	7'-0"	1 3/8"	1	FIBER-GLASS	ENTRY	HINGE PIN AUTO-CLOSER
B	2'-8"	6'-8"	1 3/4"	2	S.C.-COMP.	PRIVACY	WOOD
C	2'-6"	6'-8"	1 3/4"	2	S.C.-COMP.	PRIVACY	WOOD
D	3'-0"	6'-8"	1 3/4"	3	S.C.-COMP.	PASSAGE	WOOD / LOUVERED
E	3'-0"	6'-8"	1 3/4"	2	S.C.-COMP.	PASSAGE	WOOD
F	2'-6"	6'-8"	1 3/4"	2	S.C.-COMP.	PASSAGE	WOOD

DOOR TYPES		GENERAL NOTES	
		A.	FINAL DOOR SELECTION BY OWNER.
		B.	INTERIOR DOOR AND WINDOW CASINGS TO BE 2-1/2" WIDE.
		C.	ALL FINAL FINISHES TO BE SELECTED BY OWNER.
		D.	CASEWORK FINISHES TO BE FINALIZED BY OWNER.

WINDOW SCHEDULE							
NO.	SIZE		HEAD HT.	TYPE	MATERIAL	GLAZING	REMARKS
	WIDTH	HEIGHT					
A	2'-6"	5'-0"	8'-0"	D.H.	VINYL	LOW-E	
B	5'-0"	5'-0"	8'-0"	D.H.	VINYL	LOW-E	
C	6'-0"	5'-0"	8'-0"	D.H.	VINYL	LOW-E	EGRESS
D	2'-6"	2'-6"	8'-0"	FIXED	VINYL	LOW-E	

WINDOW TYPES			

GENERAL NOTES
 A. PROVIDE SAFETY GLAZING IN HAZARDOUS LOCATION. (R308.4)
 B. PROVIDE EGRESS WINDOWS IN ALL SLEEPING SPACES

ROOM FINISH SCHEDULE						
ROOM NAME	FLOOR	BASE	WALLS	CEILING	HEIGHT (AFF)	REMARKS
RESIDENTIAL ENTRY	LVT	MDF	P-GWB	P-GWB	9'-0"	
KITCHEN	LVT	MDF	P-GWB	P-GWB	9'-0"	
LIVING/DINING	LVT	MDF	P-GWB	P-GWB	9'-0"	
BEDROOM	LVT	MDF	P-GWB	P-GWB	9'-0"	
BEDROOM CLOSET	LVT	MDF	P-GWB	P-GWB	9'-0"	
BATH	LVT	MDF	P-GWB	P-GWB	9'-0"	
LAUNDRY/MECH. CLOSET	LVT	MDF	P-GWB	P-GWB	9'-0"	
EXIST. UTILITY	EXISTING	EXISTING	EXISTING	GWB	9'-0"	
LEASING OFFICE	EXISTING	EXISTING	EXISTING	P-GWB	9'-0"	
EXIST. BATH @ OFFICE	EXISTING	EXISTING	EXISTING	P-GWB	9'-0"	

GENERAL NOTES:
 A. WALLS TO BE PAINTED GYPSUM WALL BOARD THROUGHOUT. PAINT SHEEN TO BE 'PEARL (SATIN)'.
 B. CEILINGS TO BE PAINTED GYPSUM WALLBOARD WITH SMOOTH FINISH. PAINT SHEEN TO BE 'EGGSHELL'.
 C. PAINTED WOOD WALL BASE THROUGHOUT. PAINT SHEEN TO BE 'SEMI-GLOSS'.
 D. ALL FINAL FINISHES TO BE SELECTED BY OWNER.

ROOM FINISH KEY
 ABBREVIATION: OPEN TO STRUCTURE
 CPT CARPET
 VCT VINYL COMPOSITION TILE
 LVT LUXURY VINYL TILE FLOORING
 CONC FINISHED CONCRETE
 S-CONC SEALED CONCRETE
 RB RUBBER BASE
 MDF MDF BASE
 P-GWB PAINTED GYPSUM WALLBOARD
 GWB GYPSUM WALLBOARD, UNFINISHED

GENERAL FLOOR PLAN NOTES:
 A. ALL DIMENSIONS ARE TO FACE OF FRAMING OR CENTER OF STRUCTURE OR OPENING, U.N.O.
 B. ALL INTERIOR PARTITION WALLS SHALL BE 2X4S AT 16" O.C. W/ 1/2" GWB BOTH SIDES W/ SOUND ATTENUATION BATH U.N.O.
 C. EXTEND ALL GYPSUM WALL BOARD (G.W.B.) TO FRAMING ABOVE U.N.O.
 D. PROVIDE ALL NECESSARY TEMPORARY SUPPORT FOR WALLS, FLOORS, AND ROOFS PRIOR TO COMPLETION OF PERMANENT VERTICAL AND LATERAL LOAD SYSTEMS.
 E. PROVIDE ALL NECESSARY PERMANENT SUPPORT FOR CABINETS, SHELVING, FIXTURES, ETC.
 F. PROVIDE SOUND ATTENUATION BLANKETS IN ALL INTERIOR BEDROOM, BATHROOM, MECH. ROOM, AND LAUNDRY ROOM WALLS.
 G. PROVIDE BLOCKINGS FOR THE FUTURE INSTALLATION OF GRAB BARS, AND SHOWER SEATS AT WATER CLOSET, BATHTUBS, AND SHOWER AT TYPE B UNIT.

- FLOOR PLAN KEY NOTES:
- 1 NEW STACKED WASHER & DRYER
 - 2 HANGING ROD & SHELF
 - 3 FIBERGLASS SHOWER W/WALL SURROUND W/ SHOWER CURTAIN RAIL
 - 4 34" H X 36" W VANITY W/SINK AND WALL MIRROR
 - 5 WATER CLOSET
 - 6 TOILET ACCESSORIES: TOWEL BAR AND TOILET PAPER DISPENSER
 - 7 24" W UNDERCOUNTER DISHWASHER
 - 8 36" W SINK W/GARBAGE DISPOSAL
 - 9 36" W STOVE WITH RANGE HOOD ABOVE
 - 10 36" W REFRIGERATOR
 - 11 36" H COUNTERTOP
 - 12 12" D UPPER WALL CABINETS
 - 13 24" D BASE CABINETS
 - 14 TALL CABINET
 - 15 FURNACE
 - 16 ELECTRICAL PANEL
 - 17 WATER HEATER
 - 18 WASHER CONNECTION BOX
 - 19 HANDRAIL
 - 20 ROOF LINE BELOW TYP.
 - 21 1-HOUR SEPARATION WALL: DOUBLE 2X4 W/ 1" AIR GAP, SOUND BATT INSULATION AND 5/8" TYPE 'X' GWB, EACH SIDE, REF. 03A1.1
 - 22 PORCH COLUMN, SEE ELEVATIONS
 - 23 WALL SCONCE (SEAGULL DARK SKY BARN LIGHT, OR EQ.)
 - 24 PARTIAL HEIGHT WALL
 - 25 34" H X 48" W VANITY W/SINK AND WALL MIRROR
 - 26 36" X 48" SHOWER



EAST ELEVATION
SCALE: 1/4" = 1'-0"



SOUTH ELEVATION
SCALE: 1/4" = 1'-0"



WEST ELEVATION
SCALE: 1/4" = 1'-0"



NORTH ELEVATION
SCALE: 1/4" = 1'-0"



Jacqueline Scanlan <scanlanj@bloomington.in.gov>

506 East Wylie Proposed Duplex Construction

Amy Stupka <amyrunswithhorses@gmail.com>

Thu, May 9, 2024 at 3:52 PM

To: scanlanj@bloomington.in.gov, planning@bloomington.in.gov

Greetings Jackie and all,

My husband and I live north of the proposed construction site, and have some concerns related to the proposed 6 bedroom, 6 bathroom duplex construction. Our primary concern is for the safety of the neighborhood related to traffic and parking congestion on Wylie. Even now, with that lot currently vacant, cars frequently fill the narrow road creating a one-way street. Our neighbor accross Wylie frequently has difficulty backing out of his driveway, and it is difficult for pedestrians to see what is coming without stepping into the road. We are very concerned that the addition of 6 more cars to this small area of road will create an unsafe situation. Even though 4 parking spaces will be part of the plan, it seems clear that even the addition of a minimum of 2 more cars coming is a concern.

Another major concern is the existence of a magnificent sycamore tree that beautifies the intersection and neighborhood surroundings. Such trees exemplify the beauty of this special neighborhood as well as provide a nesting location for hawks and other wildlife adding to the character. We expressed our concerns to the contractor directly, and feel that he was very receptive to the concerns, but want to make sure that planners are also aware of them.

Is it possible to restrict street parking on Wylie to residents? These restrictions could help alleviate the current problem as well as help prevent worsening the situation with the addition of as many as 6 more drivers.

Thank you very much for your attention to these concerns.

Sincerely,

Amy Stupka
814 South Henderson Street
828-215-6098



Eric Greulich <greulice@bloomington.in.gov>

Fwd: 506 E. Wylie Duplex Proposal

Jacqueline Scanlan <scanlanj@bloomington.in.gov>
To: Eric Greulich <greulice@bloomington.in.gov>

Fri, May 3, 2024 at 3:16 PM

I'm sure you'll get this from the front, but fyi!

Jackie

----- Forwarded message -----

From: **ian woollen** <iwool@hotmail.com>

Date: Fri, May 3, 2024 at 2:47 PM

Subject: RE: 506 E. Wylie Duplex Proposal

To: planning@bloomington.in.gov <planning@bloomington.in.gov>, scanlanj@bloomington.in.gov <scanlanj@bloomington.in.gov>, isabel.piedmont@bloomington.in.gov <isabel.piedmont@bloomington.in.gov>, caylan.m.evans@gmail.com <caylan.m.evans@gmail.com>

Hi - I was at the BPNA meeting last night and heard the presentation from architect/developer Caylan Evans for a new duplex at 506 E. Wylie.

I just want to register my concern that the arrangement of 6 beds with 6 baths seems obviously aimed at the student market, rather than a family tenant. Cutting the number of bathrooms from 3 down to 2 in each unit would allow for a larger master bedroom and be more likely to attract a family tenant.

Thanks for your time.

Regards,

Ian Woollen

1106 S. Washington

May 17, 2024

Dear Members of the Bloomington Zoning Appeals:

I am writing to ask you to reject the proposed infill project at 506 E. Wylie. The project is too big to maintain a consistency of style with the existing mid-century style houses on Wylie. It's a challenge to fit 6 bedrooms and 6 bathrooms in any house. Also, the proposed project does not meet design mandates of the UDO (see below).

The proposed, large, multi-gabled roof lines, vertical roof pitch and orientation of the building does not resemble the established style of the established houses on Wylie. The houses on Wylie, from Henderson to Lincoln, were built in the early 1950s and are exceptionally consistent and harmonious in the roof pitch, porch depth, front building setbacks, massing, shape, size, and design with the broad side of the house facing Wylie. In this letter I have included images of all the houses on the south side of Wylie.

At our last Bryan Park Neighborhood Association meeting, the developer was asked how he was going to address this design issue. He did say it was a problem but did not offer a solution. At the Elm Heights neighborhood meeting, the developer said he was going to revise the plans. Several neighbors requested a readable digital file because the document he brought was so small that many of the numbers were unreadable. At this date, we have not received any.

The Bryan Park houses are generally more affordable than most of the neighborhoods in Bloomington. We have seen an uptick of developers purchasing property in the neighborhood for the land itself. The developer said that the price range for the duplex was going to be approximately \$1,000 per bedroom.

One of the goals for infill projects in the Comprehensive Plan is to ensure all land development activity makes a positive and lasting community contribution. This project will not meet this goal.

Sincerely,
Jan Sorby

From the UDO:

Pg. 89: Chapter 20.03, Use Regulations Design: In the R1, R2, R3, and R4 zoning districts the following shall apply: Each unit in a newly constructed duplex dwelling shall have a separate exterior entrance facing a public or private street. The following design elements of the duplex dwelling shall be similar in general shape, size, and design with the majority of existing single-family or duplex structures on the same block face on which it is located: Roof pitch; Front porch width and depth; Front building setback; and Vehicle parking access (i.e., front-, side-, or rear-access garage or parking area). No duplex dwelling structure shall contain more than six bedrooms total. Each individual dwelling unit shall have separate utility meters.

Pg. 18: R3: Residential Small Lot Purpose: The R3 district is intended to protect and enhance established residential neighborhoods by increasing the viability of owner-occupied and affordable dwelling units through small-lot subdivisions, accessory dwelling units, and property improvements compatible with surrounding development patterns. The conversion of existing housing stock to more intense land uses is discouraged.

From the Comprehensive Plan

Pg. 16: Housing & Neighborhoods Objective: Overall this chapter supports the following Vision Statement principles: 11. Ensure all land development activity makes a positive and lasting community contribution.

Pg. 60: Housing Trends and Issues: Most core neighborhoods are stable but are trending towards a lower percentage of new single-family homes. With greater density in the city comes the challenge to preserve neighborhood character and the opportunity to strengthen neighborhoods by developing small commercial nodes as community gathering places. Existing core neighborhoods should not be the focus of the city's increasing density.

Pg. 62: Many neighborhoods in Bloomington were developed during a span from the late 1800s through the 1950s. These older homes are generally well built and have distinctive architectural features. They also often have smaller footprints compared to more modern homes. As seen in communities across the nation, this can lead to the phenomenon of people purchasing these homes purely for their desirable urban locations and tearing down the existing structure to make way for a brand-new home, which often features an excessively large footprint and a contemporary architectural style. Such homes may not fit into the period context of their surroundings and can negatively impact the fabric of the entire neighborhood. Unchecked, this practice can lead to the large-scale loss of a community's historic integrity and also the loss of affordable housing stock.

**All the Houses located on the South side of East Wylie,
from Henderson to Lincoln**



430 E Wylie



424 E Wylie



414 E Wylie



412 E Wylie



408 E Wylie



400 E Wylie



318 E Wylie

The block faces of east Wylie from Henderson to Lincoln streets consist of split-level and small ranch style houses, built in the early 1950s.

The houses are exceptionally consistent in shape, size, and design with the broad side of the house facing the street. The roof pitches, porch depths and widths, front building setbacks, and massing are uniform and harmonious.